

- Wide 0.004Hz to 4MHz Frequency range
- CW/Triggered and Gated modes
- Sweep output and VCG input
- 1000:1 linear sweep and 10,000:1 frequency log sweep widths
- Settable Sweep Start and Stop Frequencies
- Low Distortion sinewave

**B8400**

## SPECIFICATIONS

### Frequency Characteristics

**Frequency Range:** 0.004Hz to 4MHz in 7 ranges

**Ranges:** x1, x10x, x100, x1K, x10k, x100k, x1M

**Dial Accuracy:** 5% of full scale

### Output Characteristics

**Waveforms:** Sine, Square, Triangle, TTL Pulse

#### High output:

Amplitude: 15mV to 10V (into 50Ω)

DC Offset: 0 to ±5 into 50Ω

Impedance: 50Ω

Attenuator: 30dB variable

#### Low Output:

Amplitude: 0 to 1V (into 50Ω)

DC Offset: 0 to ±0.5 (into 50Ω)

Impedance: 50Ω

Attenuator: 30dB variable

### Sine Wave

**Frequency Range:** 0.004Hz to 4MHz

#### Flatness:

±2.0 % (0.004Hz to 400KHz)

±10% (400KHz to 4MHz)

#### Harmonic Distortion:

< 0.5 % on the 1K and 10K range

1% on the x1, x10, x 100 and x100K ranges

25dBc on the x1M range

### Square Wave

**Frequency Range:** 0.004Hz to 4MHz

**Rise/Fall Time:** < 50ns into 50Ω (High output terminals)

**Symmetry:** ±1% to 100KHz, ±5% to 4MHz

### Triangle

**Linearity:** > 99% to 200KHz

### Operating modes

CW, Triggered, Gated, Sweep, Manually Triggered

**Trigger/Gate input level:** TTL

**Trigger/Gate Frequency Range:** to 4MHz Max.

**Trigger/gate minimum pulse width:** < 50ns

### Sweep

**Type:** Linear and Log

**Sweep Time:** 30ms to 60 seconds continuously variable

**Sweep width:** 1:1,000 linear; 1:10,000 log continuously variable. Sweep start and stop frequencies may be set with the Freq dial and the Freq. Stop control.

### Outputs

**Sync:** TTL level

**GCV:** output proportional to the selected frequency, 0 to -5V

**Sweep:** 4V P-P; **Impedance:** 600Ω

### VCG Input

**Input Voltage:** 0 to ±4V P-P will cause a 1:1,000 frequency change (linear) and 1:10,000 (Log)

**Input Impedance:** 2KΩ

### General Specifications

**Operating Temperature:** 0 to 50°C (32 to 120°F)

**Dimensions:** 3.5" (H) x 11.4" (W) x 10.6" (D)

**Weight:** 5 lbs

**AC line Voltage:** 120/220V, 50/60Hz

**Accessories:** Manual, Line cord, BNC cable

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Protek:](#)

[B8400](#)