

9510 Multi-Conductor - Computer Cable for EIA RS-232 Applications

**Description:**

24 AWG stranded (7x32) TC conductors, semi-rigid PVC insulation, twisted pairs, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain Wire (continued), PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
10	24	7x32	TC - Tinned Copper

Insulation**Insulation Material:**

Insulation Material
S-R PVC - Semi-Rigid Polyvinyl Chloride

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire	Conductor Material
24	7x32		TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.368 in.

Pair**Pair Color Code Chart:**

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +80°C
Non-UL Temperature Rating:	80°C (UL AWM Style 2464)
Bulk Cable Weight:	69 lbs/1000 ft.

9510 Multi-Conductor - Computer Cable for EIA RS-232 Applications

Max. Recommended Pulling Tension:	110 lbs.
Min. Bend Radius (Install)/Minor Axis:	3.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
AWM Specification:	UL Style 2464 (300 V 80°C)
CSA Specification:	AWM I A
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 FT4 Loading
C(UL) Flame Test:	FT4

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

30

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

50

Nominal Velocity of Propagation:

VP (%)

60

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

24

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

16.5

Max. Operating Voltage - UL:

Voltage

300 V RMS (UL AWM Style 2464)

Max. Recommended Current:

Current

1.1 Amps per conductor @ 25°C

9510 Multi-Conductor - Computer Cable for EIA RS-232 Applications

Put Ups and Colors:


Item #	Putup	Ship Weight	Color	Notes	Item Desc
9510 060100	100 FT	7.600 LB	CHROME		10 PR #24 PVC FS PVC
9510 0601000	1,000 FT	75.000 LB	CHROME	C	10 PR #24 PVC FS PVC
9510 060500	500 FT	39.000 LB	CHROME	C	10 PR #24 PVC FS PVC

Notes:

C = CRATE REEL PUT-UP.

Overall Beldfoil® Shield

Computer Cables for EIA RS-232 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire (continued)																		
Semi-rigid PVC Insulation • Chrome PVC Jacket																		
 Shorting Fold	9506	NEC:	6	See	100	30.5	5.0	2.3	24.0Ω/M'	16.0Ω/M'	.289	7.34	75	60%	30	98	50	164
		CMG		Chart 3	U-500	U-152.4	23.0	10.4	78.7Ω/km	52.5Ω/km								
		CEC:		(Tech Info Section)	500	152.4	25.0	11.3										
	CMG FT4			U-1000	U-304.8	45.0	20.4							For Plenum version of 9506, see 82506.				
				1000	304.8	47.0	21.4											
	9507	NEC:	7	See	100	30.5	5.5	2.5	24.0Ω/M'	16.5Ω/M'	.294	7.47	75	60%	30	98	50	164
		CMG		Chart 3	U-500	U-152.4	25.0	11.3	78.7Ω/km	54.1Ω/km								
		CEC:		(Tech Info Section)	500	152.4	27.0	12.3										
	CMG FT4			U-1000	U-304.8	49.0	22.2											
			1000	304.8	51.0	23.1												
9508	NEC:	8	See	100	30.5	6.3	2.9	24.0Ω/M'	16.5Ω/M'	.324	8.23	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	30.5	13.8	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	60.0	27.2											
CMG FT4																		
9509	NEC:	9	See	100	30.5	6.9	3.1	24.0Ω/M'	16.5Ω/M'	.334	8.48	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	33.5	15.2	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	67.0	30.4											
CMG FT4														For Plenum version of 9509, see 82509.				
9510	NEC:	10	See	100	30.5	7.5	3.4	24.0Ω/M'	16.5Ω/M'	.368	9.34	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	36.5	16.6	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	74.0	33.6											
CMG FT4																		
9515	NEC:	15	See	100	30.5	10.4	4.7	24.0Ω/M'	16.5Ω/M'	.417	10.6	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	52.0	23.6	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	102.0	46.4											
CMG FT4																		
9519	NEC:	19	See	100	30.5	12.8	5.8	24.0Ω/M'	16.5Ω/M'	.448	11.4	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	61.5	28.0	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	122.0	55.5											
CMG FT4																		
9525	NEC:	25	See	100	30.5	16.0	7.3	24.0Ω/M'	16.5Ω/M'	.503	12.8	75	60%	30	98	50	164	
	CMG		Chart 3	500	152.4	79.5	36.1	78.7Ω/km	54.1Ω/km									
	CEC:		(Tech Info Section)	1000	304.8	155.0	70.3											
CMG FT4																		
9550	NEC:	50	Request	100	30.5	31.9	14.5	24.0Ω/M'	15.2Ω/M'	.708	18.0	75	60%	30	98	50	164	
	Technical		500†	152.4	153.5	69.8	78.7Ω/km	49.9Ω/km										
	Bulletin		1000†	304.8	311.0	141.4												
CMG FT4		T/8-4																

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

†Spools are one piece, but length may vary -0% to +20% from length shown.