


DO NOT
SCALE FROM
THIS PRINT



BSS-XXX-01-X-D-XX


No OF POSITIONS
-025, -050, -075,
*-100, *-125, *-150
(PER ROW)

LEAD STYLE
-01




PLATING SPECIFICATION
-L: LIGHT SELECTIVE GOLD W/ MATTE TIN TAILS (USE C-126-21-L) (SEE NOTE 9 & 11)
-F: FLASH SELECTIVE GOLD W/ MATTE TIN TAILS (USE C-126-21-F) (SEE NOTE 7,9 & 11)
-H: HEAVY GOLD (USE C-126-21-H) (SEE NOTE 11)
-C: ELECTRO-POLISHED SELECTIVE (USE C-126-21-C. SEE NOTE 11)

OPTION
-A: ALIGNMENT PINS
(USE BSS-XXX-01-D-A)
-LC: LOCKING CLIPS
(USE LC-08-TM-01)
-TR: TAPE & REEL (100 POS MAX)

ROW SPECIFICATION
-D: DOUBLE (USE BSS-XXX-01-D)




-LC: LOCKING CLIP OPTION SHOWN



-A: ALIGNMENT PIN OPTION SHOWN

TABLE 1	
No OF POS	COPLANARITY
-025 THRU -075	.0040[.102]
-100 THRU -150	.0060[.152]

TUBE VIEW
(PARTS TO BE LOADED WITH POSITION #1 IN
SAME DIRECTION AS ARROW ON TUBE)



TUBE: PT-1-24-03-78
PLUG: TP-03

NOTES:

1. REPRESENTS A CRITICAL DIMENSION.
2. NOTE DELETED.
3. BURR ALLOWANCE: .0015 [.038] MAX.
4. MINIMUM PUSHOUT FORCE: .5 LB.
5. NOTE DELETED.
6. MAX VARIANCE OF .002[.51].
7. -L PLATING CAN BE SUBSTITUTED FOR -F PLATING.
8. RIBBED SIDEWALLS AT SAMTEC DISCRETION.
9. MAY SUBSTITUTE C-126-01-X FOR C-126-21-X.
10. FOR NEW APPLICATIONS REQUIRING THESE POSITIONS, PLEASE CONTACT SAMTEC INTERCONNECT PROCESSING GROUP.
11. -100, -125 AND -150 POSITION PARTS USE C-269-11-X. DO NOT SUB C-126-XX-X.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES.
TOLERANCES ARE:
DECIMALS ANGLES
.XX: ±.01[.3]
.XXX: ±.005[.13]
.XXXX: ±.0020[.051]

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC, INC. AND SHALL NOT BE REPRODUCED
OR TRANSFERRED TO OTHER DOCUMENTS OR
DISCLOSED TO OTHERS OR USED FOR ANY
PURPOSE OTHER THAN THAT WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.

MATERIAL: DO NOT SCALE DRAWING
INSULATOR: LCP, COLOR: BLACK, FLAMMABILITY RATING: UL94V0
CONTACT: PHOS BRONZE

DESCRIPTION:
.635mm DOUBLE ROW SOCKET ASSEMBLY

DWG. NO. **BSS-XXX-01-X-D-XX**

BY: DEAN P 06/23/1999 SHEET 1 OF 1

samtec

520 PARK EAST BLVD. NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322