


646752-1 Product Details

Share Print Email

- Quick Links
- Check Pricing & Availability
 - Search for Tooling
 - Product Feature Selector
 - Contact Us About This Product



646752-1

2mm Hard Metric PCB Mount Connectors (Z-PACK 2mm HM)

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Connector Assembly
- Connector Style = Plug
- Type = Type A
- Interface Type = 2mm HM

View all Features

TE Internal Number: 646752-1
Pending Obsolescence
Search for Replacement Parts

Add to My Part List Request Sample Find Similar Products Buy Product

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none">MALE ASSEMBLY, Z-PACK 2mm HM, TYPE A (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none">None Available <p>Product Specifications:</p> <ul style="list-style-type: none">Z-Pack 2 mm HM CONNECTORS (PDF, English) <p>Application Specifications:</p> <ul style="list-style-type: none">Z-PACK 2mm HM Interconnection System for Board-to-Bo... (PDF, English) <p>Instruction Sheets:</p> <ul style="list-style-type: none">None Available <p>CAD Files:</p> <ul style="list-style-type: none">None Available	<p>Additional Information:</p> <ul style="list-style-type: none">Product Line Information <p>Related Products:</p> <ul style="list-style-type: none">Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none">Product Type = ConnectorConnector Type = Connector AssemblyPCB Mounting Orientation = Vertical <p>Mechanical Attachment:</p> <ul style="list-style-type: none">Board Mount = Fixed BoardModule Length (mm [in]) = 39.88 [1.571]Crosstalk Version = StandardFront Mating Level = Level 1 <p>Electrical Characteristics:</p> <ul style="list-style-type: none">Shielded = No <p>Termination Features:</p> <ul style="list-style-type: none">Interface Type = 2mm HMTermination End Plating = Tin-Lead <p>Body Features:</p> <ul style="list-style-type: none">Type = Type ANumber of Rows = 5Number of Positions = 85Grounding Contact = WithoutRows Loaded = A, B, D, E, C <p>Contact Features:</p> <ul style="list-style-type: none">Contact Configuration = ACTION PIN Post, SignalFeedthrough Post Length (mm [in]) = 3.70 [0.145], 16.00 [0.630]CompactPCI = NoContact Plating, Mating Area, Material = Conforms to IEC 61076-4-101 Performance Level 2Contact Style = Short TailContact Base Material = Phosphor BronzeFeedthrough Post Length (Rows A-E) (mm [in]) = 8.20 [0.323]	<p>Housing Features:</p> <ul style="list-style-type: none">Connector Style = PlugMating Alignment = WithMating Alignment Type = Multi-Purpose CenterHousing Color = GrayHousing Material = Polyester GFUL Flammability Rating = UL 94V-0 <p>Industry Standards:</p> <ul style="list-style-type: none">RoHS/ELV Compliance = RoHS compliant, ELV compliantLead Free Solder Processes = Not relevant for lead free processRoHS/ELV Compliance History = Always was RoHS compliant <p>Packaging Features:</p> <ul style="list-style-type: none">Packaging Quantity = 13 <p>Other:</p> <ul style="list-style-type: none">Brand = AMP