




.100" X .100" LATCH/EJECTOR, STRAIGHT AND RIGHT ANGLE



-X0XX
HEADER WITHOUT LATCH EJECTOR



-X2XX
HEADER WITH SHORT LATCH EJECTOR
FOR 3M SOCKETS WITHOUT STRAIN RELIEF



-X3XX
HEADER WITH LONG LATCH EJECTOR
FOR 3M SOCKETS WITH STRAIN RELIEF

X3XXX - XXXXXX

N= HIGH TEMP BLACK (PCT)/(RB PLATING REQ'D)

3M PART NUMBER: -
(SEE TABLE 1)

PIN CONFIGURATION: _____
1 = RIGHT ANGLE SOLDER TAILS
2 = STRAIGHT SOLDER TAILS

- PLATING:
RB = 200 μ " [5.08 μ m] MATTE TIN TAILS

```

- TAIL:
02 = FOR .062 [ 1.57 ] THICK BOARD
03 = FOR .094 TO .125 [ 2.39 TO 3.18 ] THICK BOARD

```

```
- LATCH/EJECTOR SYSTEM:
0 = NO LATCH/EJECTOR INSTALLED
2 = SHORT ROLL PIN LATCH/EJECTORS
3 = LONG ROLL PIN LATCH/EJECTORS
```

- * MILITARY (WITH 3M'S N3518 POLARIZING KEY) AND CENTERBUMP POLARIZATION.
- * LOW PROFILE.
- * OPTIONAL EJECTOR LATCHES.
- * MOUNTING HOLES FOR SECURING HEADER TO BOARD.
- * THREE WALL SHROUD PROVIDES DESIGN FLEXIBILITY.
- * STRAIGHT, RIGHT ANGLE.
- * SOLDER TAIL OPTIONS.
- * OPTIONAL POLARIZING POSTS AVAILABLE.
- * HIGH TEMPERATURE INSULATOR SUITABLE FOR "NO LEAD" SOLDERING OPERATIONS.
- * SUITABLE FOR REFLOW SOLDERING USING "PASTE IN HOLE" TECHNIQUES.

2 PHYSICAL :

INSULATOR: HIGH TEMP GLASS FILLED POLYESTER (PCT)
MATERIAL: UL94V-0
FLAMMABILITY: BLACK
COLOR: COPPER ALLOY
CONTACT: PLATING:
MATERIAL: 50 μ "-150 μ " [1.27 μ m-3.81 μ m] NICKEL-OVERALL
PLATING: 30 μ " [0.76 μ m] AVG. GOLD
UNDER PLATING: (SEE ORDERING INFORMATION)
WIPING AREA: 3M LOGO, PART IDENTIFICATION NUMBER AND
SOLDER TAILS: ORIENTATION TRIANGLE
MARKINGS:

2 ELECTRICAL :

CURRENT RATING: 5.00A, 1 CONTACT POWERED
3.00A, 6 CONTACTS POWERED
1.75A, ALL CONTACTS POWERED
RATING CONDITIONS: EIA-364-070 METHOD 2, 30°C MAXIMUM
TEMPERATURE RISE, 20% DERATED. REFERENCE APPROPRIATE
3M PRODUCT SPECIFICATION FOR DETAILED CURRENT DERATING
CURVES.

INSULATION RESISTANCE: $>1 \times 10^9 \Omega$ AT 500 V_{DC}
WITHSTANDING VOLTAGE: 1,000V_{RMS} AT SEA LEVEL

2 ENVIRONMENTAL :

TEMPERATURE RATING: -55°C TO 105°C
PROCESS RATING: 260°C, PER J-STD-020C, SINGLE PASS
MOISTURE SENSITIVITY LEVEL: 1 (PER J-STD-020C SINGLE PASS)

DIMENSIONS: INCHES [MM]
[MM] IS REF. ONLY

DESIGN REFERENCE		NEXT ASSEMBLY	
NOTES CODES			
DIVISION		DIVISION CODE	
Interconnect Solutions		EMSD	
DO NOT SCALE DRAWING		TOLERANCE EXCEPT AS NOTED	
SCALE		INCHES	
		.0 ± .1 .00 ± .01 .000 ± .005 .0000 ± .0005	
THIRD ANGLE PROJECTION		MILLIMETERS	
INTERPRET PER ASME Y14.5 - 2018		.0 .00 .000 ±	
MAX. SURFACE ROUGHNESS		ANGLES ±	
☐ TAIL SURFACES ☒ MARKED ONLY			

L	115955	MAY 08,2024 REMOVE 05 WWT TAILS	JNC	FJR
K	97909	JUN 22,2021 REVISED ORDERING INFO	JNC	SAN
J	93619	JAN 07,2021 REMOVE TIN LEAD PLATE AND KINK TAILS	JNC	SAN
H	60056	MAR 06,2015 REVISE ORDERING NUMBER	JNC	RS
G	56068	AUG 05,2014 REVISED AND REDRAWN	JNC	RS
REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
DRFT	CAS TIGLIONE	DATE AUG 05,2014	MFG	DATE
CHKD		DATE	APPR. R. SCHERER	DATE SEP 05,2014
 © 3M COPYRIGHT 2024 This document and the information it contains are confidential and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.				
TITLE				
HEADER , 3-WALL , .100 X .100 LATCH/EJECTOR, STRAIGHT AND RA				
CAGE NUMBER	SIZE	DRAWING NO.	REV.	
MODEL	340	D78-5100-0771-5	L	
		DET.	SHT 1 OF 5	

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

UL[®]
US
UL FILE NO: E68080

3M™ THREE-WALL HEADER, 3000 SERIES

.100" X .100" LATCH/EJECTOR, STRAIGHT AND RIGHT ANGLE







TABLE 1							
PIN QTY.	3M PART NUMBER	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	POLARIZING NOTCHES	PIN QTY.
10	3793	1.26 [32.1]	1.105 [28.04]	.865 [21.97]	.71 [18.0]	BC	10
14	3314	1.46 [37.2]	1.305 [33.12]	1.065 [27.05]	.91 [23.1]	BC	14
16	3408	1.56 [39.7]	1.405 [35.66]	1.165 [29.59]	1.01 [25.6]	ABC	16
20	3428	1.76 [44.8]	1.604 [40.74]	1.365 [34.67]	1.21 [30.7]	ABC	20
26	3429	2.06 [52.4]	1.905 [48.36]	1.665 [42.29]	1.51 [38.3]	ABC	26
34	3431	2.46 [62.6]	2.305 [58.52]	2.065 [52.45]	1.91 [48.5]	ABC	34
40	3432	2.76 [70.2]	2.605 [66.14]	2.365 [60.07]	2.21 [56.1]	ABC	40
50	3433	3.26 [82.9]	3.105 [78.84]	2.865 [72.77]	2.71 [68.8]	ABC	50
60	3372	3.76 [95.6]	3.605 [91.54]	3.365 [85.47]	3.21 [81.5]	ABC	60
64	3764	3.96 [100.7]	3.805 [96.62]	3.565 [90.55]	3.41 [86.6]	ABC	64

TABLE 2						
3M PART NUMBER SUFFIX	CONTACT TAIL	DIM. "E"	PIN CROSS SECTION			DIM. "G"
-1XX2	.062 [1.57] THICK PC BOARD	.112 [2.84]	DIM. "F" .0245+/- .0005 [.622]	DIAGONALS .028+/- .001 [.71]	CORNER RADIUS .0075 REF. [.191]	.035+/- .003 [.89] SEE NOTE 5
-2XX2						
-1X03	.094 [2.39] TO .125 [3.18] THICK PC BOARD	.155 [3.94]	.0245+/- .0005 [.622]	.028+/- .001 [.71]	.0075 REF. [.191]	.035+/- .003 [.89]
-2X03						



3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

DESIGN REFERENCE		NEXT ASSEMBLY		
REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
DRFT	CASTIGLIONE	DATE	AUG 05,2014	MFS
CHKD		DATE		
DIVISION		DIVISION CODE		
Interconnect Solutions		EMSD		
DO NOT SCALE DRAWING		TOLERANCES EXCEPT AS NOTED		
THIRD ANGLE PROJECTION		INCHES		
INTERPRET PER ASME Y14.5 - 2018		MILLIMETERS		
MAX. SURFACE ROUGHNESS		CAGE NUMBER		
ALL SURFACES		DRAWING NO.		
MARKED ONLY		REV.		
		L		
		SHT 2 OF 5		


3M Center
St. Paul,
MN 55144

© 3M COPYRIGHT 2024
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.


HEADER, 3-WALL, .100 X .100 LATCH/EJECTOR, STRAIGHT AND RA

MODEL 3400

3M™ THREE-WALL HEADER, 3000 SERIES
.100" X .100" LATCH/EJECTOR, STRAIGHT AND RIGHT ANGLE



RECOMMENDED MOUNTING HOLE PATTERN
(STRAIGHT VERSION)



RECOMMENDED MOUNTING HOLE PATTERN
(RIGHT ANGLE VERSION)

PART CUSTOMIZATION


THIS SPEC SHEET DETAILS OUR STANDARD OFFERING.

3M HAS SEVERAL CAPABILITIES THAT CAN PROVIDE A PART TAILORED TO YOUR SPECIFIC NEEDS. ASK YOUR 3M SALES REPRESENTATIVE OR CUSTOMER SERVICE FOR MORE DETAILS.


BOTH SNAP-IN AND ROLL PIN LATCHES MAY BE ORDERED SEPARATELY. SNAP-IN AND ROLL PIN STYLE LATCHES ARE DIMENSIONALLY AND FUNCTIONALLY EQUIVALENT. IF ORDERING SNAP-IN OR ROLL PIN STYLE LATCHES SEPARATELY, PLEASE USE THE BELOW CHART.

MATERIAL	SHORT LATCH	LONG LATCH	LATCH STYLE	COLOR
HIGH TEMP. (PCT)	N3505-2B	N3505-3B	ROLL PIN	BLACK
HIGH TEMP (PPA)	N3505-30B	N3505-31B	SNAP-IN	BLACK

- * SELECTIVE PIN REMOVAL (ATA OR OTHER COMPATABILITY)
- * WIRE WRAP TAILS STYLE




LONG



SHORT

SNAP-IN LATCHES




NOTE:
SNAP-IN LATCHES CAN ONLY BE ORDERED SEPARATELY AND ARE THE CUSTOMERS RESPONSIBILITY TO INSTALL.

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373


POLARIZING POST



3M PART NO.	MATERIAL	COLOR
3201-4	LCP	BLACK

NOTE:
INSERT POST INTO ONE MOUNTING
HARDWARE HOLE ON BOTTOM OF HEADER.
SET POST TO PROTRUDE .115 [2.92]

POLARIZING KEY



3M PART NO.	MATERIAL	COLOR	DIM. "A"
N3518	LCP	BLACK	.02

NOTE:
#2216 B/A SCOTCHWELD CAN BE USED TO
ADHERE KEYS.


DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
XXXXXX	XXXXXX	1	ECO	MAY 08, 2024 REMOVE 05 WWT TAILS	JNC	FJR
XXXXXX	XXXXXX	2	ECO	JUN 22, 2021 REVISED ORDERING INFO	JNC	SAN
XXXXXX	XXXXXX	3	ECO	JAN 07, 2021 REMOVE TIN LEAD PLATE AND KINK TAILS	JNC	SAN
XXXXXX	XXXXXX	4	ECO	MAR 06, 2015 REVISE ORDERING NUMBER	JNC	RS
XXXXXX	XXXXXX	5	ECO	AUG 05, 2014 REVISED AND REDRAWN	JNC	RS
XXXXXX	XXXXXX	6	ECO	ISSUE DATE AND DESCRIPTION	JNC	RS
XXXXXX	XXXXXX	7	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	8	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	9	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	10	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	11	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	12	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	13	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	14	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	15	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	16	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	17	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	18	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	19	ECO	DATE 05, 2014	JNC	RS
XXXXXX	XXXXXX	20	ECO	DATE 05, 2014	JNC	RS

Division	Interconnect Solutions	Division Code	EMSD
DO NOT SCALE DRAWING	SCALE	TOLERANCES EXCEPT AS NOTED	
THIRD ANGLE PROJECTION		INCHES ±.1 ±.01 ±.005 ±.0002	
INTERPRET PER ASME Y14.5 - 2018		MILLIMETERS 0 ± ±.005 ±.0002	
MAX SURFACE ROUGHNESS ALL SURFACES MARKED ONLY		ANGLES ±	


TITLE	HEADER, 3-WALL, .100 X .100 LATCH/EJECTOR, STRAIGHT AND RA
CAGE NUMBER	D78-5100-0771-5
SIZE	L
DRAWING NO.	78-5100-0771-5
REV.	L
MODEL	3400
DET	YES
SHT	3 OF 5

3M™ THREE-WALL HEADER, 3000 SERIES
.100" X .100" LATCH/EJECTOR, STRAIGHT AND RIGHT ANGLE


MOUNTING HARDWARE




3341-5
(INSTALL FROM BOTTOM OF BOARD)
PANHEAD THREAD CUTTING SCREW:
#4-24 X 5/16"
TYPE: USA STD BT, FEDERAL B6
MATERIAL: STAINLESS STEEL



3341-6
HEX HEAD BOLT, NUT AND WASHER:
BOLT - #2-56 X 1/2"
MATERIAL: STAINLESS STEEL



3341-6
#2-56 NUT AND BOLT



#4-24 TYPE BT SELF THREADING SCREW
WHEN USING LATCHES, MAXIMUM LENGTH
OF SCREW IS .250 INCHES PLUS
THICKNESS OF THE BOARD.

3341-5

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

DESIGN REFERENCE		NEXT ASSEMBLY		REV		ECO		ISSUE DATE AND DESCRIPTION		DRFT	CHKD
ACCESS CODES				DRFT		DATE		MFG		DATE	
				CHKD		DATE		APPR. R. SCHERER		DATE SEP 05,2014	
DIVISION		DIVISION CODE				3M Center St. Paul, MN 55144		© 3M COPYRIGHT 2024 This document and the information it contains are 3M property and may be reproduced or further distributed without 3M permission, or used or altered in any other than for 3M authorized purposes. All rights reserved.			
Interconnect Solutions		EMSD									
DO NOT SCALE DRAWING		TOLERANCES EXCEPT AS NOTED									
				INCHES				TITLE HEADER, 3-WALL, .100 X .100 LATCH/ELECTOR, STRAIGHT AND RA			
THIRD ANGLE PROJECTION				.0		.1					
				.00		.01					
				.000		.005					
				.0000		.0002					
INTERPRET PER ASME Y14.5 - 2018				MILLIMETERS							
				.0		.1					
				.00		.01					
				.000		.005					
MAX SURFACE ROUGHNESS				ANGLES							
				.0		.1					
				.00		.01					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					
				.000		.005					

3M™ THREE-WALL HEADER, 3000 SERIES

.100" X .100" LATCH/EJECTOR, STRAIGHT AND RIGHT ANGLE

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: For industrial use only. Not intended, labeled or packaged for consumer sale or use.

3M Company
Electronics Materials Solutions Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753-5380
1-800-225-5373
www.3M.com/interconnect

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
http://www.3M.com/interconnect

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

L	115955	MAY 08,2024	JNC	FJR
K	97909	JUN 22,2021	JNC	SAN
J	93619	JAN 07,2021	JNC	SAN
H	60056	MAR 06,2015	JNC	RS
G	56068	AUG 05,2014	JNC	RS
REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
DRFT	C	ASTIGLIONE	DATE	DATE
CHKD		DATE	APPRV	DATE
			R. SCHERER	SEP 05,2014
DIVISION	Interconnect Solutions	DIVISION CODE	EMSD	
DO NOT SCALE DRAWING		TOLERANCES EXCEPT AS NOTED		
THIRD ANGLE PROJECTION		INCHES		
INTERPRET PER ASME Y14.5 - 2018		.0	±.1	
MAX SURFACE ROUGHNESS		.00	±.01	
ALL SURFACES		.000	±.005	
MARKED ONLY		.0000	±.0002	
		MILLIMETERS		
		0	±	
		.0	±	
		.00	±	
		.000	±	
		ANGLES	±	
CAGE NUMBER	SIZE	DRAWING NO.	REV.	
D	78-5100-0771-5	L		
MODEL	3400	DET	LISTS	YES
		NO	SHT	5 OF 5