Product data sheet Characteristics

SUA2200X115

APC Smart-UPS 2200VA 120V W/L5-20P, (4) 5-15R, (2) 5ALT-20R, & (1) L5-20R with USB





Overview

-	
Lead time	Special Order - Call for Quoted Lead Times

General

Provided equipment	CD with software	
	Documentation CD	
	Installation guide	
	Smart UPS signalling RS-232 cable	

Physical

① To be discontinued		
Overview		
Lead time	Special Order - Call for Quoted Lead Times	
General		
Provided equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable	
	Official of O Signaturing 100-202 cable	
DL - 1 - 1		
Physical	4.00	
Cable length	1.83 m	
Colour	Black	
Depth	54.6 cm	
Height	43.2 cm	
Net weight	50.92 kg	
Width	19.6 cm	
Input		
Network frequency	50/60 Hz +/- 3 Hz auto-sensing	
Plug standard	NEMA L5-20P	
Input voltage limits	75154 V adjustable 82144 V	
Input voltage	120 V	
Output		
Detection	1980 W	
Rated power in vv		
Rated power in W Maximum configurable power in W	1980 W	

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing	
Plug standard	NEMA L5-20P	1
Input voltage limits	75154 V adjustable 82144 V	
Input voltage	120 V	

Output

Rated power in W	1980 W
Maximum configurable power in W	1980 W
Harmonic distortion	Less than 5 % at full load

Output frequency	4763 Hz sync to mains	
UPS type	Line interactive	
Wave type	Sine wave	
Nb of power socket outlets	4 NEMA 5-15R 1 NEMA 5-20R 1 NEMA L5-20R	
Output voltage	120 V	

Conformance

Product certifications	CSA
Standards	UL 1778
Equipment protection policy	Lifetime: \$150000

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage altitude	0.0015240.00 m
Acoustic level	45 dBA
Heat dissipation	275 Btu/h

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0

Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	60.92 kg	
Package 1 Height	55.9 cm	
Package 1 width	38.1 cm	
Package 1 Length	76.2 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant

EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty 2 years repair or replace	
------------------------------------	--