

cosmo High Voltage, Solid State Relay-MOSFET Output KAQW217/217A

UL 1577/ UL 508 (File No.E108430), FI EN60950 (File No.FI13698)




Features

1. Normally Open, Single Pole Single Throw
2. Control 200VAC or DC Voltage
3. Switch 180mA Loads
4. LED control Current, 5mA
5. Low ON-Resistance
6. dv/dt , >500V/ms
7. Isolation Test Voltage, 3750VACrms

Absolute Maximum Ratings

(Ta=25°C)

Emitter (Input)	Detector (Output)
Reverse Voltage.....5.0V	Output Breakdown Voltage±200V
Continuous Forward Current50mA	Continuous Load Current±180mA
Peak Forward Current1A	Power Dissipation450mW
Power Dissipation75mW	
Derate Linearly from 25°C1.3mW/°C	
General Characteristics	
Isolation Test Voltage3750VACrms	Storage Temperature Range ...-40°C to +150°C
Isolation Resistance	Operating Temperature Range...-40°C to +85°C
Vio=500V, Ta=25°C≥10 ¹⁰ Ω	Junction Temperature.....100°C
Total Power Dissipation500mW	Soldering Temperature,
Derate Linearly from 25°C2.5mW/°C	2mm from case, 10 sec260°C



Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Emitter (Input)						
Forward Voltage	V _F	I _F =10mA		1.2	1.5	V
Operation Input Current	I _{FON}	V _L =±20V, I _L =100mA, t =10mS		1.5	5	mA
Recovery Input Current	I _{FOFF}	V _L =±20V, I _L ≤5uA	0.2			mA
Detector (Output)						
Output Breakdown Voltage	V _B	I _B =50uA	200			V
Output Off-State Leakage	I _{TOFF}	V _T =100V, I _F =0mA		0.2	1	uA
I/O Capacitance	C _{ISO}	I _F =0, f =1MHz		6		pF
ON Resistance	R _{ON}	I _L =100mA, I _F =10mA		6	15	Ω
Turn-On Time	T _{ON}	I _F =10mA, V _L =±20V		0.4	1.0	ms
Turn-Off Time	T _{OFF}	t =10ms, I _L =±100mA		0.3	1.0	ms

Schematic and Wiring Diagrams

Type	Schematic	Output configuration	Load	Connection	Wiring Diagrams
KAQW217 & KAQW217A		2a	AC/DC	—	(1)Two independent 1 Form A use (2) 2 Form A use

Data Curve

Fig.1 Load current vs. ambient temperature
Allowable ambient temperature:
-40°C to +85°C




Fig.2 On resistance vs. ambient temperature
Across terminals 5,7 and 6,8 pin
LED current: 5mA
Continuous load current: 180mA(DC)




Fig.3 Turn on time vs. ambient temperature
Load voltage: 200V(DC)
LED current: 5mA
Continuous load current: 180mA(DC)




Fig.4 Turn off time vs. ambient temperature
LED current: 5mA; Load voltage:
200V(DC)
Continuous load current: 180mA(DC)




Fig.5 LED operate vs. ambient temperature
Load voltage: 200V(DC)
Continuous load current: 180mA(DC)




Fig.6 LED turn off current vs. ambient temperature
Load voltage: 200V(DC)
Continuous load current: 180mA(DC)




Fig.7 LED dropout voltage vs. ambient temperature
LED current: 5 to 50mA




Fig.8 Voltage vs. current characteristics of output at MOS FET portion
Measured portion: across terminals 5,7 and 6,8 pin
Ambient temperature: 25°C




Fig.9 Off state leakage current
Across terminals 5,7 and 6,8 pin
Ambient temperature: 25°C




Fig.10 LED forward current vs. turn on time
Across terminals 5,7 and 6,8 pin;
Load voltage: 200V (DC);
Continuous load current: 180mA (DC);
Ambient temperature: 25°C




Fig.11 LED forward current vs. turn off time
Across terminals 5,7 and 6,8 pin;
Load voltage: 200V (DC);
Continuous load current: 180mA (DC);
Ambient temperature: 25°C




Fig.12 Applied voltage vs. output capacitance
Across terminals 5,7 and 6,8 pin
Frequency: 1MHz
Ambient temperature: 25°C

