



CGAT-18/6-0-STK Product Details




CGAT-18/6-0-STK

TE Internal Number: 2687052007



Active

Heat Shrink Tubing



Always EU RoHS/ELV Compliant (Statement of Compliance)


Product Highlights:


- Heat Shrinkable Tubing
- Product Name = CGAT
- Product Source = U.K.
- Semiflexible
- Thin Wall Style


[View all Features](#)


Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
<div>Product Drawings:<ul style="list-style-type: none">None AvailableCatalog Pages/Data Sheets:<ul style="list-style-type: none">None AvailableProduct Specifications:<ul style="list-style-type: none">None AvailableApplication Specifications:<ul style="list-style-type: none">None AvailableInstruction Sheets:<ul style="list-style-type: none">None AvailableCAD Files:<ul style="list-style-type: none">None Available</div>	<div>Related Products:<ul style="list-style-type: none">Tooling</div>
<div><div>List all Documents</div></div>	

Product Features (Please use the Product Drawing for all design activity)	
<div>Product Type Features:<ul style="list-style-type: none">Product Type = Heat Shrinkable TubingColor = BlackDimensions:<ul style="list-style-type: none">Expanded ID, Min. (mm [in]) = 18.00 [0.709]Recovered ID, Max. (mm [in]) = 6.00 [0.236]Cut Length (mm [in]) = 1220.00 [48.031]Body Features:<ul style="list-style-type: none">Product Name = CGATPliancy = SemiflexibleWall Style = ThinWall Type = DualLining Type = AdhesiveMaterial = Crosslinked PolyolefinShrink Ratio = 3:1Fluid Type = Brake Fluid, WaterResistant To = FluidsWall Thickness - Full Recovery (Nominal) (mm [in]) = 1.70 [0.067]Housing Features:<ul style="list-style-type: none">Material Systems = NoIndustry Standards:<ul style="list-style-type: none">Government/Industry Qualification = NoFlammability Rating Type = Flame-RetardantUL Rating = RecognizedCSA Certified = NoApproved Standards = UL E85381RoHS/ELV Compliance = RoHS compliant, ELV compliantLead Free Solder Processes = Not relevant for lead free processRoHS/ELV Compliance History = Always was RoHS compliant</div>	<div>Environmental:<ul style="list-style-type: none">Fluid Resistance = Moisture/SprayOperating Temperature (°C) = -30 - +80Conditions for Usage:<ul style="list-style-type: none">Full Recovery Temperature (°C) = 115Shrink Temperature, Min. (°C) = 80High Temperature Compatible = NoOperation/Application:<ul style="list-style-type: none">Application = SealingEmission Free = NoProduct Use = Connector-to-Cable Transitions, Wire BreakoutsPackaging Features:<ul style="list-style-type: none">Packaging Method = StickProduct Availability:<ul style="list-style-type: none">Product Source = U.K.Other:<ul style="list-style-type: none">Brand = Raychem</div>