

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

1HS117

1HS117

PAGE 1 OF 1

REPLACES

RELEASE NO. PR-6693

M

DRAWING
NUMBER

8

8

ISSUE

8

CHECK

REVISIONS

A	C O	55162-F	D J S	8 MAR 85
B	CO	62736	M A M	15 MAR 88
C	CO	61043	TSK	26 AUG 88
D	CO	72580	DAW	20 AUG 92
E	CO	75625	J D S	15 JULY 93
F	CO	76375	WES	31 AUG 93
G	CO	94122	TSM	12 MAR 99

CHECK

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77


20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77




NOTE -

- ⚠ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
- 2 - FOR USE IN AMBIENT TEMPERATURE RANGE FROM MINUS 65° F TO PLUS 250° F

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE-- 32 OZ MAX

RELEASE FORCE-----4 OZ MIN

DIFFERENTIAL TRAVEL-.020 MAX

OVERTRAVEL-----.032 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

LINE
VOLTAGE

INDUCTIVE
LOAD

RESISTIVE
LOAD

28 VDC
(SEA LEVEL-100,000 FT)

8 AMP

25 AMP

125 VAC
(SEA LEVEL-70,000 FT)

1 AMP

.5 AMP

L277 1A-125VAC, 5A-28VDC

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES

APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM.	TOL.	DIM.	TOL.
mm	mm/in	in	mm/in
NO PLACES	X	1/.04	
ONE PLACE	X X	0.4/.018	X X
TWO PLACES	X X X	0.13/.005	X X X
THREE PLACES	X X X X	0.13/.005	X X X X
ANGLES			

SI METRIC

US CUSTOMARY

DESIGN UNITS

WEIGHT 1.9 OZ MAX

FO-52848-A
FORMTEK

DRAWN

CHECK

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77

20 JULY 77