

HBL8452C -- Plug



4P4W, 50A 3PH 250V, 15-50P, 4-Position Angle, Black & White Nylon

Product Specifications



Plugs

Product Type

Angle

NEMA

50A

3ph 250V AC

3 Pole, 4 Wire Grounding

No

Insulgrip

Color




Black

15-50P

| | |
|--------------------------------------|---|
| Horsepower | 7.5 |
| Cord Dia. | .625"-1.310" (15.9-33.3) |
| Description | Straight Blade Plug |
| Type | 3 Pole, 4 Wire, Grounding |
| Rating | 50A, 3ph 250V |
| Certification | UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280 |
| IP Suitability | IP20 |
| Housing Material | Nylon |
| Blade Holder Material | Glass Reinforced PET |
| Retainer Material | Glass Reinforced PET |
| Cord Clamp Material | Glass Reinforced Polyester |
| Contact Blades Material | .100" Brass |
| Ground Contact Blade Material | .075" Brass |
| Terminal Screw Material | Steel - Zn plated |
| Ground Screw Material | 3/8" Allen Head, Plated Steel |
| Body Holding Screws | Steel Multiple Drive |
| Box Terminals Material | Copper |
| Dielectric Voltage | Withstands 2,000V minimum. |
| Current Interrupting | Certified for current interrupting at full rated current. |
| Temperature Rise | Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.. |
| Terminal Identification | Terminals identified in accordance with UL498 (Brass, White, Green). |
| Terminal Accommodation | #12-#4 AWG copper stranded or solid conductor only. |
| Product Identification | Ratings are a permanent part of the device. |
| Flammability | UL 94 HB or better. |
| Operating Temperatures | Maximum continuous 75°C, minimum -40°C (w/o impact). |
| M Drawings | Click here for M-Drawing |
| Catalog Page | Click here for catalog page A34 |
| Brochures | Click here for product brochure |
| Hubbellnet | Click here for Hubbellnet |

| | |
|------------------------|--|
| Catalog Section | Click here for Section-A |
| UPC Number | 78358501517 |
| Weight in LBs | 0.85 |



NEMA
Configuration

Hubbell Incorporated (Delaware)
185 Plains Road
Milford, CT 06460-2420
Ph: (203) 882-4800
Fax: (800) 255-1031



Wiring Device-Kellems