

## Panel feed-through - ST-7EP1N8ACK04S - 1618791

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel feed-through, straight, SPEEDCON locking, M17, Number of positions: 7+PE, Type of contact: Male connector, Crimp connection, Flat gasket, 4xØ3,2, shielded: Yes, Flange dimensions: 25.75 mm x 25.75 mm, Cable diameter: 9 mm...11 mm



### Key commercial data

Packing unit	1 pc
GTIN	 4 046356 817424
Weight per Piece (excluding packing)	44.44 g
Custom tariff number	85366990
Country of origin	Germany
Product key	ABRCEK
Note	Made to Order (non-returnable)

### Technical data

#### General

Note	Order information Order crimp contacts Ø 1 mm separately
Type of locking	SPEEDCON locking
Direction of rotation of contact chamber numbering	Standard
Coding	N
Contact connection method	Crimp connection
Type of contacts	Male connector
Number of positions	8
Contact diameter of power contacts	1 mm
Nominal current per power contact at 25°C	14 A
Contact diameter of signal contacts	1 mm
Nominal current per signal contact at 25°C	14 A
Conductor entry	9 mm ... 11 mm
Mounting type	4xØ3,2

#### Ambient conditions

# Panel feed-through - ST-7EP1N8ACK04S - 1618791

## Technical data

### Ambient conditions

Degree of protection	IP67
----------------------	------

### Specifications according to DIN EN 61984:2001

Nominal / operating voltage of power contacts	630 V
Rated surge voltage of power contacts	6 kV
Surge voltage category of power contacts	III
Pollution degree of power contacts	3

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260702
eCl@ss 7.0	27440102
eCl@ss 8.0	27440103

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002635
ETIM 5.0	EC002061

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

## Approvals

### Approvals

---

### Approvals

UL Recognized / UL Recognized / cUL Recognized / cUL Recognized / cULus Recognized

---

### Ex Approvals

---

## Panel feed-through - ST-7EP1N8ACK04S - 1618791

### Approvals

Approvals submitted

---

#### Approval details

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	1
Nominal current IN	5 A
Nominal voltage UN	600 V

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	0.75
Nominal current IN	4 A
Nominal voltage UN	600 V

cUL Recognized	
mm <sup>2</sup> /AWG/kcmil	1
Nominal current IN	5 A
Nominal voltage UN	600 V


cUL Recognized	
mm <sup>2</sup> /AWG/kcmil	0.75
Nominal current IN	4 A
Nominal voltage UN	600 V

cULus Recognized	
------------------	---

### Drawings

## Panel feed-through - ST-7EP1N8ACK04S - 1618791

Schematic diagram



Connector pin assignment

Dimensioned drawing

