

9926 Hook-up/Lead - UL AWM Styles 1007 and 1569

 	For more information please call 1-800-Belden1 <u>See Put-ups and Colors</u>
--	---

Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 300V. Rated 600V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	26
Stranding	7x34
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.015 in.

OVERALL:

Overall Nominal Diameter	.051 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
UL Rating	300 V RMS, 80°C and 300 V, 105°C
CSA Type	TR-64, TRSR-64
CSA Rating	300 V RMS, 90°C and 300 V, 105°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

FLAME TEST:

UL Flame Test	VW-1
CSA Flame Test	FT1

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

9926 Hook-up/Lead - UL AWM Styles 1007 and 1569

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9926 001100	26 STR PVC BRN	100	0.2	BROWN	
9926 0011000	26 STR PVC BRN	1000	3	BROWN	P
9926 001D5000	26 STR PVC BRN	D5000	10	BROWN	
9926 002100	26 STR PVC RED	100	0.2	RED	
9926 0021000	26 STR PVC RED	1000	3	RED	P
9926 002D5000	26 STR PVC RED	D5000	10	RED	
9926 003100	26 STR PVC ORG	100	0.2	ORANGE	
9926 0031000	26 STR PVC ORG	1000	3	ORANGE	P
9926 003D5000	26 STR PVC ORG	D5000	10	ORANGE	
9926 004100	26 STR PVC YEL	100	0.2	YELLOW	
9926 0041000	26 STR PVC YEL	1000	3	YELLOW	P
9926 005100	26 STR PVC GRN	100	0.2	GREEN, DARK	
9926 0051000	26 STR PVC GRN	1000	3	GREEN, DARK	P
9926 005D5000	26 STR PVC DGRN	D5000	10	GREEN, DARK	
9926 007100	26 STR PVC VIO	100	0.2	VIOLET	
9926 0071000	26 STR PVC VIO	1000	3	VIOLET	P
9926 0081000	26 STR PVC GRY	1000	3	GRAY	P
9926 009100	26 STR PVC WHT	100	0.2	WHITE	
9926 0091000	26 STR PVC WHT	1000	3	WHITE	P
9926 009D5000	26 STR PVC WHT	D5000	10	WHITE	
9926 010100	26 STR PVC BLK	100	0.2	BLACK	
9926 0101000	26 STR PVC BLK	1000	3	BLACK	P
9926 010D5000	26 STR PVC BLK	D5000	10	BLACK	
9926 013100	26 STR PVC D. BLU	100	0.2	BLUE, DARK	
9926 0131000	26 STR PVC D. BLU	1000	3	BLUE, DARK	P

9926 Hook-up/Lead - UL AWM Styles 1007 and 1569

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 11-17-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.