

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

10-08-5061

Status:

Active

Overview:

KK® Interconnect System - Molex

Description:

KK® Header, Vertical, with Polarizing Backwall, 6 Circuits, Tin (Sn) Plating

Documents:

3D Model

Drawing (PDF)

Product Specification PS-99020-0087 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Series

Application

Overview

Product Name

UPC

PCB Headers

2599

Power, Wire-to-Board

KK® Interconnect System - Molex

KK®

800753612259

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Flammability

Glow-Wire Compliant

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

Plating min - Termination

Polarized to PCB

Shrouded

Stackable

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

No

6

6

Natural

25

No

94V-2

No

No

No

None

None

Brass

Tin

Tin

Nylon

1.700/g

1

Vertical

4.45mm

None

1.60mm

Bag

5.08mm

5.08mm

5.080µm

5.080µm

No

Partial

Yes

No


See Product Specification

Through Hole

Electrical

Current - Maximum per Contact

7A



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Low-Halogen Status

Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

2599Series

Mates With

KK® Crimp Housing 3001 , 5058 , 3002

KK® PC Board Connector

Voltage - Maximum	250V
Solder Process Data	
Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Wave Capable (TH only)
Process Temperature max. C	260
Material Info	
Old Part Number	2599M-06A
Reference - Drawing Numbers	
Product Specification	PS-99020-0087
Sales Drawing	SDAE-2599M-N*

This document was generated on 07/08/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION