


9182 Twinax - Computer & Instrumentation Cable



Description:

150 Ohm twinaxial cable, 22 AWG stranded (19x34) tinned copper, Datalene® insulation, Duofoil® 100% shield + 22 AWG (19x34) tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	22
Stranding	19x34
Conductor Diameter	.031 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene

PAIR:

Pair Lay Length & Direction :		
Lay Length (in.)	Direction	Twists/ft (twist/ft)

3.0		4
-----	--	---

Pair Diameter	.275 in.
---------------	----------

Pair Color Code Chart :	
Number	Color

1	Black & Yellow
---	----------------

OUTER SHIELD:

Outer Shield Trade Name	Duofoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape-Aluminum Foil
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :	
Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	19x34
Outer Shield Drain Wire Diameter	.031 in.

9182 Twinax - Computer & Instrumentation Cable

Outer Shield Drain Wire Conductor Material	TC - Tinned Copper
--	--------------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.345 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
Bulk Cable Weight	41 lbs/1000 ft.
Max. Recommended Pulling Tension	28 lbs.
Min. Bend Radius (Install)	3.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CMX, CL2X
CEC/C(UL) Specification	CMX
AWM Specification	Style 2668

FLAME TEST:

UL Flame Test	1581 Vertical Flame (VW-1)
---------------	----------------------------

SUITABILITY:

Suitability - Indoor	Y
Suitability - Outdoor	Y
Suitability - Aerial	Y, when supported by a messenger wire

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	89182

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	150 Ohms
Nom. Inductance	0.293 μ H/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	8.8 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	16.5 pF/ft
Nominal Velocity of Propagation	78 %
Nominal Delay	1.3 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	14.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance	6.3 Ohms/1000 ft
Nom. Attenuation :	

9182 Twinax - Computer & Instrumentation Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
Nominal Attenuation	1			0.4
	10			1.2
	50			2.7
	100			4.3
	200			6.2
	400			8.8

Max. Operating Voltage - UL :

UL Voltage	Description
300 V RMS	NEC CMX
150 V RMS	NEC CL2X
30 V RMS	AWM Style 2668

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9182 0101000	2 #22 FHDPE SHLD PVC	1000	44	BLACK	C
9182 010500	2 #22 FHDPE SHLD PVC	500	23	BLACK	C
9182 010U500	2 #22 FHDPE SHLD PVC	U500	22.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 12-06-2002

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.