SERIES 346/396



FEATURES

UL Recognized

.125 (3.18) Contact Spacing x .250 (6.35) Row Spacing

Accepts .062 (1.57) Nominal Thickness P.C. Board

High Profile Insulator Body, .600 (15.24)

Contact Termination Options include P.C Tail, Wire Hole, .025 (0.64) Square Wire Wrap, 90 Degree & Extender Board Bends

Single or Dual Row Configurations

Large Variety of Mounting Options, Flush or Offset Lugs

Pre-assembled Card Guides Available

Accepts Between Contact and In-Contact Polarizing Keys

Automatic Wire Wrap Positioning Holes

SPECIFICATIONS

Insulator Material: Thermoplastic Polyester, UL 94V-0.

Contact Material: Copper, Nickel, Tin Alloy CA-725

Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate

Current Rating: 3 Amperes Continuous

Contact Resistance: 10 Milliohms Maximum

Dielectric Withstanding Voltage: 1500 V AC rms at Sea Level Between Adjacent Contacts

Insulation Resistance: 5000 Megohms Minimum

Operating Temperature: -65 to +105 Degrees C

Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge

Withdrawal Force: 1 oz (.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

Example Part Number 346 - 056 - 540 - 8 02

Series
Total Number of Contacts
Contact Code
Contact Rows and Insulator Style
Mounting Options

Series	Insulator Colour
346	Green
396	Black

Total Number of Contacts	Contact Rows
005, 006, ..., 050	Single Row
010, 012, ..., 100	Dual Row

Contact Code		Description & Tail Size	Tail Length "G"
500	Wire Hole	.050 x ..025 (1.27 x 0.64)	.260 (6.60)
520	P.C. Tail	.025 Square (0.64 Square)	.175 (4.45)
521	P.C. Tail	.025 Square (0.64 Square)	.150 (3.81)
522	P.C. Tail	.025 Square (0.64 Square)	.440(11.18)
526	P.C. Tail	.025 Square (0.64 Square)	.350 (8.89)
540	Wire Wrap	.025 Square (0.64 Square)	.560(14.22)
541	Wire Wrap	.025 Square (0.64 Square)	.750(19.05)
555	Extender Board Bend (Code 500 Contacts)		
556	Extender Board Bend (Code 520 Contacts)		
558	90 Degree Bend (Code 541 Contacts)		
559	90 Degree Bend (code 541 Contacts)		
560	Extender Board Bend (Code 526 Contacts)		

Contact Rows and Insulator Style	Description
1	Single Row, Flush Mounting Lugs
2	Dual Row, Flush Mounting Lugs
6	Single Row, .170 (4.32) Offset Lugs
8	Dual Row, .170 (4.32) Offset Lugs

Mounting Options	Description
01	No Mounting Lugs
02	.128 (3.25) Dia. Mounting Holes
03	.116 (2.95) I.D. Floating Eyelets
04	.156 (3.96) Dia. Mounting Holes
07	M3-0.5 Metric Threaded Inserts
08	#4-40 Unified Threaded Inserts
12	.128 (3.25) Dia. Side Mounting Holes
58	.468 (11.89) Offset Card Guides
78	In-Line Card Guides

Ordering Code Notes

1) All connector sizes up to 50 contacts single row / 100 contacts dual row are available upon request

2) The 500 contact code is standard in the 346 series only. Diallyl Phthalate insulator material will be supplied

3) Consult with Edac regarding connectors with a .420 (10.67) card slot depth

4) For lugless connectors, code 01 mounting, specify contact row codes 1 or 2

5) In-line card guides are only available with offset mounting lugs

Phone: (416) - 754 - 3322 Fax: (416) - 754 - 3299 Email: CustomerService@edac.net Website: www.edac.net

EDAC

SERIES 346/396



NUMBER OF CONTACTS		"A"		"B"		"C"		"D"		"E"	
Single	Dual	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)
5	10	1.435	(36.45)	1.170	(29.72)	.910	(23.11)	.750	(19.05)	.500	(12.70)
6	12	1.560	(39.62)	1.295	(32.89)	1.035	(26.29)	.875	(22.23)	.625	(15.88)
10	20	2.060	(52.32)	1.795	(45.59)	1.535	(38.99)	1.375	(34.93)	1.125	(28.58)
15	30	2.685	(68.20)	2.420	(61.47)	2.160	(54.86)	2.000	(50.80)	1.750	(44.45)
18	36	3.060	(77.72)	2.795	(70.99)	2.535	(64.39)	2.375	(60.33)	2.125	(53.98)
22	44	3.560	(90.42)	3.295	(83.69)	3.035	(77.09)	2.875	(73.03)	2.625	(66.68)
25	50	3.935	(99.95)	3.670	(93.22)	3.410	(86.61)	3.250	(82.55)	3.000	(76.20)
30	60	4.560	(115.82)	4.295	(109.09)	4.035	(102.49)	3.875	(98.43)	3.625	(92.08)
31	62	4.685	(119.00)	4.420	(112.27)	4.160	(105.66)	4.000	(101.60)	3.750	(95.25)
35	70	5.185	(131.70)	4.920	(124.97)	4.660	(118.36)	4.500	(114.30)	4.250	(107.95)
36	72	5.310	(134.87)	5.045	(128.14)	4.785	(121.54)	4.625	(117.48)	4.375	(111.13)
40	80	5.810	(147.57)	5.545	(140.84)	5.285	(134.24)	5.125	(130.18)	4.875	(123.83)
43	86	6.185	(157.10)	5.920	(150.37)	5.660	(143.76)	5.500	(139.70)	5.250	(133.35)
50	100	7.060	(179.32)	6.795	(172.59)	6.535	(165.99)	6.375	(161.93)	6.125	(155.58)

Dimensions of Other Connector Sizes are Listed

Phone: (416) - 754 - 3322 Fax: (416) - 754 - 3299 Email: CustomerService@edac.net Website: www.edac.net

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EDAC:

346-012-500-202 346-012-500-204 346-012-500-802 346-012-500-804 346-012-520-201 346-012-520-202 346-012-520-204 346-012-520-802 346-012-520-804 346-012-521-201 346-012-521-202 346-012-521-204 346-012-521-802 346-012-521-804 346-012-522-201 346-012-522-202 346-012-522-204 346-012-522-802 346-012-522-804 346-012-526-201 346-012-526-202 346-012-526-204 346-012-526-802 346-012-526-804 346-012-540-201 346-012-540-202 346-012-540-204 346-012-540-802 346-012-540-804 346-012-541-201 346-012-541-202 346-012-541-204 346-012-541-802 346-012-541-804 346-020-500-201 346-020-500-202 346-020-500-204 346-020-500-802 346-020-500-804 346-020-520-201 346-020-520-202 346-020-520-204 346-020-520-802 346-020-520-804 346-020-521-201 346-020-521-202 346-020-521-204 346-020-521-802 346-020-521-804 346-020-522-201 346-020-522-202 346-020-522-204 346-020-522-802 346-020-522-804 346-020-526-201 346-020-526-202 346-020-526-204 346-020-526-802 346-020-526-804 346-020-540-201 346-020-540-202 346-020-540-204 346-020-540-802 346-020-540-804 346-020-541-201 346-020-541-202 346-020-541-204 346-020-541-802 346-020-541-804 346-030-500-201 346-030-500-202 346-030-500-204 346-030-500-802 346-030-500-804 346-030-520-201 346-030-520-202 346-030-520-204 346-030-520-802 346-030-520-804 346-030-521-201 346-030-521-202 346-030-521-204 346-030-521-802 346-030-521-804 346-030-522-201 346-030-522-202 346-030-522-204 346-030-522-802 346-030-522-804 346-030-526-201 346-030-526-202 346-030-526-204 346-030-526-802 346-030-526-804 346-030-540-201 346-030-540-202 346-030-540-204 346-030-540-802 346-030-540-804 346-030-541-201