






MICROCHIP




nanowatt XLP Technology



www.microchip.com/XLP

Products with nanoWatt XLP Technology offer the industry's lowest currents for Run and Sleep, where extreme low power applications spend 90-99% of their time.



Looking Beyond Low Power MCUs

Microchip has introduced nanoWatt XLP eXtreme Low Power Technology to address the needs of your next product. Benefits include:

- Sleep currents below 20 nA
- Brown-out Reset down to 45 nA
- Watch-dog Timer down to 220 nA
- Real-time Clock/Calendar down to 470 nA
- Run currents down to 50 μ A/MHz
- Full analog and self-write capability down to 1.8V

Low Power Peripheral Integration

Today's low power products require integrated advanced peripherals. nanoWatt XLP MCUs are available with:

- USB Connectivity
- LCD Controllers
- Hardware RTCC
- mTouch™ Capacitive Touch Sensing

Example XLP PIC® MCUs

Device	Flash Memory (KB)	Pins	Sleep (nA)	WDT* (nA)	RTC* (nA)	1 MHz Run (μ A)
PIC16LF182X CAP SENSE	3.5-7	8-28	20	300	600	50
PIC16LF72X CAP SENSE	3.5-14	28/44	20	500	600	110
PIC16LF193X CAP SENSE LCD	7-28	28/44	60	500	600	150
PIC18LF1XK50 CAP SENSE USB	8-16	20	24	450	790	170
PIC18LF14K22 CAP SENSE	8-16	20	34	460	650	150
PIC18LF4XK22 CAP SENSE	8-64	28/44	50	600	500	250
PIC18F46J11 CAP SENSE	16-64	28/44	13	813	813	272
PIC18F46J50 CAP SENSE USB	16-64	28/44	13	813	813	272
PIC18F87K90 CAP SENSE LCD	32-128	64/80	25	350	720	181
PIC24F04KA201 CAP SENSE	4	14/20	20	370	470	195
PIC24F16KA102 CAP SENSE	8-16	20/28	20	420	520	195
PIC24FJ64GB004 CAP SENSE USB	32-64	28/44	20	220	520	250

*Base sleep current included in WDT and/or RTC numbers. Typical I/O pin leakage current ± 5 nA. All numbers are typical values at minimum V_{DD}, taken from the data sheet.

Information subject to change. The Microchip name and logo, the Microchip logo, MPLAB and PIC are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. mTouch and PiTail are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. © 2010 Energizer, Energizer and other marks are trademarks owned by Energizer. All other trademarks mentioned herein are property of their respective companies. © 2010, Microchip Technology Incorporated. All Rights Reserved. Printed in the U.S.A. 4/10 DS01274C

Low Power Safety

Reliability is a primary concern for battery powered products. Integrated low power supervisory circuit benefits:

- Brown-out Reset guards against low batteries, power loss
- Watchdog Timer with on-chip clock source for dependable operation
- Real Time Clock/Calendar for precise time keeping

Low Power Design Support

Full support for your extreme low power design:

- Global Sales and Technical Support (24/7)
- Regional Training Centers
- Low Cost Development Tools
 - Free MPLAB® IDE and C Compiler
 - Free software stacks: USB, mTouch, ZigBee®, IrDA®
- On-line Design Center: www.microchip.com/XLP

75
PRODUCTS

Example Applications

Battery

- Consumer
- Utility Metering
- Asset Tracking
- Electronic Locks
- Portable Medical
- Smoke/CO₂ Detectors
- Irrigation Systems
- Security Systems/Sensors
- Remote Keyless Entry

Green Initiatives

- Compliance with Regulations
- Appliances
- Home Electronics

Energy Harvesting

- Wireless Switches
- Battery-free Sensors
- Wireless Sensor Networks
- RF Powered Sensors

XLP 16-bit Development Board (DM240311)




Designed with eXtreme Low Power in mind, this board enables development with the PIC24F family of 16-bit PIC XLP MCUs.

- Supports 20-/28-pin devices
- Flexible power options
 - CR2032 coin cell
 - 2xAAA lithium** or alkaline cells
 - Energy harvesting: solar, vibration, RF, etc.
 - External/USB
- Easy Prototyping:
 - PiTail™ connector supports RF Modules, SD/MMC storage, speech playback modules and more
 - LEDs, capacitive and mechanical buttons, resistive pot, temperature sensor and EEPROM
 - Generic prototyping area
 - USB communication to PC

** Microchip recommends Energizer® Ultimate Lithium AAA Batteries for the XLP 16-bit Development Board.

Broad Low-Power Product Offering



www.microchip.com/XLP

