

# ISL28118, ISL28218

40V Precision Single-Supply, Rail-to-rail Output, Low-power Operational Amplifiers

FN7532  
Rev.8.00  
Jan 16, 2020

The [ISL28118](#), [ISL28218](#) are single and dual, low-power precision amplifiers optimized for single-supply applications. These devices feature a common mode input voltage range extending to 0.5V below the  $V_{\text{rail}}$ , a rail-to-rail differential input voltage range for use as a comparator and rail-to-rail output voltage swing, which makes them ideal for single-supply applications where input operation at ground is important.

These op amps feature low power, low offset voltage and low temperature drift, making them the ideal choice for applications requiring both high DC accuracy and AC performance. These amplifiers are designed to operate over a single supply range of 3V to 40V or a split supply voltage range of +1.8V/-1.2V to  $\pm 20\text{V}$ . The combination of precision and small footprint provides the user with outstanding value and flexibility relative to similar competitive parts.

Applications for these amplifiers include precision instrumentation, data acquisition, precision power supply controls and industrial controls.

Both parts are offered in 8 Ld SOIC and 8 Ld MSOP packages. All devices are offered in standard pin configurations and operate across the extended temperature range of  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

## Related Literature

For a full list of related documents, visit our website:

- [ISL28118](#), [ISL28218](#) device pages

## Features

- Rail-to-rail output .....  $<10\text{mV}$
- Below-ground ( $V_{\text{L}}$ ) input capability to  $-0.5\text{V}$ , ground sensing
- Single-supply range .....  $3\text{V}$  to  $40\text{V}$
- Low current consumption .....  $850\mu\text{A}$
- Low noise voltage .....  $5.6\text{nV}/\sqrt{\text{Hz}}$
- Low noise current .....  $355\text{fA}/\sqrt{\text{Hz}}$
- Low input offset voltage
  - ISL28118 .....  $150\mu\text{V}$  (max)
  - ISL28218 .....  $230\mu\text{V}$  (max)
- Superb offset voltage temperature drift
  - ISL28118 .....  $1.2\mu\text{V}/^{\circ}\text{C}$  (max)
  - ISL28218 .....  $1.4\mu\text{V}/^{\circ}\text{C}$  (max)
- Operating temperature range .....  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$
- No phase reversal

## Applications

- Precision instruments
- Medical instrumentation
- Data acquisition
- Power supply control
- Industrial process control




FIGURE 1. TYPICAL APPLICATION: SINGLE-SUPPLY, LOW-SIDE CURRENT SENSE AMPLIFIER






FIGURE 2. INPUT OFFSET VOLTAGE vs INPUT COMMON MODE VOLTAGE,  $V_{\text{S}} = \pm 15\text{V}$

# Table of Contents

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>Pin Configurations</b>                                   | <b>3</b>  |
| <b>Pin Descriptions</b>                                     | <b>3</b>  |
| <b>Ordering Information</b>                                 | <b>4</b>  |
| <b>Absolute Maximum Ratings</b>                             | <b>5</b>  |
| <b>Thermal Information</b>                                  | <b>5</b>  |
| <b>Recommended Operating Conditions</b>                     | <b>5</b>  |
| <b>Electrical Specifications (<math>V_S \pm 15V</math>)</b> | <b>5</b>  |
| <b>Electrical Specifications (<math>V_S \pm 5V</math>)</b>  | <b>7</b>  |
| <b>Typical Performance Curves</b>                           | <b>9</b>  |
| <b>Applications Information</b>                             | <b>19</b> |
| Functional Description                                      | 19        |
| Operating Voltage Range                                     | 19        |
| Input Stage Performance                                     | 19        |
| Output Drive Capability                                     | 19        |
| Output Phase Reversal                                       | 19        |
| Single Channel Usage                                        | 19        |
| Power Dissipation                                           | 20        |
| ISL28118 and ISL28218 SPICE Model                           | 20        |
| <b>Characterization vs Simulation Results</b>               | <b>23</b> |
| <b>Revision History</b>                                     | <b>26</b> |
| <b>Package Outline Drawings</b>                             | <b>28</b> |

Pin Configurations



Pin Descriptions

| ISL28118<br>(8 LD SOIC, MSOP) | ISL28218<br>(8 LD SOIC, MSOP) | PIN<br>NAME  | EQUIVALENT<br>CIRCUIT | DESCRIPTION                    |
|-------------------------------|-------------------------------|--------------|-----------------------|--------------------------------|
| 3                             | 3                             | +IN, +IN_A   | 1                     | Amplifier A noninverting input |
| 2                             | 2                             | -IN, -IN_A   | 1                     | Amplifier A inverting input    |
| 6                             | 1                             | VOUT, VOUT_A | 2                     | Amplifier A output             |
| 4                             | 4                             | V-           | 3                     | Negative power supply          |
|                               | 5                             | +IN_B        | 1                     | Amplifier B noninverting input |
|                               | 6                             | -IN_B        | 1                     | Amplifier B inverting input    |
|                               | 7                             | VOUT_B       | 2                     | Amplifier B output             |
| 7                             | 8                             | V+           | 3                     | Positive power supply          |
| 1, 5, 8                       | -                             | NC           | -                     | No Connect                     |

CIRCUIT 1

CIRCUIT 2

CIRCUIT 3

## Ordering Information

| PART NUMBER<br>(Notes 2, 3) | PART MARKING     | TEMP RANGE<br>(°C) | TAPE AND REEL<br>(Units) (Note 1) | PACKAGE<br>(RoHS Compliant) | PKG.<br>DWG. # |
|-----------------------------|------------------|--------------------|-----------------------------------|-----------------------------|----------------|
| ISL28118FBZ                 | 28118 FBZ        | -40 to +125        | -                                 | 8 Ld SOIC                   | M8.15E         |
| ISL28118FBZ-T7              | 28118 FBZ        | -40 to +125        | 1k                                | 8 Ld SOIC                   | M8.15E         |
| ISL28118FBZ-T7A             | 28118 FBZ        | -40 to +125        | 250                               | 8 Ld SOIC                   | M8.15E         |
| ISL28118FBZ-T13             | 28118 FBZ        | -40 to +125        | 2.5k                              | 8 Ld SOIC                   | M8.15E         |
| ISL28118FUZ                 | 8118Z            | -40 to +125        | -                                 | 8 Ld MSOP                   | M8.118B        |
| ISL28118FUZ-T7              | 8118Z            | -40 to +125        | 1.5k                              | 8 Ld MSOP                   | M8.118B        |
| ISL28118FUZ-T7A             | 8118Z            | -40 to +125        | 250                               | 8 Ld MSOP                   | M8.118B        |
| ISL28118FUZ-T13             | 8118Z            | -40 to +125        | 2.5k                              | 8 Ld MSOP                   | M8.118B        |
| ISL28218FBZ                 | 28218 FBZ        | -40 to +125        | -                                 | 8 Ld SOIC                   | M8.15E         |
| ISL28218FBZ-T7A             | 28218 FBZ        | -40 to +125        | 250                               | 8 Ld SOIC                   | M8.15E         |
| ISL28218FBZ-T13             | 28218 FBZ        | -40 to +125        | 2.5k                              | 8 Ld SOIC                   | M8.15E         |
| ISL28218FUZ                 | 8218Z            | -40 to +125        | -                                 | 8 Ld MSOP                   | M8.118B        |
| ISL28218FUZ-T7              | 8218Z            | -40 to +125        | 1k                                | 8 Ld MSOP                   | M8.118B        |
| ISL28218FUZ-T7A             | 8218Z            | -40 to +125        | 250                               | 8 Ld MSOP                   | M8.118B        |
| ISL28218FUZ-T13             | 8218Z            | -40 to +125        | 2.5k                              | 8 Ld MSOP                   | M8.118B        |
| ISL28218SOICEVAL1Z          | Evaluation Board |                    |                                   |                             |                |

### NOTES:

1. See [TB347](#) for details about reel specifications.
2. These Pb-free plastic packaged products employ special Pb-free material sets, molding compounds/die attach materials and 100% matte tin plate plus anneal (e3 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations). Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.
3. For Moisture Sensitivity Level (MSL), see the [ISL28118](#), [ISL28218](#) device information pages. For more information about MSL, see [TB363](#).

## Absolute Maximum Ratings

|                                                    |                                     |
|----------------------------------------------------|-------------------------------------|
| Maximum Supply Voltage                             | 42V                                 |
| Maximum Differential Input Current                 | 20mA                                |
| Maximum Differential Input Voltage                 | 42V or $V_- - 0.5V$ to $V_+ + 0.5V$ |
| Min/Max Input Voltage                              | 42V or $V_- - 0.5V$ to $V_+ + 0.5V$ |
| Max/Min Input Current                              | $\pm 20mA$                          |
| Output Short-circuit Duration (1 output at a time) | Indefinite                          |
| ESD Tolerance                                      |                                     |
| Human Body Model (Tested per JESD22-A114F)         | 3kV                                 |
| Machine Model (Tested per JESD22-A115-A)           | 300V                                |
| Charged Device Model (Tested per JESD22-C101D)     | 2kV                                 |
| ESD Tolerance (ISL28118 SOIC package only)         |                                     |
| Human Body Model (Tested per JESD22-A114F)         | 5.5kV                               |
| Machine Model (Tested per JESD22-A115-C)           | 300V                                |
| Charged Device Model (Tested per JESD22-C101D)     | 2kV                                 |

## Thermal Information

| Thermal Resistance (Typical)   | $\theta_{JA}$ ( $^{\circ}C/W$ )   | $\theta_{JC}$ ( $^{\circ}C/W$ ) |
|--------------------------------|-----------------------------------|---------------------------------|
| ISL28118                       |                                   |                                 |
| 8 Ld SOIC Package (Notes 4, 5) | 120                               | 60                              |
| 8 Ld MSOP Package (Notes 4, 5) | 165                               | 57                              |
| ISL28218                       |                                   |                                 |
| 8 Ld SOIC Package (Notes 4, 5) | 120                               | 55                              |
| 8 Ld MSOP Package (Notes 4, 5) | 150                               | 58                              |
| Storage Temperature Range      | $-65^{\circ}C$ to $+150^{\circ}C$ |                                 |
| Pb-free Reflow Profile         | see <a href="#">TB493</a>         |                                 |

## Recommended Operating Conditions

|                                        |                                           |
|----------------------------------------|-------------------------------------------|
| Ambient Operating Temperature Range    | $-40^{\circ}C$ to $+125^{\circ}C$         |
| Maximum Operating Junction Temperature | $+150^{\circ}C$                           |
| Supply Voltage                         | 3V ( $+1.8V/-1.2V$ ) to 40V ( $\pm 20V$ ) |

CAUTION: Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions can adversely impact product reliability and result in failures not covered by warranty.

### NOTES:

- $\theta_{JA}$  is measured with the component mounted on a high effective thermal conductivity test board in free air. See [TB379](#) for details.
- For  $\theta_{JC}$ , the case temperature location is taken at the package top center.

**Electrical Specifications ( $V_S \pm 15V$ )**  $V_{CM} = 0$ ,  $V_O = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^{\circ}C$ , unless otherwise noted. **Boldface entries apply across the operating temperature range,  $-40^{\circ}C$  to  $+125^{\circ}C$ . Temperature data established by characterization.**

| PARAMETER       | DESCRIPTION                                  | TEST CONDITIONS                                              | MIN<br>(Note 6)         | TYP         | MAX<br>(Note 6)               | UNIT              |
|-----------------|----------------------------------------------|--------------------------------------------------------------|-------------------------|-------------|-------------------------------|-------------------|
| $V_{OS}$        | Input Offset Voltage                         | ISL28118                                                     | -150                    | 25          | 150                           | $\mu V$           |
|                 |                                              |                                                              | <b>-270</b>             |             | <b>270</b>                    | $\mu V$           |
|                 |                                              | ISL28218                                                     | -230                    | 40          | 230                           | $\mu V$           |
|                 |                                              |                                                              | <b>-290</b>             |             | <b>290</b>                    | $\mu V$           |
| $TCV_{OS}$      | Input Offset Voltage Temperature Coefficient | ISL28118                                                     | <b>-1.2</b>             | <b>0.2</b>  | <b>1.2</b>                    | $\mu V/^{\circ}C$ |
|                 |                                              | ISL28218                                                     | <b>-1.4</b>             | <b>0.3</b>  | <b>1.4</b>                    | $\mu V/^{\circ}C$ |
| $\Delta V_{OS}$ | Input Offset Voltage Match (ISL28218 only)   | All packages                                                 | -280                    | 44          | 280                           | $\mu V$           |
|                 |                                              | SOIC                                                         | <b>-365</b>             |             | <b>365</b>                    | $\mu V$           |
|                 |                                              | MSOP                                                         | <b>-390</b>             |             | <b>390</b>                    | $\mu V$           |
| $I_B$           | Input Bias Current                           |                                                              | -575                    | -230        |                               | nA                |
|                 |                                              |                                                              | <b>-800</b>             |             |                               | nA                |
| $TCI_B$         | Input Bias Current Temperature Coefficient   |                                                              |                         | <b>-0.8</b> |                               | nA/ $^{\circ}C$   |
| $I_{OS}$        | Input Offset Current                         |                                                              | -50                     | 4           | 50                            | nA                |
|                 |                                              |                                                              | <b>-75</b>              |             | <b>75</b>                     | nA                |
| CMRR            | Common Mode Rejection Ratio                  | $V_{CM} = V_- - 0.5V$ to $V_+ - 1.8V$                        |                         | 118         |                               | dB                |
|                 |                                              | $V_{CM} = V_-$ to $V_+ - 1.8V$<br>ISL28118 SOIC              | 102                     | 118         |                               | dB                |
|                 |                                              |                                                              | <b>98</b>               |             |                               | dB                |
|                 |                                              | $V_{CM} = V_-$ to $V_+ - 1.8V$<br>ISL28218 SOIC              | 103                     | 118         |                               | dB                |
|                 |                                              |                                                              | <b>99</b>               |             |                               | dB                |
|                 |                                              | $V_{CM} = V_-$ to $V_+ - 1.8V$<br>ISL28118 and ISL28218 MSOP | 102                     | 118         |                               | dB                |
|                 |                                              |                                                              | <b>97</b>               |             |                               | dB                |
| $V_{CMIR}$      | Common Mode Input Voltage Range              | Guaranteed by CMRR test                                      | $V_- - 0.5$             |             | $V_+ - 1.8$                   | V                 |
|                 |                                              |                                                              | <b><math>V_-</math></b> |             | <b><math>V_+ - 1.8</math></b> | V                 |

**Electrical Specifications ( $V_S \pm 15V$ )**  $V_{CM} = 0$ ,  $V_O = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise noted. **Boldface entries apply across the operating temperature range,  $-40^\circ\text{C}$  to  $+125^\circ\text{C}$ . Temperature data established by characterization. (Continued)**

| PARAMETER                    | DESCRIPTION                                             | TEST CONDITIONS                                                                         | MIN<br>(Note 6) | TYP       | MAX<br>(Note 6) | UNIT                   |
|------------------------------|---------------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------|-----------|-----------------|------------------------|
| PSRR                         | Power Supply Rejection Ratio                            | $V_S = 3V$ to $40V$ , $V_{CMIR} = \text{Valid Input Voltage}$                           | 109             | 124       |                 | dB                     |
|                              |                                                         |                                                                                         | <b>105</b>      |           |                 | dB                     |
| $A_{VOL}$                    | Open-loop Gain                                          | $V_O = -13V$ to $+13V$ , $R_L = 10k\Omega$ to ground, ISL28118 SOIC                     | 125             | 136       |                 | dB                     |
|                              |                                                         |                                                                                         | <b>120</b>      |           |                 | dB                     |
|                              |                                                         | $V_O = -13V$ to $+13V$ , $R_L = 10k\Omega$ to ground, ISL28218 SOIC                     | 125             | 136       |                 | dB                     |
|                              |                                                         |                                                                                         | <b>122</b>      |           |                 | dB                     |
|                              |                                                         | $V_O = -13V$ to $+13V$ , $R_L = 10k\Omega$ to ground, ISL28118 and ISL28218 MSOP        | 120             | 136       |                 | dB                     |
|                              |                                                         |                                                                                         | <b>116</b>      |           |                 | dB                     |
| $V_{OL}$                     | Output Voltage Low, $V_{OUT}$ to $V_-$ (see Figure 32)  | ISL28118<br>$R_L = 10k\Omega$                                                           |                 |           | 70              | mV                     |
|                              |                                                         |                                                                                         |                 |           | <b>85</b>       | mV                     |
|                              |                                                         | ISL28218<br>$R_L = 10k\Omega$                                                           |                 |           | 70              | mV                     |
|                              |                                                         |                                                                                         |                 |           | <b>73</b>       | mV                     |
| $V_{OH}$                     | Output Voltage High, $V_+$ to $V_{OUT}$ (see Figure 32) | ISL28118<br>ISL28218<br>$R_L = 10k\Omega$                                               |                 |           | 110             | mV                     |
|                              |                                                         |                                                                                         |                 |           | <b>120</b>      | mV                     |
| $I_S$                        | Supply Current/Amplifier                                | ISL28118<br>$R_L = \text{Open}$                                                         |                 | 0.85      | 1.2             | mA                     |
|                              |                                                         |                                                                                         |                 |           | <b>1.6</b>      | mA                     |
|                              |                                                         | ISL28218<br>$R_L = \text{Open}$                                                         |                 | 0.85      | 1.1             | mA                     |
|                              |                                                         |                                                                                         |                 |           | <b>1.4</b>      | mA                     |
| $I_{SC+}$                    | Output Short-circuit Source Current                     | $R_L = 10\Omega$ to $V_-$                                                               |                 | 16        |                 | mA                     |
| $I_{SC-}$                    | Output Short-circuit Sink Current                       | $R_L = 10\Omega$ to $V_+$                                                               |                 | 28        |                 | mA                     |
| $V_{SUPPLY}$                 | Supply Voltage Range                                    | Guaranteed by PSRR                                                                      | <b>3</b>        |           | <b>40</b>       | V                      |
| <b>AC SPECIFICATIONS</b>     |                                                         |                                                                                         |                 |           |                 |                        |
| GBWP                         | Gain Bandwidth Product                                  | $A_{CL} = 101$ , $V_{OUT} = 100mV_{P-P}$ , $R_L = 2k$                                   |                 | 4         |                 | MHz                    |
| $e_{n-p-p}$                  | Voltage Noise                                           | 0.1Hz to 10Hz, $V_S = \pm 18V$                                                          |                 | 300       |                 | nV <sub>P-P</sub>      |
| $e_n$                        | Voltage Noise Density                                   | $f = 10\text{Hz}$ , $V_S = \pm 18V$                                                     |                 | 8.5       |                 | nV/ $\sqrt{\text{Hz}}$ |
| $e_n$                        | Voltage Noise Density                                   | $f = 100\text{Hz}$ , $V_S = \pm 18V$                                                    |                 | 5.8       |                 | nV/ $\sqrt{\text{Hz}}$ |
| $e_n$                        | Voltage Noise Density                                   | $f = 1\text{kHz}$ , $V_S = \pm 18V$                                                     |                 | 5.6       |                 | nV/ $\sqrt{\text{Hz}}$ |
| $e_n$                        | Voltage Noise Density                                   | $f = 10\text{kHz}$ , $V_S = \pm 18V$                                                    |                 | 5.6       |                 | nV/ $\sqrt{\text{Hz}}$ |
| $i_n$                        | Current Noise Density                                   | $f = 1\text{kHz}$ , $V_S = \pm 18V$                                                     |                 | 355       |                 | fA/ $\sqrt{\text{Hz}}$ |
| THD + N                      | Total Harmonic Distortion + Noise                       | 1kHz, $G = 1$ , $V_O = 3.5V_{RMS}$ , $R_L = 10k\Omega$                                  |                 | 0.0003    |                 | %                      |
| <b>TRANSIENT RESPONSE</b>    |                                                         |                                                                                         |                 |           |                 |                        |
| SR                           | Slew Rate                                               | $A_V = 1$ , $R_L = 2k\Omega$ , $V_O = 10V_{P-P}$                                        |                 | $\pm 1.2$ |                 | V/ $\mu\text{s}$       |
| $t_r$ , $t_f$ , Small Signal | Rise Time<br>10% to 90% of $V_{OUT}$                    | $A_V = 1$ , $V_{OUT} = 100mV_{P-P}$ , $R_f = 0\Omega$ ,<br>$R_L = 2k\Omega$ to $V_{CM}$ |                 | 100       |                 | ns                     |
|                              | Fall Time<br>90% to 10% of $V_{OUT}$                    | $A_V = 1$ , $V_{OUT} = 100mV_{P-P}$ , $R_f = 0\Omega$ ,<br>$R_L = 2k\Omega$ to $V_{CM}$ |                 | 100       |                 | ns                     |
| $t_s$                        | Settling Time to 0.01%<br>10V Step; 10% to $V_{OUT}$    | $A_V = 1$ , $V_{OUT} = 10V_{P-P}$ , $R_f = 0\Omega$<br>$R_L = 2k\Omega$ to $V_{CM}$     |                 | 8.5       |                 | $\mu\text{s}$          |

**Electrical Specifications ( $V_S \pm 5V$ )**  $V_S \pm 5V$ ,  $V_{CM} = 0$ ,  $V_O = 0V$ ,  $T_A = +25^\circ C$ , unless otherwise noted. **Boldface entries apply across the operating temperature range,  $-40^\circ C$  to  $+125^\circ C$ . Temperature data established by characterization.**

| PARAMETER       | DESCRIPTION                                                                 | TEST CONDITIONS                                                                       | MIN<br>(Note 6)         | TYP         | MAX<br>(Note 6)               | UNITS            |
|-----------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-------------------------|-------------|-------------------------------|------------------|
| $V_{OS}$        | Input Offset Voltage                                                        | ISL28118                                                                              | -150                    | 25          | 150                           | $\mu V$          |
|                 |                                                                             |                                                                                       | <b>-270</b>             |             | <b>270</b>                    | $\mu V$          |
|                 |                                                                             | ISL28218                                                                              | -230                    | 40          | 230                           | $\mu V$          |
|                 |                                                                             |                                                                                       | <b>-290</b>             |             | <b>290</b>                    | $\mu V$          |
| $TCV_{OS}$      | Input Offset Voltage Temperature Coefficient                                | ISL28118                                                                              | <b>-1.2</b>             | <b>0.2</b>  | <b>1.2</b>                    | $\mu V/^\circ C$ |
|                 |                                                                             | ISL28218                                                                              | <b>-1.4</b>             | <b>0.3</b>  | <b>1.4</b>                    | $\mu V/^\circ C$ |
| $\Delta V_{OS}$ | Input Offset Voltage Match (ISL28218 only)                                  |                                                                                       | -280                    | 44          | 280                           | $\mu V$          |
|                 |                                                                             |                                                                                       | <b>-365</b>             |             | <b>365</b>                    | $\mu V$          |
| $I_B$           | Input Bias Current                                                          |                                                                                       | -575                    | -230        |                               | nA               |
|                 |                                                                             |                                                                                       | <b>-800</b>             |             |                               | nA               |
| $TCI_B$         | Input Bias Current Temperature Coefficient                                  |                                                                                       |                         | <b>-0.8</b> |                               | nA/ $^\circ C$   |
| $I_{OS}$        | Input Offset Current                                                        |                                                                                       | -50                     | 4           | 50                            | nA               |
|                 |                                                                             |                                                                                       | <b>-75</b>              |             | <b>75</b>                     | nA               |
| CMRR            | Common Mode Rejection Ratio                                                 | $V_{CM} = V_- - 0.5V$ to $V_+ - 1.8V$                                                 |                         | 119         |                               | dB               |
|                 |                                                                             | $V_{CM} = V_-$ to $V_+ - 1.8V$<br>ISL28118 and ISL28218 SOIC                          | 101                     | 117         |                               | dB               |
|                 |                                                                             |                                                                                       | <b>97</b>               |             |                               | dB               |
|                 |                                                                             | $V_{CM} = V_-$ to $V_+ - 1.8V$<br>ISL28118 and ISL28218 MSOP                          | 101                     | 117         |                               | dB               |
|                 |                                                                             |                                                                                       | <b>96</b>               |             |                               | dB               |
|                 |                                                                             |                                                                                       |                         |             |                               |                  |
| $V_{CMIR}$      | Common Mode Input Voltage Range                                             | Guaranteed by CMRR test                                                               | $V_- - 0.5$             |             | $V_+ - 1.8$                   | V                |
|                 |                                                                             |                                                                                       | <b><math>V_-</math></b> |             | <b><math>V_+ - 1.8</math></b> | V                |
| PSRR            | Power Supply Rejection Ratio                                                | $V_S = 3V$ to $10V$ , $V_{CMIR}$ = Valid Input Voltage,<br>ISL28118 and ISL28218 SOIC | 109                     | 124         |                               | dB               |
|                 |                                                                             |                                                                                       | <b>105</b>              |             |                               | dB               |
|                 |                                                                             | ISL28118 MSOP                                                                         | 108                     | 124         |                               | dB               |
|                 |                                                                             | ISL28218 MSOP                                                                         | 107                     | 124         |                               | dB               |
|                 |                                                                             | ISL28118 and ISL28218 MSOP                                                            | <b>103</b>              |             |                               | dB               |
|                 |                                                                             |                                                                                       |                         |             |                               |                  |
| $A_{VOL}$       | Open-loop Gain                                                              | $V_O = -3V$ to $+3V$ , $R_L = 10k\Omega$ to ground,<br>ISL28118 and ISL28218 SOIC     | 122                     | 132         |                               | dB               |
|                 |                                                                             |                                                                                       | <b>117</b>              |             |                               | dB               |
|                 |                                                                             | ISL28118 and ISL28218 MSOP                                                            | 120                     | 132         |                               | dB               |
|                 |                                                                             |                                                                                       | <b>115</b>              |             |                               | dB               |
| $V_{OL}$        | Output Voltage Low, $V_{OUT}$ to $V_-$<br>(see <a href="#">Figure 32</a> )  | $R_L = 10k\Omega$                                                                     |                         |             | 38                            | mV               |
|                 |                                                                             |                                                                                       |                         |             | <b>45</b>                     | mV               |
| $V_{OH}$        | Output Voltage High, $V_+$ to $V_{OUT}$<br>(see <a href="#">Figure 31</a> ) | $R_L = 10k\Omega$                                                                     |                         |             | 65                            | mV               |
|                 |                                                                             |                                                                                       |                         |             | <b>70</b>                     | mV               |
| $I_S$           | Supply Current/Amplifier                                                    | $R_L = \text{Open}$                                                                   |                         | 0.85        | 1.1                           | mA               |
|                 |                                                                             |                                                                                       |                         |             | <b>1.4</b>                    | mA               |
| $I_{SC+}$       | Output Short-circuit Source Current                                         | $R_L = 10\Omega$ to $V_-$                                                             |                         | 13          |                               | mA               |
| $I_{SC-}$       | Output Short-circuit Sink Current                                           | $R_L = 10\Omega$ to $V_+$                                                             |                         | 20          |                               | mA               |

**Electrical Specifications ( $V_S \pm 5V$ )**  $V_S \pm 5V$ ,  $V_{CM} = 0$ ,  $V_O = 0V$ ,  $T_A = +25^\circ C$ , unless otherwise noted. **Boldface entries apply across the operating temperature range,  $-40^\circ C$  to  $+125^\circ C$ . Temperature data established by characterization. (Continued)**

| PARAMETER                    | DESCRIPTION                                         | TEST CONDITIONS                                                                         | MIN<br>(Note 6) | TYP     | MAX<br>(Note 6) | UNITS             |
|------------------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------|---------|-----------------|-------------------|
| <b>AC SPECIFICATIONS</b>     |                                                     |                                                                                         |                 |         |                 |                   |
| GBWP                         | Gain Bandwidth Product                              | $A_{CL} = 101$ , $V_{OUT} = 100mV_{P-P}$ ; $R_L = 2k$                                   |                 | 3.2     |                 | MHz               |
| $e_{np-p}$                   | Voltage Noise                                       | 0.1Hz to 10Hz                                                                           |                 | 320     |                 | nV <sub>P-P</sub> |
| $e_n$                        | Voltage Noise Density                               | $f = 10Hz$                                                                              |                 | 9       |                 | nV/ $\sqrt{Hz}$   |
| $e_n$                        | Voltage Noise Density                               | $f = 100Hz$                                                                             |                 | 5.7     |                 | nV/ $\sqrt{Hz}$   |
| $e_n$                        | Voltage Noise Density                               | $f = 1kHz$                                                                              |                 | 5.5     |                 | nV/ $\sqrt{Hz}$   |
| $e_n$                        | Voltage Noise Density                               | $f = 10kHz$                                                                             |                 | 5.5     |                 | nV/ $\sqrt{Hz}$   |
| $i_n$                        | Current Noise Density                               | $f = 1kHz$                                                                              |                 | 380     |                 | fA/ $\sqrt{Hz}$   |
| THD + N                      | Total Harmonic Distortion + Noise                   | 1kHz, $G = 1$ , $V_O = 1.25V_{RMS}$ , $R_L = 10k\Omega$                                 |                 | 0.0003  |                 | %                 |
| <b>TRANSIENT RESPONSE</b>    |                                                     |                                                                                         |                 |         |                 |                   |
| SR                           | Slew Rate                                           | $A_V = 1$ , $R_L = 2k\Omega$ , $V_O = 4V_{P-P}$                                         |                 | $\pm 1$ |                 | V/ $\mu s$        |
| $t_r$ , $t_f$ , Small Signal | Rise Time<br>10% to 90% of $V_{OUT}$                | $A_V = 1$ , $V_{OUT} = 100mV_{P-P}$ , $R_f = 0\Omega$ ,<br>$R_L = 2k\Omega$ to $V_{CM}$ |                 | 100     |                 | ns                |
|                              | Fall Time<br>90% to 10% of $V_{OUT}$                | $A_V = 1$ , $V_{OUT} = 100mV_{P-P}$ , $R_f = 0\Omega$ ,<br>$R_L = 2k\Omega$ to $V_{CM}$ |                 | 100     |                 | ns                |
| $t_s$                        | Settling Time to 0.01%<br>4V Step; 10% to $V_{OUT}$ | $A_V = 1$ , $V_{OUT} = 4V_{P-P}$ , $R_f = 0\Omega$ ,<br>$R_L = 2k\Omega$ to $V_{CM}$    |                 | 4       |                 | $\mu s$           |

NOTE:

6. Compliance to datasheet limits is assured by one or more methods: production test, characterization, and/or design.



## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ C$ , unless otherwise specified.




FIGURE 3. ISL28118 INPUT OFFSET VOLTAGE DISTRIBUTION




FIGURE 4. ISL28118 INPUT OFFSET VOLTAGE DISTRIBUTION




FIGURE 5. ISL28218 INPUT OFFSET VOLTAGE DISTRIBUTION




FIGURE 6. ISL28218 INPUT OFFSET VOLTAGE DISTRIBUTION




FIGURE 7. ISL28118  $TCV_{OS}$  vs NUMBER OF AMPLIFIERS  $\pm 15V$




FIGURE 8. ISL28118  $TCV_{OS}$  vs NUMBER OF AMPLIFIERS  $\pm 5V$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise specified. (Continued)




FIGURE 9. ISL28218  $TCV_{OS}$  vs NUMBER OF AMPLIFIERS  $\pm 15V$




FIGURE 10. ISL28218  $TCV_{OS}$  vs NUMBER OF AMPLIFIERS  $\pm 5V$




FIGURE 11.  $V_{OS}$  vs TEMPERATURE




FIGURE 12. INPUT OFFSET VOLTAGE vs INPUT COMMON MODE VOLTAGE,  $V_S = \pm 15V$




FIGURE 13.  $I_{BIAS}$  vs  $V_S$




FIGURE 14.  $I_{BIAS}$  vs TEMPERATURE vs SUPPLY

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise specified. (Continued)




FIGURE 15. ISL28118 CMRR vs TEMPERATURE,  $V_S = \pm 15V$




FIGURE 16. ISL28118 CMRR vs TEMPERATURE,  $V_S = \pm 5V$




FIGURE 17. ISL28218 CMRR vs TEMPERATURE,  $V_S = \pm 15V$




FIGURE 18. ISL28218 CMRR vs TEMPERATURE,  $V_S = \pm 5V$




FIGURE 19. CMRR vs FREQUENCY,  $V_S = \pm 15V$




FIGURE 20. PSRR vs TEMPERATURE,  $V_S = \pm 15V$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ C$ , unless otherwise specified. (Continued)




FIGURE 21. PSRR vs FREQUENCY,  $V_S = \pm 15V$




FIGURE 22. PSRR vs FREQUENCY,  $V_S = \pm 5V$




FIGURE 23. OPEN-LOOP GAIN, PHASE vs FREQUENCY,  $V_S = \pm 15V$




FIGURE 24. FREQUENCY RESPONSE vs CLOSED LOOP GAIN




FIGURE 25. GAIN vs FREQUENCY vs  $R_L$ ,  $V_S = \pm 15V$




FIGURE 26. GAIN vs FREQUENCY vs  $R_L$ ,  $V_S = \pm 5V$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise specified. (Continued)




FIGURE 27. GAIN vs FREQUENCY vs OUTPUT VOLTAGE




FIGURE 28. GAIN vs FREQUENCY vs SUPPLY VOLTAGE




FIGURE 29. OUTPUT OVERHEAD VOLTAGE vs TEMPERATURE,  
 $V_S = \pm 15V$ ,  $R_L = 10k$




FIGURE 30. OUTPUT OVERHEAD VOLTAGE vs TEMPERATURE,  
 $V_S = \pm 5V$ ,  $R_L = 10k$




FIGURE 31. OUTPUT OVERHEAD VOLTAGE HIGH vs LOAD CURRENT,  
 $V_S = \pm 5V$  AND  $\pm 15V$




FIGURE 32. OUTPUT OVERHEAD VOLTAGE LOW vs LOAD CURRENT,  
 $V_S = \pm 5V$  AND  $\pm 15V$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise specified. (Continued)




FIGURE 33. OUTPUT VOLTAGE SWING vs LOAD CURRENT  $V_S = \pm 15V$




FIGURE 34. OUTPUT VOLTAGE SWING vs LOAD CURRENT  $V_S = \pm 5V$




FIGURE 35. ISL28118 SUPPLY CURRENT vs TEMPERATURE vs SUPPLY VOLTAGE




FIGURE 36. ISL28218 SUPPLY CURRENT vs TEMPERATURE vs SUPPLY VOLTAGE




FIGURE 37. SUPPLY CURRENT vs SUPPLY VOLTAGE

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise specified. (Continued)




FIGURE 38. INPUT NOISE VOLTAGE (en) AND CURRENT (in) vs FREQUENCY,  $V_S = \pm 18V$




FIGURE 39. INPUT NOISE VOLTAGE (en) AND CURRENT (in) vs FREQUENCY,  $V_S = \pm 5V$




FIGURE 40. INPUT NOISE VOLTAGE 0.1Hz TO 10Hz,  $V_S = \pm 18V$




FIGURE 41. INPUT NOISE VOLTAGE 0.1Hz TO 10Hz,  $V_S = \pm 5V$




FIGURE 42. THD+N vs FREQUENCY vs TEMPERATURE,  $A_V = 1, 10$ ,  $R_L = 2k$




FIGURE 43. THD+N vs FREQUENCY vs TEMPERATURE,  $A_V = 1, 10$ ,  $R_L = 10k$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ C$ , unless otherwise specified. (Continued)




FIGURE 44. THD+N vs OUTPUT VOLTAGE ( $V_{OUT}$ ) vs TEMPERATURE,  $A_V = 1, 10$ ,  $R_L = 2k$




FIGURE 45. THD+N vs OUTPUT VOLTAGE ( $V_{OUT}$ ) vs TEMPERATURE,  $A_V = 1, 10$ ,  $R_L = 10k$




FIGURE 46. LARGE SIGNAL 10V STEP RESPONSE,  $V_S = \pm 15V$




FIGURE 47. LARGE SIGNAL 4V STEP RESPONSE,  $V_S = \pm 5V$




FIGURE 48. SMALL SIGNAL TRANSIENT RESPONSE,  $V_S = \pm 5V, \pm 15V$




FIGURE 49. NO PHASE REVERSAL



## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ C$ , unless otherwise specified. (Continued)




FIGURE 50. POSITIVE OUTPUT OVERLOAD RESPONSE TIME,  $V_S = \pm 15V$




FIGURE 51. NEGATIVE OUTPUT OVERLOAD RESPONSE TIME,  $V_S = \pm 15V$




FIGURE 52. POSITIVE OUTPUT OVERLOAD RESPONSE TIME,  $V_S = \pm 5V$




FIGURE 53. NEGATIVE OUTPUT OVERLOAD RESPONSE TIME,  $V_S = \pm 5V$




FIGURE 54. OUTPUT IMPEDANCE vs FREQUENCY,  $V_S = \pm 15V$




FIGURE 55. OUTPUT IMPEDANCE vs FREQUENCY,  $V_S = \pm 5V$

## Typical Performance Curves

$V_S = \pm 15V$ ,  $V_{CM} = 0V$ ,  $R_L = \text{Open}$ ,  $T_A = +25^\circ C$ , unless otherwise specified. (Continued)




FIGURE 56. OVERSHOOT vs CAPACITIVE LOAD,  $V_S = \pm 15V$




FIGURE 57. OVERSHOOT vs CAPACITIVE LOAD,  $V_S = \pm 5V$




FIGURE 58. ISL28118 SHORTCIRCUIT CURRENT vs TEMPERATURE,  $V_S = \pm 15V$




FIGURE 59. ISL28218 SHORTCIRCUIT CURRENT vs TEMPERATURE,  $V_S = \pm 15V$




FIGURE 60. MAX OUTPUT VOLTAGE vs FREQUENCY




FIGURE 61. CHANNEL SEPARATION vs FREQUENCY,  $R_L = \text{INF}$ ,  $V_S = \pm 15V$

## Applications Information

### Functional Description

The ISL28118 and ISL28218 are single and dual, 3.2MHz, single-supply, rail-to-rail output amplifiers with a common mode input voltage range extending to a range of 0.5V below the  $V_{-}$  rail. Their input stages are optimized for precision sensing of ground-referenced signals in single-supply applications. The input stage is able to handle large input differential voltages without phase inversion, making these amplifiers suitable for high-voltage comparator applications. Their bipolar design features high open loop gain and excellent DC input and output temperature stability. These op amps feature very low quiescent current of 850 $\mu$ A and low temperature drift. Both devices are fabricated in a new precision 40V complementary bipolar DI process and are immune from latch-up.

### Operating Voltage Range

The op amp is designed to operate over a single supply range of 3V to 40V or a split supply voltage range of +1.8V/-1.2V to  $\pm$ 20V. The device is fully characterized at 10V ( $\pm$ 5V) and 30V ( $\pm$ 15V). Both DC and AC performance remain virtually unchanged over the complete operating voltage range. Parameter variation with operating voltage is shown in the [“Typical Performance Curves” on page 9](#).

The input common mode voltage to the  $V_{+}$  rail ( $V_{+}$  -1.8V over the full temperature range) may limit amplifier operation when operating from split  $V_{+}$  and  $V_{-}$  supplies. [Figure 12 on page 10](#) shows the common mode input voltage range variation over-temperature.

### Input Stage Performance

The ISL28118 and ISL28218 PNP input stage has a common mode input range extending up to 0.5V below ground at +25°C ([Figure 12](#)). Full amplifier performance is guaranteed down for input voltage down to ground ( $V_{-}$ ) over the -40°C to +125°C temperature range. For common mode voltages down to -0.5V below ground ( $V_{-}$ ), the amplifiers are fully functional, but performance degrades slightly over the full temperature range. This feature provides excellent CMRR, AC performance and DC accuracy when amplifying low-level, ground-referenced signals.

The input stage has a maximum input differential voltage equal to a diode drop greater than the supply voltage (max 42V) and does not contain the back-to-back input protection diodes found on many similar amplifiers. This feature enables the device to function as a precision comparator by maintaining very high input impedance for high-voltage differential input comparator voltages. The high differential input impedance also enables the device to operate reliably in large signal pulse applications, without the need for anti-parallel clamp diodes required on MOSFET and most bipolar input stage op amps. Thus, input signal distortion caused by nonlinear clamps under high slew rate conditions is avoided.

In applications where one or both amplifier input terminals are at risk of exposure to voltages beyond the supply rails, current-limiting resistors may be needed at each input terminal (see [Figure 62](#),  $R_{IN+}$ ,  $R_{IN-}$ ) to limit current through the power-supply ESD diodes to 20mA.




FIGURE 62. INPUT ESD DIODE CURRENT LIMITING

### Output Drive Capability

The bipolar rail-to-rail output stage features low saturation levels that enable an output voltage swing to less than 15mV when the total output load (including feedback resistance) is held below 50 $\mu$ A ([Figures 31](#) and [32](#)). With  $\pm$ 15V supplies, this can be achieved by using feedback resistor values >300k $\Omega$ .

The output stage is internally current limited. Output current limit over-temperature is shown in [Figures 33](#) and [34](#). The amplifiers can withstand a short-circuit to either rail as long as the power dissipation limits are not exceeded. This applies to only one amplifier at a time for the dual op amp. Continuous operation under these conditions may degrade long-term reliability.

The amplifiers perform well when driving capacitive loads ([Figures 56](#) and [57](#)). The unity gain, voltage follower (buffer) configuration provides the highest bandwidth but is also the most sensitive to ringing produced by load capacitance found in BNC cables. Unity gain overshoot is limited to 35% at capacitance values to 0.33nF. At gains of 10 and higher, the device is capable of driving more than 10nF without significant overshoot.

### Output Phase Reversal

Output phase reversal is a change of polarity in the amplifier transfer function when the input voltage exceeds the supply voltage. The ISL28118 and ISL28218 are immune to output phase reversal out to 0.5V beyond the rail ( $V_{ABS\ MAX}$ ) limit ([Figure 49](#)).

### Single Channel Usage

The ISL28218 is a dual op amp. If the application requires only one channel, the user must configure the unused channel to prevent it from oscillating. The unused channel oscillates if the input and output pins are floating. This results in higher than expected supply currents and possible noise injection into the channel being used. The proper way to prevent oscillation is to short the output to the inverting input and ground the positive input ([Figure 63](#)).




FIGURE 63. PREVENTING OSCILLATIONS IN UNUSED CHANNELS

## Power Dissipation

It is possible to exceed the +150°C maximum junction temperatures under certain load and power supply conditions. It is therefore important to calculate the maximum junction temperature ( $T_{JMAX}$ ) for all applications to determine if power supply voltages, load conditions, or package type need to be modified to remain in the safe operating area. These parameters are related using [Equation 1](#):

$$T_{JMAX} = T_{MAX} + \theta_{JA} \times PD_{MAXTOTAL} \quad (EQ. 1)$$

Where

- $PD_{MAXTOTAL}$  is the sum of the maximum power dissipation of each amplifier in the package ( $PD_{MAX}$ )
- $T_{MAX}$  = Maximum ambient temperature
- $\theta_{JA}$  = Thermal resistance of the package

$PD_{MAX}$  for each amplifier can be calculated using [Equation 2](#):

$$PD_{MAX} = V_S \times I_{qMAX} + (V_S - V_{OUTMAX}) \times \frac{V_{OUTMAX}}{R_L} \quad (EQ. 2)$$

Where

- $PD_{MAX}$  = Maximum power dissipation of 1 amplifier
- $V_S$  = Total supply voltage
- $I_{qMAX}$  = Maximum quiescent supply current of one amplifier
- $V_{OUTMAX}$  = Maximum output voltage swing of the application
- $R_L$  = Load resistance

## ISL28118 and ISL28218 SPICE Model

[Figure 64 on page 21](#) shows the SPICE model schematic and [Figure 65 on page 22](#) shows the net list for the SPICE model. The model is a simplified version of the actual device and simulates important AC and DC parameters. AC parameters incorporated into the model are: 1/f and flatband noise voltage, slew rate, CMRR and gain and phase. The DC parameters are  $I_{OS}$ , total supply current and output voltage swing. The model uses typical parameters given in the “Electrical Specifications” table beginning on [page 5](#). The AVOL is adjusted for 136dB with the dominant pole at 0.6Hz. The CMRR is set at 120dB,  $f = 50kHz$ . The input stage models the actual device to present an accurate AC representation. The model is configured for an ambient temperature of +25°C.

[Figures 66](#) through [80](#) show the characterization vs simulation results for the noise voltage, open loop gain phase, closed loop gain vs frequency, gain vs frequency vs  $R_L$ , CMRR, large signal 10V step response, small signal 0.1V step and output voltage swing  $\pm 15V$  supplies.

## LICENSE STATEMENT

The information in the SPICE model is protected under United States copyright laws. Intersil Corporation hereby grants users of this macro-model, hereto referred to as “Licensee”, a nonexclusive, nontransferable licence to use this model, as long as the Licensee abides by the terms of this agreement. Before using this macro-model, the Licensee should read this license. If the Licensee does not accept these terms, permission to use the model is not granted.

The Licensee may not sell, loan, rent, or license the macro-model, in whole, in part, or in modified form, to anyone outside the Licensee’s company. The Licensee may modify the macro-model to suit his/her specific applications and the Licensee may make copies of this macro-model for use within their company only.

This macro-model is provided “AS IS, WHERE IS AND WITH NO WARRANTY OF ANY KIND EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.”

In no event will Intersil be liable for special, collateral, incidental, or consequential damages in connection with, or arising out of, the use of this macro-model. Intersil reserves the right to make changes to the product and the macro-model without prior notice.




FIGURE 64. SPICE SCHEMATIC

```

*ISL28118_218 Macromodel - covers
following *products
*ISL28118
*ISL28218
*
*Revision History:
* Revision B, LaFontaine January 22 2014
* Model for Noise, supply currents, CMRR
*120dB f = 40kHz, AVOL 136dB f = 0.5Hz
* SR = 1.2V/us, GBWP 4MHz.
*Copyright 2011 by Intersil Corporation
*Refer to data sheet "LICENSE STATEMENT"
*Use of this model indicates your acceptance
*with the terms and provisions in the License
*Statement.
*
*Intended use:
*This Pspice Macromodel is intended to give
*typical DC and AC performance
*characteristics *under a wide range of
*external circuit *configurations using
*compatible simulation *platforms – such as
*iSim PE.
*
*Device performance features supported by
this *model:
*Typical, room temp., nominal power supply
*voltages used to produce the following
*characteristics:
*Open and closed loop I/O impedances,
*Open loop gain and phase,
*Closed loop bandwidth and frequency
*response,
*Loading effects on closed loop frequency
*response,
*Input noise terms including 1/f effects,
*Slew rate,
*Input and Output Headroom limits to I/O
*voltage swing,
*Supply current at nominal specified supply
*voltages,
*
*Device performance features NOT
supported *by this model:
*Harmonic distortion effects,
*Output current limiting (current will limit at
*40mA),
*Disable operation (if any),
*Thermal effects and/or over-temperature
*parameter variation,
*Limited performance variation vs. supply
*voltage is modeled,
*Part to part performance variation due to
*normal process parameter spread,
*Any performance difference arising from
*different packaging,
*Load current reflected into the power supply
*current.
*
* source ISL28118_218 SPICEmodel
*
* Connections:      +input
*                   |
*                   | -input
*                   |
*                   | +Vsupply
*                   |
*                   | -Vsupply
*                   |
*                   | output
.subckt ISL28118_218 Vin+ Vin-Vs V_ VOUT
* source ISL28118_218_presubckt_0
*
*Voltage Noise
E_En      VIN+ 6 2 0 0.3
D_D13     1 2 DN
D_D14     1 2 DN
V_V7      1 0 0.1
V_V8      4 0 0.1
R_R17     2 0 750
*R_R18     3 0 750
*
*Input Stage
Q_Q6      11 10 9 PNP_input
Q_Q7      8 7 9 PNP_input
Q_Q8      V-- VIN- 7 PNP_LATERAL
Q_Q9      V-- 12 10 PNP_LATERAL
I_I1      V++ 9 DC 80e-6
I_I2      V++ 7 DC 54E-6
I_I3      V++ 10 DC 54E-6
I_IOS     6 VIN- DC 4e-9
D_D1      7 10 DBREAK
D_D2      10 7 DBREAK
R_R1      5 6 5e11
R_R2      VIN- 5 5e11
R_R3      V-- 8 1000
R_R4      V-- 11 1000
C_Cin1     V-- VIN- 4.02e-12
C_Cin2     V-- 6 4.02e-12
C_CinDif   6 VIN- 1.33E-12
*
*1st Gain Stage
G_G1      V++ 14 8 11 0.65897
G_G2      V-- 14 8 11 0.65897
V_V1      13 14 -0.91
V_V2      14 15 -0.96
D_D3      13 V++ DX
D_D4      V-- 15 DX
R_R5      14 V++ 1
R_R6      V-- 14 1
*
*2nd Gain Stage
G_G3      V++ VG 14 VMID 1.69138e-3
G_G4      V-- VG 14 VMID 1.69138e-3
V_V3      16 VG -0.91
V_V4      VG 17 -0.96
D_D5      16 V++ DX
D_D6      V-- 17 DX
R_R7      VG V++ 3.7304227e9
R_R8      V-- VG 3.7304227e9
C_C1      VG V++ 6.6667E-11
C_C2      V-- VG 6.6667E-11
*
*Mid supply Ref
E_E2      V++ 0 V+ 0 1
E_E3      V-- 0 V- 0 1
E_E4      VMID V-- V++ V-- 0.5
I_ISY     V+ V- DC 0.85E-3
*
*Common Mode Gain Stage with Zero
G_G5      V++ 19 5 VMID 1
G_G6      V-- 19 5 VMID 1
G_G7      V++ VC 19 VMID 1
G_G8      V-- VC 19 VMID 1
E_EOS     12 6 VC VMID 1
L_L1      18 V++ 3.18319E-09
L_L2      20 V-- 3.18319E-09
L_L3      21 V++ 3.18319E-09
L_L4      22 V-- 3.18319E-09
R_R9      19 18 1e-3
R_R10     20 19 1e-3
R_R11     VC 21 1e-3
R_R12     22 VC 1e-3
*
*Pole Stage
G_G9      V++ 23 VG VMID 1.2566e-3
G_G10     V-- 23 VG VMID 1.2566e-3
R_R13     23 V++ 795.7981
R_R14     V-- 23 795.7981
C_C3      23 V++ 10e-12
C_C4      V-- 23 10e-12
*
*Output Stage with Correction Current
Sources
G_G11     26 V-- VOUT 23 12.5e-3
G_G12     27 V-- 23 VOUT 12.5e-3
G_G13     VOUT V++ V++ 23 12.5e-3
G_G14     V-- VOUT 23 V-- 12.5e-3
D_D7      23 24 DX
D_D8      25 23 DX
D_D9      V-- 26 DY
D_D10     V++ 26 DX
D_D11     V++ 27 DX
D_D12     V-- 27 DY
V_V5      24 VOUT -0.4
V_V6      VOUT 25 -0.4
R_R15     VOUT V++ 80
R_R16     V-- VOUT 80
.model PNP_LATERAL pnp(is=1e-016
bf=250 va=80
+ ik=0.138 rb=0.01 re=0.101 rc=180 kf=0
af=1)
.model PNP_input pnp(is=1e-016 bf=100
va=80
+ ik=0.138 rb=0.01 re=0.101 rc=180 kf=0
af=1)
.model DBREAK D(bv=43 rs=1)
.model DN D(KF=6.69e-9 AF=1)
.MODEL DX D(IS=1E-12 Rs=0.1)
.MODEL DY D(IS=1E-15 BV=50 Rs=1)
.ends ISL28118_218

```

FIGURE 65. SPICE NET LIST

## Characterization vs Simulation Results




FIGURE 66. CHARACTERIZED INPUT NOISE VOLTAGE




FIGURE 67. SIMULATED INPUT NOISE VOLTAGE




FIGURE 68. CHARACTERIZED OPEN-LOOP GAIN, PHASE vs FREQUENCY




FIGURE 69. SIMULATED OPEN-LOOP GAIN, PHASE vs FREQUENCY




FIGURE 70. CHARACTERIZED CLOSED-LOOP GAIN vs FREQUENCY




FIGURE 71. SIMULATED CLOSED-LOOP GAIN vs FREQUENCY

## Characterization vs Simulation Results (Continued)




FIGURE 72. CHARACTERIZED GAIN vs FREQUENCY vs  $R_L$ FIGURE 73. SIMULATED GAIN vs FREQUENCY vs  $R_L$ 

FIGURE 74. CHARACTERIZED CMRR vs FREQUENCY




FIGURE 75. SIMULATED CMRR vs FREQUENCY




FIGURE 76. CHARACTERIZED LARGE-SIGNAL 10V STEP RESPONSE




FIGURE 77. SIMULATED LARGE-SIGNAL 10V STEP RESPONSE



## Characterization vs Simulation Results (Continued)




FIGURE 78. CHARACTERIZED SMALL-SIGNAL TRANSIENT RESPONSE




FIGURE 79. SIMULATED SMALL-SIGNAL TRANSIENT RESPONSE




FIGURE 80. SIMULATED OUTPUT VOLTAGE SWING

## Revision History

The revision history provided is for informational purposes only and is believed to be accurate, but not warranted. Please go to web to make sure you have the latest Rev.

| DATE         | REVISION | CHANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Jan 16, 2020 | FN7532.8 | Updated links throughout document.<br>Updated Related Literature section.<br>Updated ordering information table by adding tape and reel information and updating note 1.<br>Updated Figures 38, 39, and 66, changed unit from fA to pA.<br>Removed About Intersil section.<br>Updated disclaimer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Jul 27, 2015 | FN7532.7 | Page 1 under Features:<br>Removed bullet 3 (Rail-to-rail input differential voltage range for comparator application).<br>Added to the end of bullet 2 "ground sensing".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Jul 15, 2015 | FN7532.6 | Figures 48 and 78 changed Y-axis from (V) to (mV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| May 1, 2014  | FN7532.5 | Updated Spice model netlist on page 22.<br>Absolute Maximum Ratings table on page 5: Added ESD Tolerance (ISL28118 SOIC package only).<br>Changed POD:<br>FROM M8.118: Corrected lead width dimension in side view 1 from "0.25 - 0.036" to "0.25 - 0.36"<br>To M8.118B: Correct lead dimension in side view 2 from 0.15 - 0.05mm to 0.15+/-0.05mm.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Jan 24, 2013 | FN7532.4 | Added ISL28218 MSOP specifications, and removed references to ISL28118 and ISL28218 TDFN options.<br>page 1: Removed "8 Ld TDFN" from last paragraph of description.<br>page 3: Removed TDFN "Pin Configurations", and TDFN columns and the "PAD" row from "Pin Descr" table.<br>Moved Ordering Information table from pg 3 to page 2. Removed "Coming Soon" from ISL28218FUZ and added "Note 1" reference, and deleted 2 TDFN offerings in "Ordering Info" table.<br>page 5: Removed TDFN entries from "Thermal Resistance" section, and removed notes 5 and 6.<br>Added delta Vos MSOP row, with limits of $\pm 390\mu\text{A}$ , and added "ISL28218" to the CMRR MSOP entry.<br>page 6: added "ISL28218" to the existing AVOL MSOP entry.<br>page 7: added new +25°C 28218 MSOP row with 107dB min limit, and added "ISL28218 MSOP" to the existing ISL28118 MSOP full temp row for PSRR.<br>page 7: added "ISL28218" to the existing CMRR SOIC and MSOP rows, and deleted the "ISL28218" rows.<br>page 7: added "ISL28218 MSOP" to the existing ISL28118 MSOP rows for AVOL.<br>page 9: added "+25°C" to "default conditions" info at top of page.<br>Moved "sales Info" from p25 to p23.<br>Removed TDFN package outline drawing. |
| Aug 31, 2011 | FN7532.3 | Page 7: Electrical Spec Table for Supply Current/Amplifier<br>Change from: 1.4 $\mu\text{A}$ Full Temp Max<br>Change to: 1.4mA Full Temp Max<br>Page 28: Updated POD M8.118 to current revision. Corrected lead width dimension in side view 1 from "0.25 - 0.036" to "0.25 - 0.36".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| May 9, 2011  | FN7532.2 | Page 2: Added NC pin to Pin Descriptions table.<br>Page 3: Added ISL28218EVAL1Z evaluation board to the Ordering Information table.<br>Page 12: Added new Output Overhead Voltage plots (Figs. 31,32)<br>Pages 19 through 24: Added SPICE model schematic, netlist, description and Figs. 66 through 80.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

The revision history provided is for informational purposes only and is believed to be accurate, but not warranted. Please go to web to make sure you have the latest Rev. **(Continued)**

| DATE          | REVISION | CHANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nov 12, 2010  | FN7532.1 | <p>On page 1: Features Section, added Low input offset voltage and superb offset voltage temperature drift for ISL28118.</p> <p>Updated Intersil trademark statement (bottom of page)</p> <p>On page 4: Removed "coming soon" from ISL28118FBZ. Updated tape &amp; reel note.</p> <p>On page 5: Change ISL28118 Theta JA value from 158 to 165. Added ISL28118 min/max specs to VOS (input offset voltage), TCVOS and min specs to CMRR.</p> <p>On page 6: Added AVOL MIN spec for ISL28118 in dB. Changed existing AVOL spec from V/mV to dB. Added VOL max spec for ISL28118, IS Typ and Max spec for ISL28118. Changed TS from 18<math>\mu</math>s to 8.5<math>\mu</math>s.</p> <p>On page 7: Added Min Max VOS spec, TCVOS spec for ISL28118. Changed AVOL specs from V/mV to dB.</p> <p>On page 8: Changed Slew Rate TYP from <math>\pm 1.2V/\mu s</math> to <math>\pm 1V/\mu s</math>. Added for TS TYP spec = 4<math>\mu</math>s. Changed min/max note 6 to "Compliance to datasheet limits is assured by one or more methods: production test, characterization and/or design." Added Figs 3 &amp; 4 for ISL28118. Figures 5 &amp; 6 moved to page 9.</p> <p>On page 9: Added Figures 7 &amp; 8</p> <p>On page 11: Added Figures 15 &amp; 16 for ISL28118</p> <p>On page 11, in Figure 19, changed VS from <math>\pm 5V</math> to <math>\pm 15V</math></p> <p>On page 13 and page 14: Added Figures 27, 28, 31 &amp; 34 for ISL28118</p> <p>On page 14: Added Figure 35 for ISL28118</p> <p>On page 15: Figure 41 changed VS from <math>\pm 18V</math> to <math>\pm 5V</math>, Figure 42 added RL = 2k, Figure 43 added RL = 10k and corrected "HD+N" to "THD+N"</p> <p>On page 16, Figure 44 added RL = 2k, Figure 45 RL = 10k.</p> <p>On page 18: Added Figure 58 for ISL28118</p> <p>On page 18, Figure 58 and 59, graph upper left corner changed VS = <math>\pm 5V</math> to VS = <math>\pm 15V</math></p> <p>On page 18, Figure 61, deleted VS = <math>\pm 5V</math></p> |
| Sept 16, 2010 | FN7532.0 | Initial Release                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |






# Package Outline Drawings

For the most recent package outline drawing, see [M8.15E](#).

M8.15E

8 LEAD NARROW BODY SMALL OUTLINE PLASTIC PACKAGE

Rev 0, 08/09




## NOTES:


1. Dimensions are in millimeters.  
Dimensions in ( ) for Reference Only.
2. Dimensioning and tolerancing conform to AMSE Y14.5m-1994.
3. Unless otherwise specified, tolerance : Decimal  $\pm 0.05$
4. Dimension does not include interlead flash or protrusions.  
Interlead flash or protrusions shall not exceed 0.25mm per side.
5. The pin #1 identifier may be either a mold or mark feature.
6. Reference to JEDEC MS-012.

**M8.118B**  
**8 LEAD MINI SMALL OUTLINE PLASTIC PACKAGE**  
 Rev 1, 3/12


For the most recent package outline drawing, see [M8.118B](#).




**TOP VIEW**




**SIDE VIEW 2**



**SIDE VIEW 1**



**DETAIL "X"**



**TYPICAL RECOMMENDED LAND PATTERN**

**NOTES:**

1. Dimensions are in millimeters.
2. Dimensioning and tolerancing conform to JEDEC MO-187-AA and AMSEY14.5m-1994.
3. Plastic or metal protrusions of  $0.15 \text{ mm}$  max per side are not included.
4. Plastic interlead protrusions of  $0.15 \text{ mm}$  max per side are not included.

5. Dimensions are measured at Datum Plane "H".

6. Dimensions in ( ) are for reference only.

## Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
4. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
5. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.

6. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
7. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
8. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
9. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
10. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
11. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.4.0-1 November 2017)

## Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,  
Koto-ku, Tokyo 135-0061, Japan  
[www.renesas.com](http://www.renesas.com)

## Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:  
[www.renesas.com/contact/](http://www.renesas.com/contact/)

## Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.