

TL-176 Tension Latch Receptacle




Characteristic

It is used for keeping an arm of tension latch steady and where tension latch is installed on a flat plane.

Application

Tension latch



Specification

Model No.	Material	Finish	Net Weight (g)	Code No.	Applicable Latch
TL-176-1	SPCC	—	12.8	1023	TL-11-1,-4
TL-176-2			4.0	1025	TL-11-2,-3,-5
TL-176-3			2.7	1026	TL-11-2,-3,-5
TL-176-4			4.2	1046	TL-11-2

Size List


Model No.	A	B	C	D	E	F	G	H	J	K	t
TL-176-1	37.0	25.0	21.0	25.0	12.0	6.0	8	11.0	R2.5	5.5	2.0
TL-176-2	23.5	16.0	14.0	15.5	6.5	3.25	5	7.0	R1.5	3.2	1.6
TL-176-3	22.5	13.5	15.5	14.5	7.5	3.5		6.5	R2.25	3.5	1.0
TL-176-4	23.5	—	14.0	15.5	6.5	—		7.0	R1.5	—	1.6

TL-177 TL-178 Tension Latch Receptacle



Characteristic

It is used where tension latch is installed on a corner.



Specification

Model No.	Material	Finish	Net Weight (g)	Code No.
TL-177	SPCC	—	22.2	1024
TL-178			7.5	1027