


2mm x 5mm Rectangular LED CBI® Circuit Board Indicator 12 LED Array

Dialight

566-xx08



PART NO

COLOR

566-0208
566-0308
566-0408

Green
Yellow
Red

Features

- Multiple CBIs form horizontal LED arrays on 7.0mm (0.276") center-lines.
- High Contrast, UL 94 V-0 rated, black housing
- Oxygen index: 32%
- Polymer content: PBT, 8.948 g
- Housing stand-offs facilitate PCB cleaning
- Solderability per MIL-STD-202F, method 208F
- LEDs are safe for direct viewing per IEC 825-1, EN-60825-1

Custom Combinations

- For custom color combinations contact factory

Tolerance note: As noted, otherwise:

- LED Protrusion: ± 0.04 mm [± 0.016]
- CBI Housing: ± 0.02 mm [± 0.008]

Typical Operating Characteristics ($T_A = 25^\circ\text{C}$)

See LED data sheet for additional information

See Page 5-20 and 5-21 for Reference Only LED Drive Circuit Example


See Page 5-22 for Pin Out

Part Number	Color	Peak Wavelength nm	I_v mcd	V_F Volts	Test Current (mA)	Viewing Angle $2\theta_{1/2}$	LED Data sheet	Page #
566-0208	Green	565	4	2.2	20	110°	521-9332	5-16
566-0308	Yellow	583	3.5	2.1	20	110°	521-9452	5-16
566-0408	Red	635	7.4	2	20	140°	521-9499	5-16

2mm x 5mm Discrete LED
Rectangular
Tinted, Diffused

Dialight

521-9332, -9452, -9499, -9718



PART NO.	COLOR	DRAWING
521-9332	Green	A
521-9452	Yellow	A
521-9499	Red	B
521-9718	Blue	B

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)	Green -9332	Yellow -9452	Red -9499	Blue -9718
Power Dissipation (mW)	135	85	100	189
Forward Current (mA)	30	20	30	30
Derating (mA/ $^\circ\text{C}$) From 50°C 1. mW/ $^\circ\text{C}$ From 25°C	.5	.34	.4	.45 ¹
Peak Current (mA)	500*	500*	120	180
Pulse width = 1 ms *Pulse width = 10 μs				
Operating Temperature ($^\circ\text{C}$)	-20/+100	-55/+100	-55/+100	-25/+75
Storage Temperature ($^\circ\text{C}$)	-55/+100	-55/+100	-55/+100	-25/+100
Soldering Temperature	260 $^\circ\text{C}$, 5 seconds, 1.6 mm from case			

Solder Adherence per MIL-STD-202E, Method 208C

OPERATING CHARACTERISTICS ($T_A=25^\circ\text{C}$)		Green -9332	Yellow -9452	Red -9499	Blue -9718
Luminous Intensity (mcd)	Min.	2.6	2.2	3	9
	Typical	4	3.5	7.4	18
Peak Wavelength (nm)	Typical	565	583	635	430
λ Peak					
Viewing Angle (2θ $^\circ$)	Typical	110 $^\circ$	110 $^\circ$	140 $^\circ$	120 $^\circ$
Forward Voltage (V)	Typical	2.2	2.1	2	5.3
	Max.	3	2.6	2.8	6
Reverse Voltage (V), $I_R=100\mu\text{A}$	Min.	5	5	5	5

θ $^\circ$ is the off axis angle at which the luminous intensity is half the axial luminous intensity