





REVISION HISTORY

DESCRIPTION

DCN 42242

APPROVED

STW

DATE

06/16

FINISH:

BODY & CONTACT:

GOLD PER ASTM B488, TYPE II, CODE C, CLASS 1.27, OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

PERFORMANCE:

IMPEDANCE: 50 OHMS NOTES:

TO BE TIN DIPPED USING Sn96 SOLDER. ALL DIMENSIONS APPLY PRIOR TO SOLDER DIPPING.

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X* ±1*0' X*X' ±15' DECIMAL: .X ±.030	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 151 & LAST THREADS. 5) SURFACE ROUGHNESS 63.4MIL-STD-10. 6) DIA: SON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS		SV Microwave, Inc.		
FINISH:	SEE NOTES				2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409		
SURFACE AR	^{EA:} N/A				2-PORT SMPM MALE FD R/A CONTACT PCB MOUNT		
1	PROPRIETARY TION CONTAINED IN THIS DRAWING		DRAWN:	MAL 06/21/16	R/A CC	NTACT PCB MC	JUNI
IS THE SOLE PR ANY REPRODUC WITHOUT THE V	PROPERTY OF SV MICROWAVE, INC. DUCTION IN PART OR AS A WHOLE E WRITTEN PERMISSION OF IVE, INC IS PROHIBITED.	⊕	CHECKED:	STW 06/21/16	B 95077	DWG. NO. 3211-40	024-TD
			APPROVED:	STW 06/21/16	SCALE: 12:1		SHEET 1 OF 1