

Features

Regulated Converter

- 2MOPP, 250VAC working voltage isolation
- Clearance and creepage distance >8mm
- Up to 10kVDC reinforced insulation
- IEC/EN/UL 60601 certified with CB Report (3rd Ed. Safety, 4th Ed. EMC)
- -40°C to +75°C operation, no derating
- 2:1 wide input range

RECOM
DC/DC Converter

REM6E

6 Watt
2:1 Input
DIP24
Single & Dual
Output



Description

The REM6E series of medical grade regulated DC/DC converters feature reinforced 250VAC continuous working isolation with >8mm creepage/clearance. The compact DIP24 package offers industry standard pinouts with tightly regulated single/dual outputs and UVLO, SCP, OCP and OVP. The operating ambient temperature range is from -40°C to +75°C without derating. The converters are UL marked and certified to CB, IEC, EN and ANSI/AAMI 60601 3rd. Ed. Safety and 4th Ed. EMC medical standards. The low 1µA leakage current makes them suitable for medical B, BF and CF applications.

Selection Guide


Part Number	nom. Input Voltage [VDC]	Output Voltage [VDC]	Output Current [mA]	Efficiency typ. ⁽¹⁾ [%]	Max. Capacitive Load ⁽²⁾ [µF]
REM6E-xx09S/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	9	667	81 / 82 / 83	2200
REM6E-xx12S/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	12	500	82 / 83 / 84	2200
REM6E-xx15S/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	15	400	83 / 84 / 84	2200
REM6E-xx24S/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	24	250	83 / 84 / 85	1000
REM6E-xx09D/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	±9	±335	81 / 82 / 83	±2200
REM6E-xx12D/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	±12	±250	82 / 83 / 84	±2200
REM6E-xx15D/R ⁽³⁾ /A ^(4,5)	12 / 24 / 48	±15	±200	83 / 84 / 84	±2200

Notes:

Note1: Efficiency is tested at nominal input and full load at +25°C ambient

Note2: Max Cap Load is tested at nominal input and full resistive load

Model Numbering



Notes:

Note3: add suffix „/R8“ for 8kVDC or „/R10“ for 10kVDC isolation

Note4: add suffix „/CTRL“ for fitted CTRL pin

Note5: add suffix „/X1“ for Under Voltage Lockout Option

IEC60601-1 pending
EN60601-1 pending
IEC60601-1-2 pending

Ordering Examples

REM6E-1209S/R8/A

= 12Vin, 9Vout, single, 8kVDC isolation and „A“ pinning

REM6E-1212D/R8/A/CTRL

= 12Vin, 12Vout, dual, 8kVDC isolation, „A“ pinning and with CTRL pin

REM6E-2448S/R8/A/X1

= 24Vin, 48Vout, single, 8kVDC isolation, „A“ pinning and with UVLO Option

REM6E-2424D/R10/A/CTRL/X1

= 24Vin, 24Vout, dual, 10kVDC isolation, „A“ pinning, CTRL pin and UVLO option

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)


BASIC CHARACTERISTICS

Parameter	Condition		Min.	Typ.	Max.
Internal Input Filter			Pi-type		
Input Voltage Range	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC		9VDC 18VDC 36VDC	12VDC 24VDC 48VDC	18VDC 36VDC 75VDC
Under Voltage Lockout (UVLO) („X1“ version)	nom. Vin= 12VDC	DC-DC ON DC-DC OFF		7.9VDC	9VDC
	nom. Vin= 24VDC	DC-DC ON DC-DC OFF		16.7VDC	18VDC
	nom. Vin= 48VDC	DC-DC ON DC-DC OFF		34.3VDC	36VDC
Input Current	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC			650mA 320mA 150mA	
Quiescent Current	nom. Vin = 12VDC nom. Vin = 24VDC nom. Vin = 48VDC				35mA 25mA 7mA
Minimum Load ⁽⁷⁾				10%	
Start-up time				0.6ms	
Rise time				0.45ms	
Hold-up time				0.6ms	
ON/OFF CTRL	DC-DC ON DC-DC OFF		Open or $0V < V_{CTRL} < 1.2V$ Short or $4.8V < V_{CTRL} < 12VDC$		
Input Current of CTRL Pin	@5V V _{CTRL}			25mA	
Standby Current	DC-DC OFF				350µA
Internal Operating Frequency			120kHz		
Output Ripple and Noise ⁽⁶⁾	20MHz BW				150mVp-p

Notes:

Note6: Measurements are made with a 1.0µF MLCC across output. (low ESR)

ON/OFF CTRL Option





R1
470Ω



continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Efficiency vs. Output Load



Efficiency vs. Input Voltage



REGULATIONS

Parameter	Condition	Value
Output Accuracy		±1.5% typ.
Line Regulation	low line to high line, full load	±0.3% max.
Load Regulation ⁽⁷⁾	10% to 100% load	0.5% typ.
Cross Regulation	dual output only	±5.0% max.
Transient Response	25% load step change	5ms



Notes:

Note7: Operation below 10% load will not harm the converter, but specifications may not be met

continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Deviation vs. Load



PROTECTIONS

Parameter	Type			Value
Short Circuit Protection (SCP)	below 100mΩ			continuous, hiccup mode, automatic recovery
Isolation Voltage ⁽⁸⁾	"/R8" suffix	I/P to O/P	tested for 1 second rated for 1 minute	8kVDC 4kVAC/60Hz
	"/R10" suffix	I/P to O/P	tested for 1 second rated for 1 minute	10kVDC 5kVAC/60Hz
Isolation Resistance				10GΩ min.
Isolation Capacitance				20pF typ.
Insulation Grade				reinforced
Leakage Current				0.8μA typ. / 1μA max.
Means of Protection				2MOPP
Medical Device Classification				built-in power supply
Internal	clearance/creepage			>8mm
External	clearance/creepage			>8mm

Notes:

Note8: For repeat Hi-Pot testing, reduce the time and/or the test voltage

Note9: Refer to local safety regulations if input over-current protection is also required. Recommended fuse: slow blow type

ENVIRONMENTAL


Parameter	Condition		Value
Operating Temperature Range	full load @ natural convection 0.1m/s (see graph)		-40°C to +75°C
Maximum Case Temperature			+105°C
Temperature Coefficient			±0.02%/K typ. / ±0.05%/K max.
Thermal Impedance	0.1m/s, horizontal		20K/W
Operating Altitude			3000m
Operating Humidity	non-condensing		5% - 95% RH max.
Pollution Degree			PD2
MTBF	according to MIL-HDBK-217F, G.B.	+25°C + 75°C	2100 x 10 ³ hours 620 x 10 ³ hours

continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Derating Graph

(@ Chamber and natural convection 0.1 m/s)



SAFETY AND CERTIFICATIONS

Certificate Type (Safety)	Report / File Number	Standard
Medical Electric Equipment, General Requirements for Safety and Essential Performance	pending	CAN/CSA-C22.2 No. 60601-1:14, 3rd Edition: 2014 ANSI/AAMI ES60601-1:2012
Medical Electric Equipment, General Requirements for Safety and Essential Performance	pending	EN60601-1:2006 + A12:2014
Medical Electric Equipment, General Requirements for Safety and Essential Performance (CB Scheme)	pending	IEC60601-1:2005, 3rd Edition + AM1:2012
RoHS 2+		RoHS 2011/65/EU + AM2015/863


EMC Compliance	Condition	Standard / Criterion
Medical electrical equipment Part 1-2: Electromagnetic disturbances – Requirements and tests	pending	IEC60601-1-2
Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement	with external filter	EN55032, Class A and B
ESD Electrostatic discharge immunity test	Air±15kV; Contact±8kV	EN61000-4-2, Criteria A
Radiated, radio-frequency, electromagnetic field immunity test	10V/m	EN61000-4-3, Criteria A
Fast Transient and Burst Immunity	DC Port: ±2kV	EN61000-4-4, Criteria A
Surge Immunity	DC Port: ±1kV	EN61000-4-5, Criteria A
Immunity to conducted disturbances, induced by radio-frequency fields	10Vr.m.s	EN61000-4-6, Criteria A

continued on next page

Specifications (measured @ $T_a = 25^\circ\text{C}$, nom. V_{in} , full load and after warm-up unless otherwise stated)

EMC Filtering Suggestions according to EN55032


Class A



Component List Class A

MODEL	C1	C2	C3	C4	L1
REM6E-12xxS/R/A	4.7μF/50V	N/A	100pF/12kV	N/A	3.3μH
REM6E-24xxS/R/A	10μF/100V		150pF/12kV		
REM6E-48xxS/R/A			100pF/12kV	100pF/12kV	
REM6E-12xxD/R/A	4.7μF/50V		150pF/12kV	150pF/12kV	
REM6E-24xxD/R/A	10μF/100V				
REM6E-48xxD/R/A					

Class B



Component List Class B

MODEL	C1	C2	C3	C4	L1	CMC
REM6E-12xxS/R/A	4.7 μF /50V	4.7 μF /50V	220pF/12kV	N/A	50 μH	N/A
REM6E-24xxS/R/A	10 μF /100V	10 μF /100V	220pF/12kV		N/A	1mH
REM6E-48xxS/R/A			330pF/12kV			
REM6E-12xxD/R/A	4.7 μF /50V	4.7 μF /50V	220pF/12kV	220pF/12kV	50 μH	N/A
REM6E-24xxD/R/A	10 μF /100V	10 μF /100V	220pF/12kV	220pF/12kV		
REM6E-48xxD/R/A			330pF/12kV	330pF/12kV	N/A	1mH






Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

DIMENSION and PHYSICAL CHARACTERISTICS

Parameter	Type	Value
Material	base	non-conductive black plastic, (UL94 V-0)
	case	non-conductive black plastic, (UL94 V-0)
	potting	silicone, (UL94 V-0)
Dimension (LxWxH)		31.8 x 20.3 x 10.2mm
Weight		14g typ.

Dimension Drawing (mm)

"A" Pinning



Pin Connections

Pin #	Single	Dual
1	CTRL (option)	CTRL (option)
2	-Vin	-Vin
11	NC	-Vout
14	+Vout	+Vout
16	-Vout	Com
22	+Vin	+Vin
23	+Vin	+Vin

Tolerance:
XX.X ± 0.5mm
XX.XX ± 0.25mm

PACKAGING INFORMATION

Parameter	Type	Value
Packaging Dimension (LxWxH)	tube	530.0 x 22.7 x 18.3mm
Packaging Quantity	tube	15pcs
Storage Temperature Range		-55°C to +125°C
Storage Humidity		95% RH max.

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.