

SPECIFICATION CONTROL DRAWING

55PC7001

Title

TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT


Date

02-24-04

Revision

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC7000



ADDITIONAL REQUIREMENTS

SOLDERABILITY: 95% (minimum) coverage per MIL-STD-202, Method 208 (1 hour steam aging)

Except as specified above, this construction shall meet all the requirements of Raychem Specification Sheet 55PC0121 for AWG sizes 22 through 16.

*Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.
Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.*

^{1/} COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.