



Features

- High current up to 10 A
- Lead free version available (see How to Order)
- Lead free versions are RoHS compliant*

Applications

- DC/DC converters
- Power supplies

LPV Series Radial Power Inductors


General Specifications

Temperature Rise45 °C max. at rated current
 Operating Temperature...-20 °C to +80 °C
 Storage Temperature....-25 °C to +85 °C

Materials


Core MaterialFerrite DR core
 WireEnamelled copper wire
 Lead.....See How to Order
 TubeShrinkable tube 125 °C, 600 V

Product Dimensions



DIMENSIONS ARE: $\frac{\text{MM}}{(\text{INCHES})}$

Electrical Schematic



How to Order

LPV1620 - 102K

Model: see table _____
 Value/Tolerance: from table _____
 Lead _____
 L = Cu/Sn
 Blank = Cu/SnPb

Electrical Characteristics and Product Dimensions

BOURNS Part No.	Inductance (μ H) 1KHz	RDC (Ω) max.	IDC (A) max.	Dimensions			
				A max.	B max.	F	W dia.
LPV1620-100M_	10 $\pm$ 20 %	0.024	5.0	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620-250K_	25 $\pm$ 10 %	0.040	4.0	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620-500K_	50 $\pm$ 10 %	0.060	3.0	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620-101K_	100 $\pm$ 10 %	0.090	2.0	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620--251K_	250 $\pm$ 10 %	0.180	1.5	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620-501K_	500 $\pm$ 10 %	0.400	1.0	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1620-102K_	1000 $\pm$ 10 %	0.800	0.7	$\frac{16.0}{(.630)}$	$\frac{20.0}{(.787)}$	$\frac{8.0 \pm 1.5}{(.315 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-100M_	10 $\pm$ 20 %	0.009	8.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{14.0 \pm 1.5}{(.551 \pm .059)}$	$\frac{1.2 \pm 0.1}{(.047 \pm .004)}$
LPV1823-250K_	25 $\pm$ 10 %	0.022	6.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{14.0 \pm 1.5}{(.551 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-500K_	50 $\pm$ 10 %	0.036	4.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{14.0 \pm 1.5}{(.551 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-101K_	100 $\pm$ 10 %	0.090	3.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{9.0 \pm 1.5}{(.354 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-251K_	250 $\pm$ 10 %	0.150	2.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{9.0 \pm 1.5}{(.354 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-501K_	500 $\pm$ 10 %	0.300	1.2	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{9.0 \pm 1.5}{(.354 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV1823-102K_	1000 $\pm$ 10 %	0.600	1.0	$\frac{18.0}{(.709)}$	$\frac{23.0}{(.906)}$	$\frac{9.0 \pm 1.5}{(.354 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-100M_	10 $\pm$ 20 %	0.008	10.0	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{15.5 \pm 1.5}{(.610 \pm .059)}$	$\frac{1.3 \pm 0.1}{(.051 \pm .004)}$
LPV2023-500K_	50 $\pm$ 10 %	0.032	5.0	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{15.5 \pm 1.5}{(.610 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-101K_	100 $\pm$ 10 %	0.060	4.0	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{15.5 \pm 1.5}{(.610 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-251K_	250 $\pm$ 10 %	0.140	2.5	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{12.5 \pm 1.5}{(.492 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-501K_	500 $\pm$ 10 %	0.280	1.5	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{12.5 \pm 1.5}{(.492 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-102K_	1000 $\pm$ 10 %	0.550	1.2	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{12.5 \pm 1.5}{(.492 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$
LPV2023-202K_	2000 $\pm$ 10 %	1.200	0.8	$\frac{20.0}{(.787)}$	$\frac{23.0}{(.906)}$	$\frac{12.5 \pm 1.5}{(.492 \pm .059)}$	$\frac{1.0 \pm 0.1}{(.039 \pm .004)}$

*RoHS Directive 2002/95/EC Jan 27 2003 including Annex
 Specifications are subject to change without notice.
 Customers should verify actual device performance in their specific applications.