

PS-800 Soldering System



Compact Production Soldering System

Designed to be the perfect, compact system for repetitive manual soldering and touch-up. The PS-800 Soldering System features an innovative, compact power supply with a small footprint which is ideal for production environments. The system combines the power and superior process control advantages of SmartHeat®, with the system quality and innovative design of OK International irons. In addition, the PS-800 Soldering System utilizing SmartHeat® Technology requires no calibration

Minimal Cost of Ownership

The PS-800 Soldering System uses replaceable heater tips rather than cartridges, with the cost being comparable to that of conventional tips, making cost of ownership competitive. The unique two-piece design separates the induction coil from the heater tip. The long-life induction coil remains in the handle, while replaceable heater tips are easily removed and replaced.

OK International has developed a comprehensive line of soldering tip geometries for the PS-800 Soldering System. Plus, enhancements to SmartHeat® Technology have allowed for an increase to the plating thickness of the tips. The result is extended tip life without reducing thermal performance.

Perfect For Lead-Free Hand Soldering

The most important technical challenge of lead-free hand soldering is being able to solder heat sensitive components at 215-220°C, without causing damage. This requires a soldering iron that can respond to the thermal energy demands of the application and deliver the correct amount of energy to the joint without overshoot that can cause damage.

OK International's PS-800 Soldering System is perfect for lead-free hand soldering. SmartHeat® Technology allows the higher thermal performance requirements of lead-free alloys to be met without increasing the tip temperature. Thus, the risk of thermal damage is eliminated.



The PS-800 Soldering System allows operators to produce high quality product quickly, easily and safely. It is a reliable, hassle-free production tool that can be used to solder lead-free PCBs immediately without needing to be continually re-calibrated to meet the higher temperature requirements like traditional technologies.

PS-800 Soldering System

Part No.	Description
PS-800	PS-800 Soldering System
Includes	
PS-PW1	PS-800 Power Supply
PS-WSK1	PS-800 Workstand with Sponge
PS-HC1	PS-800 Soldering Handle with Coil Assembly

Specifications

Power Supply	
Ambient Operating Temperature	10 - 40°C
Maximum Enclosure Temperature	65°C
Input Line Voltage	90 - 240 VAC
Input Line Frequency	50/60 Hz
Power Consumption	50 Watts max.
Output Power	35 Watts max. at 22°C ambient temperature
Output Frequency	470 KHz
Power Cord (3-wire)	183cm (72")
Dimensions (W x D x H)	70mm x 161mm x 100mm (2.76" x 6.34" x 3.94")

Lead-Free Process Identification

For factories that are transitioning to lead-free, it is important to identify which processes are using lead-free to avoid accidental cross-contamination of solder materials. To easily identify the lead-free processes, we have designed visual indicators that fit on the system parts where cross-contamination can occur, such as tips & workstand sponges.

Part No.	Description
PS-WSAS-G	Auto Sleep Workstand with Green Cradle
AC-CK1	Green cartridge identification ring for PHT Consumables (Pack of 50)



Accessories & Spare Parts

Part No.	Description
PS-PW1	PS-800 Power Supply
PS-WSK1	PS-800 Workstand with Sponge
PS-WSC1	PS-800 Cradle
PS-WSAS	PS-800 Auto Sleep Workstand with Sponge
AC-YS4	Sponge 3.12" ϕ x 1" (pack of 10)
PS-HC1	PS-800 Soldering Handle with Coil Assembly
PS-CA1	PS-800 Coil Assembly
AC-CP2	Heater Tip Removal Pad
AC-PM	Power Meter – AC



PS-800 Heater Tips


	PHT-XY0315 Chisel Fine 30° 1.0mm (.04")		PHT-XY2017 Conical 60° 0.25mm (.01")
	PHT-XY0326 Chisel Fine/Bent 30° 1.5mm (.06")		PHT-XY2035 Conical Fine 0.5mm (.02")
	PHT-XY0335 Chisel Fine 30° 1.78mm (.07")		PHT-XY2057 Conical Fine 1.0mm (.04")
	PHT-XY1355 Chisel 30° 2.5mm (.10")		PHT-XY2327 Conical Fine/Bent 0.4mm (.016")
	PHT-XY0325 Chisel 60° 1.5mm (.06")		PHT-XY2335 Conical Fine 30° 0.5mm (.02")
	PHT-XY1367 Chisel 30° 3.0mm (.12")		PHT-XY2337 Conical Fine/Bent 30° 0.5mm (.02")
	PHT-XY1384 Chisel 30° 5.0mm (.197")		PHT-XY3035 Conical 30° 0.5mm (.02")

650 Series **XY** = 65, 750 Series **XY** = 75


Dimensions and artwork listed are for indication/guidance only. Numbers have been rounded up.

Please contact your local technical support if you require specific technical information.


PS-800 Heater Tips




PHT-XY3047
Conical 1.2mm (.05")




PHT-XY4497
Hoof 45° 4.0mm (.16")




PHT-XY3057
Power Conical 1.0mm (.04")




PHT-XY4697
Hoof 60° 4.0mm (.16")




PHT-XY3067
Conical Long 1.0mm (.04")




PHT-XY4627F
Mini Hoof 60° Face Only 1.0mm (.04")




PHT-XY3077
Power Conical 1.0mm (.04")




PHT-XY4637F
Mini Hoof 60° Face Only 1.5mm (.06")




PHT-XY4607
Mini Hoof 60° 0.5mm (.02")




PHT-XY4467F
Hoof 45° Face Only 2.0mm (.08")




PHT-XY4617
Mini Hoof 45° 0.5mm (.02")




PHT-XY4487F
Hoof 45° Face Only 3.0mm (.12")




PHT-XY4627
Mini Hoof 60° 1.0mm (.04")




PHT-XY4497F
Hoof 45°, 4.0mm (.16")




PHT-XY4637
Mini Hoof 60° 1.5mm (.06")




PHT-XY5437
Knife Sharp 45° 3.0mm (.12")




PHT-XY4467
Hoof 45° 2.0mm (.08")




PHT-XY5457
Knife Sharp 45° 4.5mm (.18")




PHT-XY4667
Hoof 60° 2.0mm (.08")




PHT-XY5477
Knife Bevel 45° 5.0mm (.20")



PHT-XY4487
Hoof 45° 3.0mm (.12")



PHT-XY5487
Knife Sharp 45° 5.0mm (.20")



PHT-XY4687
Hoof 60° 3.0mm (.12")

650 Series XY = 65, 750 Series XY = 75

Dimensions and artwork listed are for indication/guidance only. Numbers have been rounded up.
Please contact your local technical support if you require specific technical information.