



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.


SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1125	B	UPDATED TO TABULAR SPEC	HYO	3/16/01	JC	5/17/01	JC	5/17/01
1848	C	Update Tolerance	HO	7/1/05	JWM	7/1/05	JWM	7/1/05

SPC TYPE NO.	Thickness (Inches)	O.D. (Inches)	Screw Size
WLI-02-012-SC	(0.010 - 0.015)	(0.175 - 0.200)	2
WLI-04-017-SC	(0.015 - 0.019)	(0.255 - 0.270)	4
WLI-06-018-SC	(0.017 - 0.021)	(0.275 - 0.295)	6
WLI-08-021-SC	(0.018 - 0.023)	(0.325 - 0.340)	8
WLI-10-024-SC	(0.020 - 0.025)	(0.365 - 0.381)	10
WLI-25-030-SC	(0.023 - 0.028)	(0.460 - 0.478)	1/4
WLI-24-044-SC	(0.032 - 0.040)	(0.670 - 0.692)	3/8



MATERIAL: Spring Steel, Zinc Plated

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
J.C.	9/10/91
CHECKED BY:	DATE:
APPROVED BY:	DATE:

DRAWING TITLE:

INTERNAL TOOTH LOCKWASHERS

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	TA-306	TA-306.DWG	C
SCALE: NTS	U.O.M.: INCHES	SHEET: 1 OF 1	