

H8SGL-F

[A+ Products](#) ▶ [Motherboards](#) ▶ [[H8SGL-F](#)]

Key Features



1. Single AMD Opteron™ 6100 Series processors (G34) Twelve/Eight-Core ready; HT3.0 Link support
2. AMD SR5650 + SP5100 Chipset
3. Up to 128GB DDR3 Registered ECC or 32GB DDR3 Unb. ECC/non-ECC 1333/1066/800 SDRAM in 8 DIMMs
4. Two Intel® 82574L controllers, Dual-Port Gigabit Ethernet
5. 6x SATA2 3.0 Gbps Ports via AMD SP5100 controller, RAID 0, 1, 10
6. 1/1/1/3 PCI-E 2.0 x8 (in x16) / x8 / x4 (in x8) / PCI
7. Integrated Matrox G200 Graphics
8. IPMI 2.0 with Dedicated LAN support

Links & Resources

- ▶ [Tested Memory List](#)
- ▶ [Motherboard Manual](#)
- ▶ [Update Your BIOS](#)
- ▶ [IPMI Firmware](#)
- ▶ [Download the Latest Drivers and Utilities](#)



Specifications

Product SKUs

MBD-H8SGL-F	▪ H8SGL-F (Standard Retail Pack)
--------------------	----------------------------------

Physical Stats

Form Factor	▪ ATX Form
Dimensions	▪ 12" x 8" (30.5cm x 20.3cm)

Processor/Chipset

CPU	<ul style="list-style-type: none"> ▪ Single 1944-pin Socket G34 ▪ Supports one Twelve/Eight-Core ready AMD Opteron™ 6100 Series processors ▪ HT3.0 Link support
Chipset	▪ AMD chipset SR5650 + SP5100

System Memory

Memory Capacity	<ul style="list-style-type: none"> ▪ Eight DIMM sockets ▪ Support up to 128GB DDR3 1333/1066/800 MHz memory ▪ Quad channel memory bus ▪ See Detailed Memory Support Matrix
Memory Type	▪ DDR3 1333/1066/800 MHz Registered ECC SDRAM or Unbuffered ECC/non-ECC 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	▪ 256MB, 512MB, 1GB, 2GB, 4GB, 8GB, 16GB
Memory Voltage	▪ 1.35V or 1.5V

On-Board Devices

SATA	▪ AMD SP5100 (RAID 0, 1, 10)
IPMI	<ul style="list-style-type: none"> ▪ Support for Intelligent Platform Management Interface v.2.0 ▪ IPMI 2.0 with virtual media over LAN and KVM over LAN support ▪ Winbond® WPCM450 BMC
Network Controllers	<ul style="list-style-type: none"> ▪ Two Intel® 82574L controller, Dual-Port Gigabit Ethernet ▪ 10/100/1000BASE-T support

Recommended Chassis

1U Chassis	▪ SC512F-350B, SC813MTQ-350CB, SC113MTQ-563CB
Mid-Tower	▪ SC733T-465

System BIOS

BIOS Type	▪ 16Mb SPI Flash ROM with AMI® BIOS
BIOS Features	<ul style="list-style-type: none"> ▪ Plug and Play (PnP) ▪ DMI 2.3 ▪ PCI 2.2 ▪ ACPI 2.0 ▪ USB Keyboard Support ▪ SMBIOS 2.3

Management

Software	<ul style="list-style-type: none"> ▪ IPMI (Intelligent Platform Management Interface) 2.0 ▪ Super Doctor III
Power Configurations	<ul style="list-style-type: none"> ▪ ACPI Power Management ▪ Wake-On-LAN (WOL) header ▪ Keyboard Wakeup from Soft-Off ▪ Power-on mode control for AC power loss recovery

PC Health Monitoring

CPU	<ul style="list-style-type: none"> ▪ Monitors CPU Core Voltages, +1.8V, +3.3V, +5V, ±12V, +3.3V Standby, VBAT, HT, memory, chipset ▪ CPU switching voltage regulator
FAN	<ul style="list-style-type: none"> ▪ Up to 6-fan status tachometer monitoring ▪ Up to six 4-pin fan headers ▪ Status monitor for speed control ▪ 3-pin fan support (w/o speed control) ▪ Low noise fan speed control (4-pin fan only) ▪ Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> ▪ Monitoring for CPU and chassis environment ▪ CPU Thermal Trip Support ▪ Thermal Wakeup for 6x Fan connectors

VGA	▪ Matrox G200 16MB DDR2
Super I/O	▪ Winbond® W83527 chip
Input / Output	
SATA	▪ 6x SATA2.0 (3Gb/s) Ports
LAN	▪ 2 RJ45 LAN ports ▪ 1 RJ45 Dedicated LAN supports IPMI
USB	▪ 8x USB 2.0 ports ▪ 2x Rear, 4x header, and 2x TypeA
VGA	▪ 1x VGA port
Keyboard / Mouse	▪ PS/2 keyboard and mouse ports
Serial Ports	▪ 1x Fast UART 16550 serial port ▪ 1x serial port header
Expansion Slots	
PCI-E/PCI	▪ 1/1/1/3 PCI-E 2.0 x8 (in x16) / x8 / x4 (in x8) / PCI

	▪ I ² C Temperature Sensing Logic
LED	▪ CPU / System Overheat LED ▪ +5V Standby Alert LED
Other Features	▪ Chassis Intrusion Detection ▪ Chassis Intrusion Header

Operating Environment / Compliance

RoHS



	▪ RoHS Compliant 6/6, Pb Free
Environmental Specifications	▪ Operating Temperature: 10°C to 35°C (50°F to 95°F)
	▪ Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
	▪ Operating Relative Humidity: 8% to 90% (non-condensing)
	▪ Non-operating Relative Humidity: 5% to 95% (non-condensing)

OS Compatibility

- Please see our [OS Compatibility Chart](#)

Regulatory

FCC	▪ Passed to meet FCC standard requirement
------------	---

Parts List

Retail Pack List

	Part Number	Qty	Description
Motherboard	MBD-H8SGL-F	1	H8SGL-F Motherboard
Manual	MNL-H8SGL-F	-	Motherboard Manual for H8SGL-F
I/O Cables	CBL-0010L	1	9-pin Serial Port Cable
	CBL-0036L-03	1	ATA 66/100 IDE LP Cable
	CBL-0044L	6	2ft. Amphenol, SATA Cable
Driver Disk	CDR-APLUS2	1	Version 1.02 (or newer) Chipset Driver CD
I/O Shield	MCP-260-00003-00	1	Standard I/O shield
Retention	BKT-0035L	1	Retention Bracket

[Terms & Conditions](#) | [Privacy](#)

Copyright © 2009 Super Micro Computer, Inc.

Information in this document is subject to change without notice.

Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

Page Viewed: Friday, July 2, 2010: @15:31:42