

## PRODUCT DATASHEET Oslo series



Ordering number F12237

Description F12237-Oslo-Cluster-W-OSL

Family Oslo **FWHM** 64 degrees Туре Lens Efficiency

LED Oslon SSL 80 cd/lm Gerber File Available

Color Transparent Diameter 26 mm 6.7 mm Height Style Round

Cluster

**PMMA** Optic Material Holder Material

Pin, glue Fastening Status Ready

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



## PRODUCT DATASHEET Oslo series



## **GENERAL INFORMATION**

- Product series especially designed & optimized for Oslon SSL 80 series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet\_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

