

T-01-09

LOW LEAKAGE DIODES

1N456 • 1N456A • 1N457 • 1N457A
1N458 • 1N458A • 1N459 • 1N459A

ABSOLUTE MAXIMUM RATINGS

- I_R 25 nA @ WIV
- C 6.0 pF

Temperatures

Storage Temperature Range	-65 °C to +200 °C
Maximum Junction Operating Temperature	+175 °C
Lead Temperature	+260 °C

Power Dissipation


Maximum Total Power Dissipation at 25 °C Ambient	500mW
Linear Power Derating Factor	3.33 mW/ °C

Maximum Voltage and Currents

	1N456/A	1N457/A	1N458/A	1N459/A
WIV Working Inverse Voltage	25V	60V	125V	175V
IO Average Rectified Current				200mA
I_F Continuous Forward Current				500mA
I_{FR} Peak Repetitive Forward Current				600mA
I_{FS} (surge) Peak Forward Surge Current				4.0 A
Pulse Width = 1μs				1.0A
Pulse Width = 1s				

ELECTRICAL CHARACTERISTICS (25 °C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
V_F	Forward Voltage 1N456A/7A/8A/9A		1.0	V	$I_F = 100$ mA
	1N456		1.0	V	$I_F = 40$ mA
	1N457		1.0	V	$I_F = 20$ mA
	1N458		1.0	V	$I_F = 7$ mA
	1N459		1.0	V	$I_F = 3$ mA
I_R	Reverse Current		25	nA	$V_R =$ Rated WIV
			5.0	μA	$V_R =$ Rated WIV, $T_A = 150$ °C
B_V	Breakdown Voltage 1N456/A	30		V	$I_R = 100$ μA
	1N457/A	70		V	$I_R = 100$ μA
	1N458/A	150		V	$I_R = 100$ μA
	1N459/A	200		V	$I_R = 100$ μA
C	Capacitance		6.0	pF	$V_R = 0$, $f = 1$ MHz



DO-35 PACKAGE

6 Lake Street
P.O. Box 1436
Lawrence, MA 01841
Telephone (617) 681-0392
TeleFax (617) 681-9135
Telex 928377



BKC International
Electronics, Inc.