





## Main

|                                             |                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial Status                           | Commercialised                                                                                                                                                                                                                                                                                                           |
| Range of product                            | TeSys D                                                                                                                                                                                                                                                                                                                  |
| Product or component type                   | Contacteur                                                                                                                                                                                                                                                                                                               |
| Device short name                           | LC1D                                                                                                                                                                                                                                                                                                                     |
| Contacteur application                      | Motor control<br>Resistive load                                                                                                                                                                                                                                                                                          |
| Utilisation category                        | AC-1<br>AC-3                                                                                                                                                                                                                                                                                                             |
| Poles description                           | 3P                                                                                                                                                                                                                                                                                                                       |
| Pole contact composition                    | 3 NO                                                                                                                                                                                                                                                                                                                     |
| [Ue] rated operational voltage              | <= 300 V DC for power circuit<br><= 690 V AC 25...400 Hz for power circuit                                                                                                                                                                                                                                               |
| [Ie] rated operational current              | 9 A (<= 140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit<br>25 A (<= 140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit                                                                                                                                                                                          |
| Motor power kW                              | 5.5 kW at 660...690 V AC 50/60 Hz<br>5.5 kW at 500 V AC 50/60 Hz<br>4 kW at 415...440 V AC 50/60 Hz<br>4 kW at 380...400 V AC 50/60 Hz<br>2.2 kW at 220...230 V AC 50/60 Hz                                                                                                                                              |
| Motor power hp                              | 7.5 hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>5 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>2 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>2 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>1 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>0.5 hp at 115 V AC 50/60 Hz for 1 phase motors |
| Control circuit type                        | AC 50/60 Hz                                                                                                                                                                                                                                                                                                              |
| Control circuit voltage                     | 440 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                        |
| Auxiliary contact composition               | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                              |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                             |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                                                      |
| [Ith] conventional free air thermal current | 10 A at <= 140 °F (60 °C) for signalling circuit<br>25 A at <= 140 °F (60 °C) for power circuit                                                                                                                                                                                                                          |
| Irms rated making capacity                  | 250 A DC for signalling circuit conforming to IEC 60947-5-1<br>140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                   |
| Rated breaking capacity                     | 250 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                 |
| [Icw] rated short-time withstand current    | 61 A <= 104 °F (40 °C) 1 min power circuit<br>30 A <= 104 °F (40 °C) 10 min power circuit<br>140 A 100 ms signalling circuit<br>120 A 500 ms signalling circuit<br>100 A 1 s signalling circuit<br>210 A <= 104 °F (40 °C) 1 s power circuit<br>105 A <= 104 °F (40 °C) 10 s power circuit                               |
| Associated fuse rating                      | 20 A gG at <= 690 V coordination type 2 for power circuit<br>25 A gG at <= 690 V coordination type 1 for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947-5-1                                                                                                                                     |
| Average impedance                           | 2.5 mOhm at 50 Hz - Ith 25 A for power circuit                                                                                                                                                                                                                                                                           |

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage | 600 V for signalling circuit certifications UL<br>600 V for signalling circuit certifications CSA<br>690 V for signalling circuit conforming to IEC 60947-1<br>600 V for power circuit certifications UL<br>600 V for power circuit certifications CSA<br>690 V for power circuit conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Electrical durability         | 2 Mcycles 9 A AC-3 at $U_e \leq 440$ V<br>0.6 Mcycles 25 A AC-1 at $U_e \leq 440$ V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Power dissipation per pole    | AC-3<br>1.56 W AC-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Protective cover              | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mounting support              | Plate<br>Rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Standards                     | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product certifications        | BV<br>CCC<br>CSA<br>DNV<br>GL<br>GOST<br>RINA<br>UL<br>LROS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Connections - terminals       | Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Power circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Power circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end |
| Tightening torque             | Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Operating time                | 4...19 ms opening<br>12...22 ms closing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Safety reliability level      | B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1<br>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                       |                                |
|-----------------------|--------------------------------|
| Mechanical durability | 15 Mcycles                     |
| Operating rate        | 3600 cyc/h at ≤ 140 °F (60 °C) |

## Complementary

|                                 |                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                 | Without built-in suppressor module                                                                                                                        |
| Control circuit voltage limits  | 0.85...1.1 Uc at 140 °F (60 °C) operational 60 Hz<br>0.8...1.1 Uc at 140 °F (60 °C) operational 50 Hz<br>0.3...0.6 Uc at 140 °F (60 °C) drop-out 50/60 Hz |
| Inrush power in VA              | 70 VA at 20 °C (cos φ 0.75) 50 Hz<br>70 VA at 20 °C (cos φ 0.75) 60 Hz                                                                                    |
| Hold-in power consumption in VA | 7 VA at 20 °C (cos φ 0.3) 50 Hz<br>7.5 VA at 20 °C (cos φ 0.3) 60 Hz                                                                                      |
| Heat dissipation                | 2...3 W at 50/60 Hz                                                                                                                                       |
| Auxiliary contacts type         | Type mirror contact (1 NC) conforming to IEC 60947-4-1<br>Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1                              |
| Signalling circuit frequency    | 25...400 Hz                                                                                                                                               |
| Minimum switching current       | 5 mA for signalling circuit                                                                                                                               |
| Minimum switching voltage       | 17 V for signalling circuit                                                                                                                               |
| Non-overlap time                | 1.5 ms on energisation (between NC and NO contact)<br>1.5 ms on de-energisation (between NC and NO contact)                                               |
| Insulation resistance           | > 10 MOhm for signalling circuit                                                                                                                          |

## Environment

|                                                       |                                                                                                                                                                                |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection                               | IP2x front face conforming to IEC 60529                                                                                                                                        |
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                |
| Pollution degree                                      | 3                                                                                                                                                                              |
| Ambient air temperature for operation                 | 23...140 °F (-5...60 °C)                                                                                                                                                       |
| Ambient air temperature for storage                   | -76...176 °F (-60...80 °C)                                                                                                                                                     |
| Permissible ambient air temperature around the device | -40...158 °F (-40...70 °C) at Uc                                                                                                                                               |
| Operating altitude                                    | 9842.52 ft (3000 m) without derating in temperature                                                                                                                            |
| Fire resistance                                       | 1562 °F (850 °C) conforming to IEC 60695-2-1                                                                                                                                   |
| Flame retardance                                      | V1 conforming to UL 94                                                                                                                                                         |
| Mechanical robustness                                 | Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open 10 Gn for 11 ms<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Vibrations contactor open 2 Gn, 5...300 Hz |
| Height                                                | 3.03 in (77 mm)                                                                                                                                                                |
| Width                                                 | 1.77 in (45 mm)                                                                                                                                                                |
| Depth                                                 | 3.39 in (86 mm)                                                                                                                                                                |
| Product weight                                        | 0.71 lb(US) (0.32 kg)                                                                                                                                                          |

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22345 - CTR,D-LINE,OPEN,NONREV-NEW |
| Discount Schedule     | I12                                |
| GTIN                  | 00785901863366                     |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 1.00                               |
| Returnability         | N                                  |
| Country of origin     | FR                                 |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS                             | Compliant - since 0627 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |