

SP Series

Heat Shrink Tubing



Black



Blue



Yellow



Red



Green Yellow



Features:

- Shrink ratio 2:1.
- Operating temperature range -55°C to 135°C.
- Shrink temperature 100°C.
- Suitable for general use on high quality equipment.
- Flexible general purpose heat shrinkable polyolefin tubing.

SP Series

Heat Shrink Tubing



Specification Values

Property	Test Method	Values
Tensile strength	ISO 37	10MPa minimum
Ultimate elongation	ISO 37	250% minimum
Specific gravity	ISO 1183	1.35 maximum
Heat shock	ASTM D2671 (4 hours at 250°C)	No dripping, cracking or flowing
Heat ageing Ultimate elongation	ISO 188 (168 hours at 175°C) ISO 37	150% minimum
Low temperature flexibility	ASTM D2671 (4 hours at -55°C)	No cracking
Flammability (except clear)	ASTM D876	Pass
Electric strength	IEC 243	20kV/mm minimum
Corrosion (copper contact and copper mirror)	ASTM D2671	No corrosion
Water absorption	ISO 62	0.5% maximum
Fluid resistance Gasoline Hydraulic fluid Lubricating oil Tensile strength Ultimate elongation	ISO 1817 ISO 37	7MPa minimum 200% minimum
Fungus resistance Tensile strength Ultimate elongation	ISO 846 ISO 37	10Mpa minimum 250% minimum

Specification References/Approvals

Type	Shrinktek	Military	CSA
SP	ST6002	MIL-DTL 23053/5 DEF STAN 59-97 VG 95343 Pt5	600V, 125°C (OFT)



SP Series

Heat Shrink Tubing



Specification Table - Reels

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Black	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/RL/BLACK
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/RL/BLACK
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/RL/BLACK
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/RL/BLACK
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/RL/BLACK
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/RL/BLACK
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/RL/BLACK
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/RL/BLACK
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/RL/BLACK

Dimensions: Millimetres (Inches)

Specification Table - 1.2m Lengths

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Black	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/BLACK
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/BLACK
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/BLACK
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2BLACK
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2BLACK
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/BLACK
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/BLACK
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/BLACK
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/BLACK
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/BLACK
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/BLACK
Clear	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/CLEAR
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/CLEAR
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/CLR
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/CLEAR
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/CLEAR
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/CLEAR
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/CLEAR
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/CLEAR
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/CLEAR
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/CLEAR
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/CLEAR

Dimensions: Millimetres (Inches)



SP Series

Heat Shrink Tubing



Specification Table - 1.2m Lengths

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Red	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/RED
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/RED
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/RED
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/RED
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/RED
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/RED
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/RED
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/RED
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/RED
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/RED
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/RED
Yellow	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/YELLOW
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/YELLOW
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/YELLOW
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/YELLOW
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/YELLOW
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/YELLOW
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/YELLOW
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/YELLOW
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/YELLOW
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/YELLOW
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/YELLOW
Blue	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/BLUE
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/BLUE
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)	0.50 (0.019)	SP32/1.2/BLUE
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/BLUE
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)		SP64/1.2/BLUE
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)	0.65 (0.026)	SP95/1.2/BLUE
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/BLUE
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/BLUE
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/BLUE
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/BLUE
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/BLUE

Dimensions: Millimetres (Inches)

SP Series

Heat Shrink Tubing



Specification Table - 1.2m Lengths

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Green/Yellow	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)	0.50 (0.019)	SP32/1.2/GREEN/YEL
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/GREEN/YEL
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/GREEN/YEL
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/GREEN/YEL
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/GREEN/YEL
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/GREEN/YEL
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/GREEN/YEL
White	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/WHITE
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/WHITE
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/WHITE
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)	0.50 (0.019)	SP48/1.2/WHITE
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/WHITE
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/WHITE
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/WHITE
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/WHITE
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/WHITE
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/WHITE
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/1.2/WHITE
Green	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/GREEN
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/GREEN
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/GREEN
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/GREEN
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/GREEN
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/GREEN
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/GREEN
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/GREEN
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/1.2/GREEN
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/1.2/GREEN
Brown	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/1.2/BROWN
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/1.2/BROWN
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/1.2/BROWN
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/1.2/BROWN
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/1.2/BROWN
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/1.2/BROWN
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/1.2/BROWN
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/1.2/BROWN

Dimensions: Millimetres (Inches)



SP Series

Heat Shrink Tubing



Specification Table - 5m Coils

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Black	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/BLACK
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/BLACK
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/BLACK
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/BLACK
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/BLACK
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/BLACK
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/BLACK
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/BLACK
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/5/BLACK
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/5/BLACK
	50.8 (2.000)	50.8 (2.000)	25.4 (1.000)	1.15 (0.045)	SP508/5/BLACK
Yellow	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/YELLOW
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/YELLOW
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/YELLOW
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/YELLOW
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/YELLOW
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/YELLOW
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/YELLOW
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/YELLOW
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/5/YELLOW
Red	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/RED
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/RED
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/RED
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/RED
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/RED
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/RED
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/RED
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/RED
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/5/RED
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/5/RED

Dimensions: Millimetres (Inches)

SP Series

Heat Shrink Tubing



Specification Table - 5m Coils

Colour	Size	Minimum Expansion	Maximum Recovered	Nominal Recovered Wall	Part Number
Blue	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/BLUE
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/BLUE
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/BLUE
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/BLUE
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/BLUE
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/BLUE
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/BLUE
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/BLUE
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/5/BLUE
	38.1 (1.500)	38.1 (1.500)	19.1 (0.750)	1.00 (0.039)	SP381/5/BLUE
White	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/WHITE
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/WHITE
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/WHITE
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/WHITE
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/WHITE
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/WHITE
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/WHITE
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/WHITE
Green	1.6 (0.063)	1.6 (0.063)	0.8 (0.031)	0.45 (0.018)	SP16/5/GREEN
	2.4 (0.093)	2.4 (0.093)	1.2 (0.046)	0.50 (0.019)	SP24/5/GREEN
	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)		SP32/5/GREEN
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/GREEN
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/GREEN
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/GREEN
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/GREEN
Green/Yellow	3.2 (0.125)	3.2 (0.125)	1.6 (0.062)	0.50 (0.019)	SP32/5/GREEN/YEL
	4.8 (0.187)	4.8 (0.187)	2.4 (0.093)		SP48/5/GREEN/YEL
	6.4 (0.250)	6.4 (0.250)	3.2 (0.125)	0.65 (0.026)	SP64/5/GREEN/YEL
	9.5 (0.375)	9.5 (0.375)	4.8 (0.187)		SP95/5/GREEN/YEL
	12.7 (0.500)	12.7 (0.500)	6.4 (0.250)		SP127/5/GREEN/YEL
	19.0 (0.750)	19.1 (0.750)	9.5 (0.375)	0.75 (0.029)	SP190/5/GREEN/YEL
	25.4 (1.000)	25.4 (1.000)	12.7 (0.500)	0.90 (0.035)	SP254/5/GREEN/YEL

Dimensions: Millimetres (Inches)

SP Series

Heat Shrink Tubing



Notes:

International Sales Offices:



AUSTRALIA – Farnell InOne
Tel No: ++ 61 2 9645 8888
Fax No: ++ 61 2 9644 7898



FINLAND – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



NETHERLANDS – Farnell InOne
Tel No: ++ 31 30 241 7373
Fax No: ++ 31 30 241 7333



SWITZERLAND – Farnell InOne
Tel No: ++ 41 1 204 64 64
Fax No: ++ 41 1 204 64 54



AUSTRIA – Farnell InOne
Tel No: ++ 43 662 2180 680
Fax No: ++ 43 662 2180 670



FRANCE – Farnell InOne
Tel No: ++ 33 474 68 99 99
Fax No: ++ 33 474 68 99 90



NEW ZEALAND – Farnell InOne
Tel No: ++ 64 9 357 0646
Fax No: ++ 64 9 357 0656



UK – Farnell InOne
Tel No: ++ 44 8701 200 200
Fax No: ++ 44 8701 200 201



BELGIUM – Farnell InOne
Tel No: ++ 32 3 475 2810
Fax No: ++ 32 3 227 3648



GERMANY – Farnell InOne
Tel No: ++ 49 89 61 39 39 39
Fax No: ++ 49 89 613 59 01



NORWAY – Farnell InOne
Tel No: ++ 45 44 53 66 66
Fax No: ++ 45 44 53 66 02



UK – BuckHickman InOne
++ 44 8450 510 150
++ 44 8450 510 130



BRAZIL – Farnell-Newark InOne
Tel No: ++ 55 11 4066 9400
Fax No: ++ 55 11 4066 9410



HONG KONG – Farnell-Newark InOne
Tel No: ++ 852 2268 9888
Fax No: ++ 852 2268 9899



PORTUGAL – Farnell InOne
Tel No: ++ 34 93 475 8804
Fax No: ++ 34 93 474 5288



UK – CPC
++ 44 8701 202 530
++ 44 8701 202 531



CHINA – Farnell-Newark InOne
Tel No: ++86 10 6238 5152
Fax No: ++86 10 6238 5022



IRELAND – Farnell InOne
Tel No: ++ 353 1 830 9277
Fax No: ++ 353 1 830 9016



SINGAPORE – Farnell-Newark InOne
Tel No: ++ 65 6788 0200
Fax No: ++ 65 6788 0300



EXPORT – Farnell InOne
Tel No: ++ 44 8701 200 208
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



DENMARK – Farnell InOne
Tel No: ++ 45 44 53 66 44
Fax No: ++ 45 44 53 66 06



ITALY – Farnell InOne
Tel No: ++ 39 02 93 995 200
Fax No: ++ 39 02 93 995 300



SPAIN – Farnell InOne
Tel No: ++ 34 93 475 8805
Fax No: ++ 34 93 474 5107



ESTONIA – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



MALAYSIA – Farnell-Newark InOne
Tel No: ++ 60 3 7873 8000
Fax No: ++ 60 3 7873 7000



SWEDEN – Farnell InOne
Tel No: ++ 46 8 730 50 00
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2004.

