

2-Channel DC SafeSnap™ Barrier

Model Numbers

Z755	(Z855)*
Z757	(Z857)*
Z764	(Z864)*
Z765	(Z865)*
Z772	(Z872)*
Z778	(Z878)*
Z779	(Z879)*
Z779.H	(Z879.H)*
Z786	(Z886)*
Z788	(Z888)*
Z788.H	(Z888.H)*
Z796	(Z896)*

- 2-channel/DC
- Narrow 12.5 mm profile
- Dedicated terminal for each connection
- Snap-on for easy mounting and grounding

SafeSnap dual-channel zener barriers feature a narrow profile of just 12.5 mm to maximize control panel space. Available in positive or negative polarity, these barriers simply snap on for easy installation and maintenance.

Note: All diodes are orientated in the opposite direction for the negative polarity versions.


Technical Data

MODEL NUMBER	Working voltage at 10 μ A leakage (V)	Max. end to end resistance (Ω)	Fuse rating max. current (mA)	Max. voltage (V)
Polarity Pos. (Neg.)				
Z755 (Z855)	0.9 (1 μ A)	18.18	250	4.8
Z757 (Z857)	6.0	15.5	200	6.9
Z764 (Z864)	10.0	1033	50	11.0
Z765 (Z865)	13.0	107	100	13.6
Z772 (Z872)	19.0	166	50	20.1
Z778 (Z878)	26.5	646	50	28.0
Z779 (Z879)	26.5	327	50	28.0
Z779.H (Z879.H)	26.5	250	80	28.0
Z786 (Z886)	26.5	36 + 0.9 V	50	28.0
Z788 (Z888)	26.5 6.5	327 64	50 50	28.0 9.1
Z788.H (Z888.H)	26.5 6.5	250 64	80 80	28.0 9.1
Z796 (Z896)	24.0 18.0	340 437	50 50	25.1 19.5
CERTIFICATES				
See page 317 for entity parameters				
FM				
No. 116-0118				
SP				
No. 116-0119				
UL				
No. 116-0139				
CE				
Zone 0, 1, 2				
BAS 01 ATEX 7005, Ex II (1) G D [EEEx ia] IIC				
Zone 2				
TÜV 99 ATEX 1484 X, Ex II 3 G EEx nAC IIC T4				
MECHANICAL				
Housing				
Type G see page 455				
Dimensions				
4.53" x 0.49" x 4.33" (115 x 12.5 x 110 mm)				
Weight				
4.0 oz. ($\approx$ 125g)				
Max. Wire Size				
2 x #14 AWG (2 x 2.5 mm ²)				
AMBIENT TEMPERATURE				
-4°F to +131°F (-20°C to +55°C)				



Engineer's Guide (page 7)
Zener Accessories (page 297)
Power Supplies (page 401)
Surge Suppression (page 413)
Latest Info. Avail. Online


Connection Diagram



Class I, Div 1, 2
Zone 0, 1, 2

Hazardous Area


Safe Area, Div 2 or Zone 2



Class I, Div 1, 2
Zone 0, 1, 2

Hazardous Area

Safe Area, Div 2 or Zone 2



Z786 and Z886

* No ATEX Zone 2 certificate