


Large Size – Alloys

LS-1950 – All Stainless Steel For High Pressure and Temperature

For high performance applications, the LS-1950 provides high temperature and pressure capabilities. Materials of construction comply with FDA food contact regulations.

Dimensions



Exceptionally accurate and rugged for higher temperatures and in pressurized or corrosive liquids. For oils, water and chemicals.

†L_F = Switch actuation level, nominal (based on a liquid specific gravity of 1.0 and N.O. dry circuit – dimension will vary for N.C. circuit).

Common Specifications

Electrical Termination: No. 18 AWG, 24" L., Polymeric Lead Wires (except Part No. 79999 which has Teflon® lead wires).

Approvals: LS-1950 Series switches are U.L. Recognized – File No. E45168 and are CSA Listed - File No. 30200 (Part No. 79999 is U.L. Recognized only).

Switch Operation: Selectable, N.O. or N.C., by inverting float on unit stem. Units are shipped N.O. unless otherwise specified.

How to Order – Select Part Number based on specifications required.

Series Number	Materials		Min. Liquid Sp. Gr.	Operating Temperature	Pressure, PSI, Max.	Switch ¹	Part Number
	Stem and Mounting	Float					
LS-1950	316 Stainless Steel	0.75	-40°F to +300°F (-40°C to +149°C)	750	SPST, 20 VA	01950	⚡
					SPST, 100 VA ²	26717	⚡
			-40°F to +480°F (-40°C to +249°C)		SPST, 20 VA	79999	⚡

Notes

- See "Electrical Data" on Page X-5 for more information.
- UL Resistive Rated

⚡ – Stock Items.