



Meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541



Features

- Trays that can stack and nest together for improved use of space
- Great container for Kanban
- Static dissipative foam bottom provides ESD and shock protection

Foam Electrical Properties: 1×10^5 to $< 1 \times 10^8$ ohms

Foam Thickness: 1/8"

Item No.	Size I.D. - L x W x D (IN)
37750	18 x 11-3/8 x 1-3/4
37751	22-7/8 x 17-1/4 x 2-3/4

SPECIFICATIONS

Properties

Surface Resistance

Sloughing Test

Recyclability

Typical Values

1×10^6 to $< 1 \times 10^9$ ohms

Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.

No conductive particles abraded from surface

Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11

ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992

Rockwell International Test Report of January 8, 1992



Made in the
United States of America

Unless otherwise noted, tolerance is $\pm 10\%$
Specifications and procedures subject to change without notice.

TEK-TRAYS

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE CHINO, CA 91710
PHONE (909) 627-2578, FAX (909) 363-7331
ProtektivePak.com

DRAWING NUMBER
37750

DATE:
March
2015