


FEATURES

- Max. propagation delay of 800ps
- Enable to Output max. of 950ps
- IEE min. of -60mA
- Extended supply voltage option:
VEE = -4.2V to -5.5V
- Voltage and temperature compensation for improved noise immunity
- Internal 75kΩ input pull-down resistors
- 50% faster than Fairchild 300K
- Function and pinout compatible with Fairchild F100K
- Available in 28-pin PLCC package

DESCRIPTION

The SY100S313 offers four drivers with two OR and two NOR outputs, designed for use in high-performance ECL systems. The four drivers are controlled by a common Enable signal which is buffered to minimize input loading. If the D inputs are not used, the Enable signal can be used to drive sixteen 50Ω lines. All inputs have 75kΩ pulldown resistors and all outputs are buffered.


BLOCK DIAGRAM



PIN NAMES

Pin	Function
Da – Dd	Data Inputs (n-1...5)
E	Enable Input
O _{na} – O _{nd}	Data Outputs
\overline{O}_{na} – \overline{O}_{nd}	Complementary Data Outputs
VEES	VEE Substrate
VCCA	Vcco for ECL Outputs

PACKAGE/ORDERING INFORMATION



28-Pin PLCC (J28-1)

Ordering Information

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY100S313JC	J28-1	Commercial	SY100S313JC	Sn-Pb
SY100S313JCTR ⁽¹⁾	J28-1	Commercial	SY100S313JC	Sn-Pb
SY100S313JZ ⁽²⁾	J28-1	Commercial	SY100S313JZ with Pb-Free bar-line indicator	Matte-Sn
SY100S313JZTR ^(1, 2)	J28-1	Commercial	SY100S313JZ with Pb-Free bar-line indicator	Matte-Sn

- Notes:
- 1. Tape and Reel.
 - 2. Pb-Free package is recommended for new designs.

LOGIC EQUATION

$$O = D + E$$

$$\overline{O} = \overline{D} + \overline{E}$$

DC ELECTRICAL CHARACTERISTICS

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$


Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current, All Inputs	—	—	200	μA	$V_{IN} = V_{IH} (Max.)$
I_{EE}	Power Supply Current	-60	-43	-20	mA	Inputs Open

AC ELECTRICAL CHARACTERISTICS

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_A = 0^\circ C$		$T_A = +25^\circ C$		$T_A = +85^\circ C$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	200	800	200	800	200	800	ps	
t_{PLH} t_{PHL}	Propagation Delay Enable to Output	300	950	300	950	300	950	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	



TIMING DIAGRAM



Propagation Delay and Transition Times

NOTE:

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$

28-PIN PLCC (J28-1)**NOTES:**

1. DIMENSIONS ARE IN INCHES [MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008 [0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. A

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USATEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB <http://www.micrel.com>

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.