



No Clean Flux Remover

1660

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, leadfree temperatures are more baked on and harder to clean. G3, Ecoline and PrecisionV flux removers have been proven very effective at removing fluxes baked on at leadfree temperatures.

Microcomponents and fine pitch leads are delicate and easily damaged, so brushing and scrubbing should be avoided if possible. Both G3, Ecoline and PrecisionV have a powerful spray and strong solvent that blasts off residues and cleans areas under components that a brush cannot touch.



High-precision AK225-based solvent cleaner

Nonflammable, high precision, and specifically formulated to avoid and clean white residues caused by noclean fluxes.

- Non-flammable
- Safe on electronics
- Rapid evaporation
- Zero residue
- Safe on most plastics
- EPA SNAP approved
- Ideal for no-clean fluxes

Product Packaging

1660-6S
No Clean Flux Remover
6 oz
12 units/case



Instructions

Make sure opening of sprayhead is pointing toward surface to be cleaned. Hold can 15-20 cm away. Direct spray to saturate soiled surface. A TechBrush® (2000 Series) may be utilized to help in the removal of heavy soils. When used as a general cleaner, start at top of area to be cleaned using a sweeping motion, and spray the area slowly, working towards the bottom. To clean in hard to reach areas, insert extension tube in sprayhead to direct spray. Allow components to dry completely before applying current. For flat surface cleaning, saturate a lint-free TechClean® Twillwipe (2357) or Purwipe™ (2355) and wipe surface with cloth. Rotate the cleaning side of the wipe periodically and re-saturate.

Chemical & Physical Properties

Appearance	Clear, colorless liquid
Odor	Faint ethereal odor
Flash Point	none
VOC (EPA)	35%
VOC (CARB)	75%
Boiling Point	44.6°C (114°F)





Density	
---------	--

Chemical Composition

CHEMICAL NAME	CAS #
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	422-56-0
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	507-55-1
1,2-transdichloroethylene	156-60-5
Methanol	67-56-1
Nitromethane	75-52-5
1,1,1,2-Tetrafluoroethane (aerosol)	811-97-2
Carbon dioxide (aerosol)	124-38-9

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe

ITW Contamination Control BV
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.