

General Specifications

Electrical Capacity (Resistive Load)

Power Level: 6A @ 125V AC or 3A @ 250V AC

Other Ratings

Contact Resistance:	10 milliohms maximum
Insulation Resistance:	1,000 megohms minimum @ 500V DC
Dielectric Strength:	1,000V AC minimum between contacts for 1 minute minimum; 1,500V AC minimum between contacts & case for 1 minute minimum
Mechanical Life:	50,000 operations minimum
Electrical Life:	25,000 operations minimum
Contact Timing:	Nonshorting (break-before-make)
Total Travel:	.087" (2.2mm)

Materials & Finishes

Actuator:	Polyamide (UL94V-0)
Frame:	Stainless steel
Case:	Glass fiber reinforced diallyl phthalate resin (UL94V-0)
Movable Contacts:	Silver alloy
Stationary Contacts:	Silver capped copper with silver plating
Terminals:	Copper or brass with silver plating

Environmental Data

Operating Temp Range:	-10°C through +55°C (+14°F through +131°F)
Humidity:	90 ~ 95% humidity for 240 hours @ 40°C (104°F)
Vibration:	10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock:	50G (490m/s ²) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

Processing

Soldering Time & Temp:	Wave Soldering Recommended (PC version): See Profile A in Supplement section. Manual Soldering: See Profile A in Supplement section. Note: Lever must be in center position while soldering.
Cleaning:	These devices are not process sealed. Hand clean locally using alcohol based solution.

Standards & Certifications

Flammability Standards: UL94V-0 rated actuator & case

Toggles

Rockers

Pushbuttons

Illuminated PB

Programmable

Keylocks

Rotaries

Slides

Tactiles

Tilt

Touch

Indicators

Accessories

Supplement

Distinctive Characteristics

Bright, LED illumination at top of actuator.

Over-center actuator block and plunger design gives crisp actuation, diminishes sparking, and increases operating life.

Guide interlocked with actuator block prevents window locking and maintains correct plunger alignment to assure contact stability.


Antijamming design protects contacts from damage due to excessive downward force on the actuator.

High internal barriers between poles and insulating sheet between case and actuator block give added protection to contacts.


Prominent external insulating barriers increase insulation resistance and dielectric strength.

Epoxy sealed terminals prevent entry of flux, solvents, and other contaminants.

Clinching of frame to case well above base and terminals provides 1,500V dielectric strength.



Actual Size



TYPICAL SWITCH ORDERING EXAMPLE

MS

1

2

L

F

W

01

C

Poles

1	SPDT
---	------

Illumination

L	LED Lighted
---	-------------

Contact Materials & Ratings

W	Silver; Rated 6A @ 125V AC & 3A @ 250V AC
---	---

LEDs

C	Red
E	Yellow
F	Green

Circuits

2	ON	NONE	ON
3	ON	OFF	ON

Mounting

N	For Straight PC (Terminal 03 only)
F	With 2-screw Flange (Terminal 01 only)

Terminals

01	Solder Lug *
03	Straight PC

* Wire harness & cable assemblies offered only in Americas


DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

MS12LFW01C

Red LED Illumination

Silver Contacts with 6-Amp Rating








Solder Lug Terminals



2-screw Flange Frame

SPDT ON-NONE-ON Circuit

POLES & CIRCUITS

		Slide Position			Connected Terminals			Throw & Schematics
Pole	Model	Left	Center	Right	Left	Center	Right	Note: Terminal numbers are not actually on the switch. LED circuit is isolated and requires an external connection.
								
SP	MS12	ON	NONE	ON	2-1	OPEN	2-3	<div>SPDT</div> 
	MS13	ON	OFF	ON				

CONTACT MATERIALS & RATINGS

W

Silver over Silver

Power Level


6A @ 125V AC & 3A @ 250V AC

MOUNTING TYPES & TERMINALS

N Straight PC Mount
(Combines with
Straight PC Terminal
03 only)




03 Straight PC



F 2-screw Flange
(Combines with Solder
Lug Terminal 01 only)



01 Solder Lug





LED COLORS & SPECIFICATIONS

LEDs are supplied as an integral part of the switch (not available separately). The lamp circuit is independent of switch operation. Electrical specifications shown are determined at a basic temperature of 25°C. If the source voltage exceeds the rated voltage, a ballast resistor is required. The resistor value can be calculated by using the formula given in the Supplement.


		C Red	E Yellow	F Green
Forward Peak Current	I_{FM}	30mA	30mA	25mA
Typical Forward Current	I_F	16mA	16mA	16mA
Forward Voltage	V_F	1.98V	2.06V	2.16V
Reverse Peak Voltage	V_{RM}	5V	5V	5V
Current Reduction Rate Above 25°C	ΔI_F	0.40mA/°C	0.42mA/°C	0.33mA/°C
Ambient Temperature Range		-15° ~ +60°C		

TYPICAL SWITCH DIMENSIONS


Solder Lug Terminals



Actuator in LEFT Position





Maximum Panel Thickness .197" (5.0mm)





MS12LFW01C

Straight PC Terminals



Actuator in LEFT Position



Maximum Panel Thickness .197" (5.0mm)



MS12LNW03C