



Features:

- Flexible power control cable commonly used in power control, instrumentation or automated equipment where screening or armoring is not required.
- Overall sheathed in Grey PVC with plain copper conductors.

PVC - Control Cable Number Coded

Application:

For decades YY Series control cables have been used successfully as connection and inter-connection cables in general machine building, production lines, production facilities and winding units among other applications for signal and data transmission. YY Series control cables are to a high degree resistant to chemicals like acids and lyes as well as certain hydrocarbonic compounds. As they are of an extraordinary flexibility, YY Series control cables are very suited to being installed where free movement without guidance is required.

In addition to this, YY Series control cables are put into operation in the heating and refrigeration technology because they are resistant to extreme temperatures. YY Series control cables should not be used outdoors or as underground cable.

Construction:

Bare, finely stranded copper conductors according to VDE-standard 0295 conductor class 5. Insulation material PVC type YI2 according to VDE 0207 part 4, sheath material PVC type Y M2 according to VDE 0207 part 5. Sheath grey RAL 7001. Cores black with white numbers. Starting at 3 cores with green/yellow protective conductor.

Technical data:

Test voltage	: 3000V
Nominal voltage	: 300/500V
Temperature range	
in fixed condition	: -40°C to +70°C
in mobile condition	: -5°C to +70°C

< 20 mm >
3 3 3

The narrow clearances in printing ensure the clear identification of cores even with short insulated lengths.

YY Series

Flexible Power Control Cables

PRO-POWER
Quality Cables

Specifications

Number of Cores x Conductor Area (mm ²)	Colour	Outside Diameter	Reel Length (m)	Current Rating (A)	Part Number
13 x 0.75	11 numbered Black, Green/Yellow	12.6	50	6	CBBR1093
13 x 1.5			50		YY 1.50 12
13 x 2.5		50	20	YY 2.50 12	
18 x 0.75	17 numbered Black, Green/Yellow	13.4	50	6	YY 0.75 18
18 x 1.5			50		16
18 x 1.5		21	20	YY 2.50 18	

Dimensions : Millimetres (Unless Specified)

PRO-POWER
Quality Cables

YY Series

Flexible Power Control Cables

PRO-POWER
Quality Cables

Notes:

International Sales Offices:



AUSTRALIA – Farnell InOne
Tel No: ++ 61 2 9645 8888
Fax No: ++ 61 2 9644 7898



FINLAND – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



NETHERLANDS – Farnell InOne
Tel No: ++ 31 30 241 7373
Fax No: ++ 31 30 241 7333



SWITZERLAND – Farnell InOne
Tel No: ++ 41 1 204 64 64
Fax No: ++ 41 1 204 64 54



AUSTRIA – Farnell InOne
Tel No: ++ 43 662 2180 680
Fax No: ++ 43 662 2180 670



FRANCE – Farnell InOne
Tel No: ++ 33 474 68 99 99
Fax No: ++ 33 474 68 99 90



NEW ZEALAND – Farnell InOne
Tel No: ++ 64 9 357 0646
Fax No: ++ 64 9 357 0656



UK – Farnell InOne
Tel No: ++ 44 8701 200 200
Fax No: ++ 44 8701 200 201



BELGIUM – Farnell InOne
Tel No: ++ 32 3 475 2810
Fax No: ++ 32 3 227 3648



GERMANY – Farnell InOne
Tel No: ++ 49 89 61 39 39 39
Fax No: ++ 49 89 613 59 01



NORWAY – Farnell InOne
Tel No: ++ 45 44 53 66 66
Fax No: ++ 45 44 53 66 02



UK – BuckHickman InOne
++ 44 8450 510 150
++ 44 8450 510 130



BRAZIL – Farnell-Newark InOne
Tel No: ++ 55 11 4066 9400
Fax No: ++ 55 11 4066 9410



HONG KONG – Farnell-Newark InOne
Tel No: ++ 852 2268 9888
Fax No: ++ 852 2268 9899



PORTUGAL – Farnell InOne
Tel No: ++ 34 93 475 8804
Fax No: ++ 34 93 474 5288



UK – CPC
++ 44 8701 202 530
++ 44 8701 202 531



CHINA – Farnell-Newark InOne
Tel No: ++86 10 6238 5152
Fax No: ++86 10 6238 5022



IRELAND – Farnell InOne
Tel No: ++ 353 1 830 9277
Fax No: ++ 353 1 830 9016



SINGAPORE – Farnell-Newark InOne
Tel No: ++ 65 6788 0200
Fax No: ++ 65 6788 0300



export Tel No: ++ 44 8701 200 208
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



DENMARK – Farnell InOne
Tel No: ++ 45 44 53 66 44
Fax No: ++ 45 44 53 66 06



ITALY – Farnell InOne
Tel No: ++ 39 02 93 995 200
Fax No: ++ 39 02 93 995 300



SPAIN – Farnell InOne
Tel No: ++ 34 93 475 8805
Fax No: ++ 34 93 474 5107



ESTONIA – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



MALAYSIA – Farnell-Newark InOne
Tel No: ++ 60 3 7873 8000
Fax No: ++ 60 3 7873 7000



SWEDEN – Farnell InOne
Tel No: ++ 46 8 730 50 00
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2004.

PRO-POWER
Quality Cables