





mat'l. code				surface				tolerance				projection				product family			
—				ISO 1302 ✓				ISO 406 ISO 1101								RIBCAGE			
ltr	ecn	no	dr	date				tolerances unless otherwise specified								title			
AA	M08-0245	MHT	8/27/08					angles		linear		.XX±.01/0.3							
AB	M09-0058	MHT	4/04/09							.XXX±.005/0.13									
AC	M09-0087	MHT	06/10/09					±2'				.XXXX±.0020/0.051		scale 3:1					
AD	N10-0174	YO	6/17/10	dr	M. CORNMAN		6/07/95						dwg no				sheet 1 of 8		size
AE	ELX-N-004143	YO	06/20/11	enrg	D. WHITING		6/07/95						95781						A3
AF	ELX-N-004665	YO	07/27/11	chr	D. WHITING		6/07/95												
AG	ELX-N-009746	YO	1/20/12	appd	D. WHITING		6/07/95												
sheet	revision				AG	AG	AG	AG	AG	AG	AG	AG	AG	AG	AG	AG			
index	sheet		1	2	3	4	5	6	7	8									

SIZE	DIM H	DIM J	DIM K	DIM L
2X5	.275/6.99	.200/5.08	.372/9.45	.320/8.13
2X10	.525/13.34	.450/11.43	.622/15.80	.570/14.48
2X15	.775/19.68	.700/17.78	.872/22.15	.820/20.83
2X20	1.025/26.03	.950/24.13	1.122/28.50	1.070/27.18
2X25	1.275/32.38	1.200/30.48	1.372/34.85	1.320/33.53
2X30	1.525/38.74	1.450/36.83	1.622/41.20	1.570/39.88
2X35	1.775/45.08	1.700/43.18	1.872/47.55	1.820/46.23
2X40	2.025/51.43	1.950/49.53	2.122/53.90	2.070/52.58
2X45	2.275/57.78	2.200/55.88	2.372/60.25	2.320/58.93
2X50	2.525/64.14	2.450/62.23	2.622/66.60	2.570/65.28






SECTION X-X
ROTATED 90° CW





SECTION Y-Y

mat'l. code —				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family RIBCAGE			
ltr	ecn	no	dr	date	tolerances unless otherwise specified		scale 3:1	title RIBCAGE III SMT VERT. HEADER ASS'Y		
AG					angles	linear				
						.XX±.01/0.3				
						.XXX±.005/0.13				
					±2°	.XXXX±.0020/0.051				
				dr	M. CORNMAN	6/07/95	FCI	dwg no		sheet 2 of 8
				enrg	D. WHITING	6/07/95		95781		size A3
				chr	D. WHITING	6/07/95				
				appd	D. WHITING	6/07/95		type Product Customer Drawing		
sheet index	revision sheet									



LOCATOR/HOLDDOWN VARIATIONS



$\phi .0520$ [1.321]
 $\phi .040$ [1.02]
 $\phi .004/0.10$ (M) A (S) B (S) (ALL PEG CONFIGURATIONS)





R.0050 [0.127]
 $\phi .0394$ [1.000]
 $\phi .028$ [0.71]
 $\phi .024$ [0.61]





$\phi .034 \pm .001$ [0.86 $\pm$ 0.03]
 $\phi .0520^{+.0005}_{-.0010}$ [1.321 $\pm$ 0.013]
 $\phi .0030$ [0.076]
 $\phi .040^{+.001}_{-.002}$ [1.02 $\pm$ 0.03]
 $\phi .008 \pm .003$ [0.20 $\pm$ 0.08]

STYLE 5





$\phi .0470^{+.0005}_{-.0010}$ [1.194 $\pm$ 0.013]
 $\phi .040^{+.001}_{-.002}$ [1.02 $\pm$ 0.03]
 $\phi .0470^{+.0005}_{-.0010}$ [1.194 $\pm$ 0.013]
 $\phi .040^{+.001}_{-.002}$ [1.02 $\pm$ 0.03]

STYLE 6
 SEE NOTE 9



$\phi .0520^{+.0005}_{-.0010}$ [1.321 $\pm$ 0.013]
 $\phi .040^{+.001}_{-.002}$ [1.02 $\pm$ 0.03]
 $\phi .0520^{+.0005}_{-.0010}$ [1.321 $\pm$ 0.013]
 $\phi .040^{+.001}_{-.002}$ [1.02 $\pm$ 0.03]

STYLE 7



$\phi .0065 \pm .001$ [0.165 $\pm$ 0.025]
 $\phi .0400$ [1.02]
 $\phi .052 \pm .001$ [1.32 $\pm$ 0.025]
 R.002 [0.05] MAX

mat'l. code				surface		tolerance		projection		product family			
-				ISO 1302		ISO 406		ISO 1101		RIBCAGE			
ltr	ec	no	dr	date		tolerances unless otherwise specified		INCH/MM		title			
AG						linear		scale 3:1		RIBCAGE III SMT			
						angles				VERT. HEADER ASS'Y			
						±2°				dwg no			
						dr				sheet 3 of 8			
						enr				95781			
						chr				A3			
						appd				type			
										Product Customer Drawing			
sheet		revision											
index		sheet											


PDS: Rev :AG

STATUS: Released


Printed: Feb 17, 2012

RECOMMENDED PCB MOUNTING PAD PATTERN


STYLE 1




STYLE 5




STYLE 4




STYLE 2




STYLE 7




STYLE 6



STYLE 3



mat'l. code -				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family RIBCAGE
ltr	ecn	no	dr	date	tolerances unless otherwise specified	scale 3:1	title RIBCAGE III SMT VERT. HEADER ASS'Y
AG					angles linear ±2'		
					dr M. CORNMAN 6/07/95	FCI	dwg no 95781 sheet 4 of 8 size A3
					enrg D. WHITING 6/07/95		
					chr D. WHITING 6/07/95		
					appd D. WHITING 6/07/95		
sheet index	revision sheet						type Product Customer Drawing



Copyright FCI

FCIconnect.com

PRODUCT NUMBER NOTE 11,4C	QTY. REEL	TAPE WIDTH PITCH MM	CONNECTOR ORIENTATION IN TAPE POCKET
87409-135TR	500	72/12	VIEW 1
87409-140TR	↑	72/12	↑
87409-145TR		72/12	
87409-150TR		88/12	
87849-105TR		24/12	
87849-110TR		24/12	
87849-115TR		44/12	
87849-120TR		44/12	
87849-125TR		56/12	
87849-130TR		56/12	
87849-135TR		72/12	
87849-140TR		72/12	
87849-145TR		72/12	
87849-150TR		88/12	
88566-110TR		24/12	
88566-115TR	↓	44/12	
88566-130TR	500	56/12	
90098-105TR	400	24/12	
90098-110TR	400	32/12	
90098-115TR	500	44/12	
90098-120TR	500	44/12	
90098-125TR	400	56/12	
90098-130TR	500	56/12	
90098-135TR	↑	72/12	
90098-140TR		72/12	
90098-145TR		72/12	
90098-150TR		88/12	
90863-110	↓	24/12	↓
90863-115	500	44/12	VIEW 1

TABLE C

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302 ✓		ISO 406 ISO 1101				RIBCAGE	
ltr	ecn	no	dr	date		tolerances unless otherwise specified		title	
AG						angles	linear	RIBCAGE III SMT	
								VERT. HEADER ASS'Y	
						±2°		scale 3:1	
						dr	M. CORNMAN	6/07/95	
						enrg	D. WHITING	6/07/95	
						chr	D. WHITING	6/07/95	
						appd	D. WHITING	6/07/95	
sheet	revision								
index	sheet								

FCI

scale 3:1

dwg no 95781

type Product Customer Drawing

sheet 7 of 8 size A3

form: A3

PDS: Rev :AG

STATUS:Released

Printed: Feb 17, 2012

1

2

3

4

5

6

PRODUCT NUMBER NOTE 11,4C	QTY. REEL	TAPE WIDTH PITCH MM	CONNECTOR ORIENTATION IN TAPE POCKET
90863-115REV	500	44/12	VIEW 2
90863-120	↑	44/12	VIEW 1
90863-125		56/12	↑
90863-130		56/12	
91036-110P		24/16	
93206-110TR	↓	24/12	
93206-115TR	500	44/12	
93221-105TR	400	24/12	
93221-110TR	400	32/12	
93221-115TR	500	44/12	
93221-120TR	500	44/12	
93221-125TR	400	56/12	
93221-130TR	500	56/12	
93221-135TR	↑	72/12	
93221-140TR		72/12	
93221-145TR	↓	72/12	↓
93221-150TR	500	88/12	VIEW 1

TABLE C

NOTES:

① XXXXX-XXXLF

LEAD FREE OPTION (NOTE 11& 13)

NUMBER OF POSITIONS (NOTE 2)

2. NUMBER OF POSITIONS = 05 THRU 50 IN 5 POS INCREMENTS.
(EXAMPLE : 105=10 POS., 110=20 POS. ETC.)

③ REQUIRED ON -X40,-X45 & -X50 POSITION PARTS ONLY.

④ PACKAGING :
A. ANTISTATIC TUBES. SEE TABLE A
B. ADD "CT" TO END OF DASH NUMBER FOR CONNECTOR WITH VACUUM CAP IN ANTISTATIC TUBES.
EX. : XXXXX-1XXCT
C. PRESSURE SEALED TAPE AND REEL. SEE TABLE C FOR AVAILABLE PART NUMBERS.

5. HOUSING MATERIAL :
GLASS FILLED THERMOPLASTIC FLAME RETARDANT PER UL 94V-0.
COLOR : NATURAL

6. TERMINAL PLATING :
30u"/.76u HARD GOLD OR GXT OVER 50u"/1.27u NI ON CONTACT ZONES.
100u"/2.54u PURE TIN OVER 50u"/1.27u Ni IN SOLDERING ZONES.

⑦ MOLDING FLOW RESTRICTOR QUANTITY AND LOCATION IS MANUFACTURING OPTION.

⑧ VACUUM CAP SLOT REQUIRED ON ALL SIZES, SLOT MAY BE LOCATED ON OPPOSITE SIDE FOR 2 X 5.

⑨ STYLE 6 IS NOT AVAILABLE IN TAPE AND REEL.

⑩ 90863-1XX IS PACKAGED ONLY IN TAPE AND REEL.

⑪ ADD LF SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.

12. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 20 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN. SEE APPLICATION NOTE/PROCEDURES IF THEY ARE AVAILABLE.

13. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.

14. PRODUCT SPECIFICATION SEE BUS-12-087.

mat'l. code

—

surface

ISO 1302 ✓

tolerance

ISO 406

ISO 1101

projection

product family

RIBCAGE

litr

ecn

no

dr

date

tolerances unless otherwise specified

angles

linear

.XX±.01/0.3

.XXX±.005/0.13

.XXXX±.0020/0.051

INCH/MM

scale 3:1

title

RIBCAGE III SMT

VERT. HEADER ASS'Y

dr

M. CORNMAN

6/07/95

enrg

D. WHITING

6/07/95

chr

D. WHITING

6/07/95

appd

D. WHITING

6/07/95

sheet

revision

sheet

dwg no

95781

sheet 8 of 8

size

A3

type

Product Customer Drawing

FCI

Copyright FCI

form: A3

1

2

3

4

5

6

PDS: Rev :AG

STATUS: Released

Printed: Feb 17, 2012