

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS								DOC. NO. SPC-F005	* Effective: 12/21/98	* DCP No: 680
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE		
1116	C	Drawing Was CRS-TV-***	JWM	6/11/01	JC	6/20/01	JC	6/20/01		
1199	D	Redrawn & Bulk items added	JWM	4/11/02	JC	4/11/02	JC	4/11/02		

Notes:

Material: Electro-tin plated Copper
Insulating Material: Vinyl (PVC) UL94V-0
Voltage Rating: 600V
Operating Temp: -40°F to 221°F (-40°C ~ 105°C)

SPC Type No.	Package Qty.	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	"T" Barrel I.D.	"W" Max. Insulator Diameter	Color
CRS-TV-1006	50	12 ~ 10	6	.28	.29	.98	.84	.040	.135	.250	Yellow
SPC3763	500		8	.28	.29	.98					
CRS-TV-1008	50		10	.38	.29	1.03					
SPC3764	500		1/4	.53	.44	1.26					
CRS-TV-1010	50	16 ~ 14	8	.31	.33	.93	.78	.030	.090	0.147	Blue
SPC3766	500		10	.31	.33	.93					
CRS-TV-1025	50		1/4	.53	.44	1.26					
SPC3767	500		5/16	.54	.44	1.26					
CRS-TV-1037	50	22 ~ 18	2	.25	.22	.80	.67	.030	.070	0.145	Red
CRS-TV-1406	100		4	.25	.22	.80					
SPC3760	1000		6	.25	.22	.80					
CRS-TV-1406-S	100		10	.33	.29	.90					
CRS-TV-1408	100	16 ~ 14	8	.31	.33	.93	.78	.030	.090	0.147	Blue
SPC3761	1000		10	.31	.33	.93					
CRS-TV-1408-S	100		1/4	.47	.40	1.08					
SPC3899	1000		2	.25	.22	.80					
CRS-TV-1410	100	22 ~ 18	4	.25	.22	.80	.67	.030	.070	0.145	Red
CRS-TV-1410-S	100		6	.25	.22	.80					
CRS-TV-1425	100		10	.31	.33	.93					
SPC3762	1000		1/4	.47	.40	1.08					
CRS-TV-1802	100	16 ~ 14	8	.31	.33	.93	.78	.030	.070	0.145	Red
CRS-TV-1804	100		10	.31	.33	.93					
SPC3755	1000		1/4	.47	.40	1.08					
CRS-TV-1806	100		2	.25	.22	.80					
SPC3756	1000	22 ~ 18	4	.25	.22	.80	.67	.030	.070	0.145	Red
CRS-TV-1808	100		6	.25	.22	.80					
SPC3757	1000		10	.31	.33	.93					
CRS-TV-1810	100		1/4	.47	.40	1.08					
SPC3758	1000	16 ~ 14	8	.31	.33	.93	.78	.030	.070	0.145	Red
CRS-TV-1825	100		10	.31	.33	.93					
SPC3759	1000		1/4	.47	.40	1.08					
CRS-TV-1825	100		2	.25	.22	.80					

DISCLAIMER
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

Tolerances: Unless
Otherwise Specified:
X = ±.015
.XX = ±.010
.XXX = ±.005



ES8918



LR22190M6

SPC-F005.DWG



SPC TECHNOLOGY

DRAWING TITLE:

Vinyl Insulated Butted Seam Ring Tongue Terminals

SIZE DWG. NO.

A TA-352

ELECTRONIC FILE

TA-352.dwg

REV

D

SCALE: NTS

U.O.M.: INCHES [mm]

SHEET: 1 OF 1