

# Double Row Terminal Blocks

## Kulka® 600A/800A GP Series

### 300 Volts AC/DC (Class B)

600A Series only

### 150 Volts AC/DC (Class C)

600A and 800A Series



600A GP 06

#### Specifications:

- Base, Phenolic, 150°C (UL RTI)
- Open Back Design (Insulator Strip required for Voltage Rating - see page 112)
- JJ (GDI-30F) Material Available
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-22 Poles
- 3/8" Centers
- Wire Range With Wire Binding Screw  
#12 - #22 AWG – 15 Amps
- 800A Series (Riveted KT's) - see page 105
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- 
- RoHS Compliant

| Kulka®<br>Catalog # | # of poles | Dimensions |      |
|---------------------|------------|------------|------|
|                     |            | A          | B    |
| 600A GP 01          | 1          | 1.03       | 0.75 |
| 600A GP 02          | 2          | 1.41       | 1.13 |
| 600A GP 03          | 3          | 1.78       | 1.50 |
| 600A GP 04          | 4          | 2.16       | 1.88 |
| 600A GP 05          | 5          | 2.53       | 2.25 |
| 600A GP 06          | 6          | 2.91       | 2.63 |
| 600A GP 07          | 7          | 3.28       | 3.00 |
| 600A GP 08          | 8          | 3.66       | 3.38 |
| 600A GP 09          | 9          | 4.03       | 3.75 |
| 600A GP 10          | 10         | 4.41       | 4.13 |
| 600A GP 11          | 11         | 4.78       | 4.50 |
| 600A GP 12          | 12         | 5.16       | 4.88 |
| 600A GP 13          | 13         | 5.53       | 5.25 |
| 600A GP 14          | 14         | 5.91       | 5.63 |
| 600A GP 15          | 15         | 6.28       | 6.00 |
| 600A GP 16          | 16         | 6.66       | 6.38 |
| 600A GP 17          | 17         | 7.03       | 6.75 |
| 600A GP 18          | 18         | 7.41       | 7.13 |
| 600A GP 19          | 19         | 7.78       | 7.50 |
| 600A GP 20          | 20         | 8.16       | 7.88 |
| 600A GP 21          | 21         | 8.53       | 8.25 |
| 600A GP 22          | 22         | 8.91       | 8.63 |

mm=dim X 25.4

For electronic drawings or 2D/3D CAD data, submit request at [www.marathonsp.com/drawings.html](http://www.marathonsp.com/drawings.html)

#### Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

| CATALOG # | PRODUCT   | PAGE                          |
|-----------|-----------|-------------------------------|
| MSP       | KULKA     | REFERENCE                     |
|           | KT19      | Full Quick Connect (0° Flat)  |
|           | KT20      | Full Quick Connect (45° Bend) |
|           | KT21      | Full Quick Connect (90° Bend) |
|           | KT25      | Half Quick Connect (0° Flat)  |
|           | KT26      | Half Quick Connect (45° Bend) |
|           | KT27      | Half Quick Connect (90° Bend) |
|           | ST        | Full Solder                   |
|           | 3/4 ST    | Half Solder                   |
|           | Y         | Feed Thru Solder (.312)       |
|           | YSY       | Feed Thru Solder (.500)       |
|           | Z         | Lug Over the Side (.625)      |
|           | J 600     | Line to Line Jumper           |
|           | 600 RJ(S) | Multiple Position Jumper      |
|           | 3860      | Wire Clamp Screw, Brass       |
|           | 3865      | Wire Clamp Screw              |
|           | 2002      | Stud                          |
| PSB       |           | Phil-Slot Brass Screw         |
|           |           | Consult C/S                   |

Quick Connects: .020" x .187"

See pages 104-115 for terminal block accessories

