

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

CJ

Chip Type, High Reliability.
Low temperature ESR specification.
series



- Chip type, high temperature range, for +125°C use.
- Added ESR specification after the test at -40°C
(Φ6.3 sizes provide only for the first stage.)
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).







CZ Low ESR Long Life CJ UB Added ESR specification at -40°C



■ Specifications

Item	Performance Characteristics																	
Category Temperature Range	-40 to +125°C																	
Rated Voltage Range	10 to 50V																	
Rated Capacitance Range	10 to 470μF																	
Capacitance Tolerance	±20% at 120Hz, 20°C																	
Leakage Current	After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4(μA), whichever is greater.																	
Tangent of loss angle (tan δ)	<table border="1"> <thead> <tr> <th>Rated voltage (V)</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> </thead> <tbody> <tr> <td>tan δ (MAX.)</td> <td>0.32</td> <td>0.24</td> <td>0.21</td> <td>0.18</td> <td>0.18</td> </tr> </tbody> </table>						Rated voltage (V)	10	16	25	35	50	tan δ (MAX.)	0.32	0.24	0.21	0.18	0.18
Rated voltage (V)	10	16	25	35	50													
tan δ (MAX.)	0.32	0.24	0.21	0.18	0.18													
Stability at Low Temperature	<table border="1"> <thead> <tr> <th>Rated voltage (V)</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> </thead> <tbody> <tr> <td>Impedance ratio ZT / Z20 (MAX.)</td> <td>Z-40°C / Z+20°C</td> <td>12</td> <td>8</td> <td>6</td> <td>4</td> </tr> </tbody> </table>						Rated voltage (V)	10	16	25	35	50	Impedance ratio ZT / Z20 (MAX.)	Z-40°C / Z+20°C	12	8	6	4
Rated voltage (V)	10	16	25	35	50													
Impedance ratio ZT / Z20 (MAX.)	Z-40°C / Z+20°C	12	8	6	4													
Endurance	<p>The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 125°C.</p> <table border="1"> <thead> <tr> <th>Capacitance change</th> <th>Within ±30% of the initial capacitance value</th> </tr> </thead> <tbody> <tr> <td>tan δ</td> <td>300% or less than the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>Less than or equal to the initial specified value</td> </tr> </tbody> </table>						Capacitance change	Within ±30% of the initial capacitance value	tan δ	300% or less than the initial specified value	Leakage current	Less than or equal to the initial specified value						
Capacitance change	Within ±30% of the initial capacitance value																	
tan δ	300% or less than the initial specified value																	
Leakage current	Less than or equal to the initial specified value																	
Shelf Life	After storing the capacitors under no load at 125°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.																	
Resistance to soldering heat	<p>The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.</p> <table border="1"> <thead> <tr> <th>Capacitance change</th> <th>Within ±10% of the initial capacitance value</th> </tr> </thead> <tbody> <tr> <td>tan δ</td> <td>Less than or equal to the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>Less than or equal to the initial specified value</td> </tr> </tbody> </table>						Capacitance change	Within ±10% of the initial capacitance value	tan δ	Less than or equal to the initial specified value	Leakage current	Less than or equal to the initial specified value						
Capacitance change	Within ±10% of the initial capacitance value																	
tan δ	Less than or equal to the initial specified value																	
Leakage current	Less than or equal to the initial specified value																	
Marking	Black print on the case top.																	

■ Chip Type



■ Dimensions

Cap.(μF)	Code	V		10		16		25		35		50	
		1A	1C	1A	1C	1E	1V	1A	1C	1E	1V	1A	1H
10	100											6.3×8.7	14
22	220							6.3×8.7	14	-	95	6.3×8.7	14
33	330							6.3×8.7	14	-	95	6.3×8.7	14
47	470					6.3×8.7	14	-	95	6.3×8.7	14	-	95
100	101	6.3×8.7	14	-	95	8×10	2.0	6.0	250	8×10	2.0	6.0	250
220	221	8×10	2.0	6.0	250	10×10	1.5	4.5	400	10×10	1.5	4.5	400
330	331	10×10	1.5	4.5	400	10×10	1.5	4.5	400	10×10	1.5	4.5	400
470	471	10×10	1.5	4.5	400								

ΦD×L (mm)	6.3×8.7	8×10	10×10
A	2.4	2.9	3.2
B	6.6	8.3	10.3
C	6.6	8.3	10.3
E	2.2	3.1	4.5
L	8.7	10	10
H	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

Rated Voltage	V	10	16	25	35	50
Code	A	C	E	V	H	

● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

Max. ESR (Ω) at -40°C 100kHz, Rated ripple current (mA rms) at 125°C 100kHz

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.

CAT.8100C