


BCN

Features

- Thick Film
- Chip Resistor Arrays
- RoHS Compliant
- Sulphur resistant version available (Tested to ASTM-B809)
- Range extended to include 0201 size resistors



Model Styles

Model (Width)	# of Resistors	Circuit	Package Size	Chip Array	Edge Finish / Termination		
					Scalloped Convex	Square Convex	Square Concave
Model BCN 06 2 (0.6mm)	2 Resistors	Isolated	0302	0201		•	
Model BCN 06 4 (0.6mm)	4 Resistors	Isolated	0502	0201		•	
Model BCN 2D (1.6mm)	2 Resistors	Isolated	0606	0603	•		
Model BCN 10 (1.0mm)	4 Resistors	Isolated	0804	0402		•	
Model BCN 16 4ABI (1.6mm)	4 Resistors	Isolated	1206	0603			•
Model BCN 16 4A/AB (1.6mm)	4 Resistors	Isolated	1206	0603	•	•	
Model BCN 16 8RB/8SB (1.6mm)	8 Resistors	Bussed	1206	0603		•	
Model BCN 21 (2.1mm)	8 Resistors	Bussed	1608	0804			•
Model BCN 4D (3.1mm)	4 Resistors	Isolated	2112	1206	•		
Model BCN 4DBI (3.1mm)	4 Resistors	Isolated	2112	1206			•
Model BCN 31 8RB/8SB (3.1mm)	8 Resistors	Bussed	2512	1206		•	
Model BCN 31 8RBI/8SBI (3.1mm)	8 Resistors	Bussed	2512	1206			•
Jumper Chip Array	4/8 Resistors	Isolated/Bussed	All	All	•	•	•

Features

- Reliable monolithic construction
- Nickel barrier terminations
- Top side marking for easy identification
- Concave or convex termination styles
- Square or scalloped edges available

Benefits

- Saves board space over equivalent rated chip resistors
- Eliminates up to seven pick & place operations
- Single component reliability
- Leadless chip, reduced inductance
- Mounts close to active devices

Applications

- Pull up / pull down resistors for digital IC's
- Series termination on high speed data busses
- Current limit for LED displays
- Available as an 8 bit R/2R Ladder Network

General Note

TT electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT electronics' own data and is considered accurate at time of going to print.


Electrical

Standard Resistance Range, Ohms	BCN06 2, BCN06 4, BCN2D, BCN4D, BCN10, BCN16 4: BCN 16 8R / 8S: BCN 31 8R / 8S: BCN 21:	10 to 1 Megohm 100 to 1 Megohm 22 to 1 Megohm 68 to 220K
Standard Resistance Tolerance	Optional: $\pm 1\%$ (F Tol.), BCN 4D, BCN 16 4, BCN31 8RB / 8SB Only $\pm 2\%$ (G Tol.), BCN 16 4, BCN31 8RB / 8SB Only	
Operating Voltage, Maximum	BCN 4D: BCN 2D, BCN 16 4, BCN 31 8R / 8S: BCN 10, BCN 16 8R / 8S, BCN 21: BCN 06 2, BCN 06 4:	75Vdc or $\sqrt{pr}$ 50Vdc or $\sqrt{pr}$ 25Vdc or $\sqrt{pr}$ 12.5Vdc or $\sqrt{pr}$
Power Rating, watts at 70°C	BCN 2D: BCN 4D: BCN 06 2: BCN 06 4: BCN 10, BCN 164: BCN 16 8R / 8S: BCN 21, BCN 31 8R / 8S:	63mW per Resistor / 125mW per Package 125mW per Resistor / 500mW per Package 31mW per Resistor / 63mW per Package 31mW per Resistor / 125mW per Package 63mW per Resistor / 250mW per Package 32mW per Resistor / 250mW per Package 63mW per Resistor / 500mW per Package

Environmental

Operating Temperature Range	-55°C to +125°C	
Temperature Coefficient of Resistance	BCN 2D: BCN 06 2, BCN 06 4, BCN 4D, BCN 16 8R / 8S, BCN 21, BCN 31: BCN 10, BCN 16 4:	$\pm 300\text{ppm}/^\circ\text{C}$ $\pm 200\text{ppm}/^\circ\text{C}$ $\pm 200\text{ppm}/^\circ\text{C}$
Moisture Resistance	1,000 hours @ +40°C, 95% R.H. (3.0% +0.1 Ω Δ R)	
High Temperature Operation	1,000 hours @ 70°C (3.0% +0.1 Ω Δ R)	
Short Time Overload	2.5 X rated voltage, 5 seconds (2.0% +0.1 Ω Δ R)	
Temperature Cycling	-55°C to +125°C, 5 cycles (1.0% +0.1 Ω Δ R)	
Resistance to Solder Heat	260°C for 10 seconds (1.0% +0.1 Ω Δ R)	
Load Life	1,000 hours @ 70°C (3.0% +0.1 Ω Δ R)	


Construction



General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Electrical



Standard Resistance Values, Ohms

Model BCN 06, BCN 2D, BCN 4D, BCN 10 & BCN 16 4					
10	100	1K	10K	100K	1 Meg
12	120	1.2K	12K	120K	Jumper
15	150	1.5K	15K	150K	
18	180	1.8K	18K	180K	
22	220	2.2K	22K	220K	
27	270	2.7K	27K	270K	
33	330	3.3K	33K	330K	
39	390	3.9K	39K	390K	
47	470	4.7K	47K	470K	
56	560	5.6K	56K	560K	
68	680	6.8K	68K	680K	
82	820	8.2K	82K	820K	

Model BCN 16 8R & BCN 16 8S			
220	1K	10K	100K
330	4.7K	47K	1 Meg


Model BCN 31 8R		Model BCN 31 8S	
220	2.2K	10K	100K
330	2.7K	22K	470K
1K	4.7K	47K	1 Meg

Model BCN 21			
68	330	4.7K	10K
220	1K	47K	100K

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.


Outline Dimensions (Inch /mm)




General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Outline Dimensions (Inch /mm)

Exterior Termination (Convex) Square Edge: Models BCN 16 8R, 8S							
							
L	W	T	A	B1	B2	C	P
.126 ±.008	.063 ±.008	.020 ±.004	.012 ±.006	.014 ±.006	.020 ±.006	.008	.025
3.20 ±0.20	1.60 ±0.20	0.50 ±0.10	0.30 ±0.15	0.36 ±0.15	0.50 ±0.15	0.20	0.64


Interior Termination (Concave) Square Edge: Models BCN 21						
						
L	W	T	A	B	C	D
.157 ±.008	.083 ±.008	.021 ±.004	.020 ±.008	.010 ±.008	.020 ±.008	.012 ±.008
4.00 ±0.20	2.10 ±0.20	0.55 ±0.10	0.50 ±0.20	0.25 ±0.20	0.50 ±0.20	0.30 ±0.20
A1	B1	C1	D1	E		P
.016 ±.008	.014 ±.008	.020 ±.008	.014 ±.008	.012 Typ.		.032 Typ.
0.40 ±0.20	0.40 ±0.20	0.50 ±0.20	0.35 ±0.20	0.30		0.80

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Outline Dimensions

Exterior Termination (Convex)
Square Edge: Models BCN 06 2, BCN 06 4




Unit : mm

Type	Number of Resistors	L	W	H	A	B	C	Y	Weight (g) (1000pcs)
BCN 06 2	2	0.80 ± 0.10	0.60 ± 0.10	0.35 ± 0.10	0.30 ± 0.10	0.50 ± 0.10	0.15 ± 0.10	0.15 ± 0.10	0.500
BCN 06 4	4	1.40 ± 0.10	0.60 ± 0.10	0.35 ± 0.10	0.20 ± 0.10	0.40 ± 0.10	0.10 ± 0.07	0.15 ± 0.05	0.833

Solder Pad Layout

Exterior Termination (Convex)
Square Edge: Models BCN 06 2, BCN 06 4





Unit : mm

Type	A	B	C	I	P
BCN 06 2	0.80	0.90	-	0.30	0.50
BCN 06 4	1.40	0.90	0.20	0.30	0.40

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Solder pad layout (Inch / mm)

											
BCN 2D BCN 4D/4DBI BCN 16 4A, AB, ABI BCN 31 8R, 8S	Wave Solder Process						Re-flow Solder Process				
	P	A	B	C	X	Y	A	B	C	X	Y
	.032	.039	.102	.014	.018	.032	.039	.079	.014	.018	.020
	0.80	1.00	2.60	0.35	0.45	0.80	1.00	2.00	0.35	0.45	0.50
	.050	.087	.169	.022	.028	.041	.087	.154	.022	.028	.034
	1.27	2.20	4.30	0.57	0.70	1.05	2.20	3.90	0.57	0.70	0.85
	.032	.039	.118	.014	.018	.039	.039	.118	.014	.018	.039
	0.80	1.00	3.00	0.35	0.45	1.00	1.00	3.00	0.35	0.45	1.00
	.050	.084	.148	.014	.036	.032	.084	.148	.014	.036	.032
	1.27	2.10	3.70	0.35	0.90	0.80	2.10	3.70	0.35	0.90	0.80
BCN 16 8RB / 8SB 											
BCN 16 8RB / 8SB	Wave Solder Process						Re-flow Solder Process				
	P	A	B	X	X1	Y	A	B	X	X1	Y
	.025	.048	.096	.012	.018	.024	.048	.096	.012	.018	.024
	0.64	1.20	2.40	0.30	0.45	0.60	1.20	2.40	0.30	0.45	0.60

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Solder pad layout (Inch / mm)

BCN 10

The diagram illustrates the BCN 10 layout. It features two rows of four rectangular pads each. The top row is labeled 'A' on the left and 'B' on the right. The bottom row is labeled 'X' and 'X1' below the pads. Dimension 'L' is the total length of the top row. 'P' is the pitch between the first three pads, and 'P1' is the pitch between the third and fourth pads. 'Y' is the vertical distance between the two rows. 'X' and 'X1' are horizontal dimensions from the left edge to the center of the first and fourth pads in the bottom row, respectively.

BCN 10

P	P1	A	B	X	X1	Y	L
.024	.020	.020 ±.004	.060 ±.004	.010 ±.004	.018 ±.004	.020 ±.004	.085 ±.004
0.60	0.50	0.50 ±0.10	1.50 ±0.10	0.25 ±0.15	0.45 ±0.10	0.50 ±0.10	2.15 ±0.10

BCN 21

The diagram illustrates the BCN 21 layout. It features a 2x4 grid of rectangular pads. The top row is labeled 'C' below the pads. The bottom row is labeled 'X' below the pads. The right side is labeled 'A' and 'B' vertically. 'L' is the total length. 'W' is the width of the leftmost pad. 'W1' is the width of the rightmost pad. 'W2' is the height of the leftmost pad. 'W3' is the width of the leftmost pad. 'Y' is the vertical distance between the two rows. 'P' is the pitch between the first three pads in the bottom row. 'X' is the horizontal distance from the left edge to the center of the first pad in the bottom row.

BCN 21

P	A	B	C	X	Y	W	W1	W2	W3	L
.032	.060 ±.008	.120 ±.008	.016 ±.004	.016 ±.004	.030 ±.004	.012 ±.001	.015 ±.004	.030 ±.004	.030 ±.004	.196 ±.008
0.80	1.20 ±0.20	3.00 ±0.20	0.40 ±0.10	0.40 ±0.10	0.75 ±0.10	0.31 ±0.02	0.38 ±0.10	0.75 ±0.10	0.75 ±0.10	4.98 ±0.20

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Ordering Information

Model Series	BCN	4	D	B	I	102	J	7	S	Construction Option:
No. of Resistors:										No code = Standard product
BCN 2D = 2 Resistors										S = Sulphur resistant - only
BCN 4D = 4 Resistors										on BCN4DxxxJ7
Circuit Configuration:										Packaging Option:
D = Isolated										7" or 13"
										(See Table A)
Edge Option (B = Square Edge):										Tolerance: ±5%
BCN 2D: Scalloped Edge Only - No Code Used										Resistance Code
BCN 4D: Scalloped Edge Only - No Code Used										Termination Code:
										I = Interior (Concave) Termination
										(Only available in BCN 4 DBI)

Model Series	BCN	16	4	A	B	I	102	J	7	S	Construction Option:
Width:											No code = Standard product
06 = 0.6mm											S = Sulphur resistant - only
10 = 1.0mm											on BCN 104/164/168RB
16 = 1.6mm											Packaging Option:
21 = 2.1mm											7" or 13"
31 = 3.1mm											(See Table A)
No. of Resistors:											Tolerance:
BCN 06 2 = 2 Resistors											F = ±1% (BCN 4D / 16 4 / 31 8RB / 31 8SB)
BCN 10 / 06 4 / 16 4 = 4 Resistors											G = ±2% (BCN 16 4, 31 8RB / 8SB Only)
BCN 16 8R / 16 8S = 8 Resistors											J = ±5% (Standard)
BCN 21 / 31 8R / 31 8S = 8 Resistors											(Use JP for Jumper Chip Array - BCN 16 4 / 31)
Circuit Configuration:											Resistance Code:
A = Isolated (BCN 06 / 10 / 16 4A)											3 digits for E4,E12,E24 Series, all Tol.
R = Bussed (Reversed) (BCN 16 8R / 31 8R)											4 digits for E96 Series, 1% Tol.
S = Bussed (Standard) (BCN 21 / 16 8S / 31 8S)											Termination Code:
Edge Option (B = Square Edge):											I = Interior (Concave) Termination
Scalloped Edge - No Code Used (Standard)											No code used for exterior termination (Standard)
Square Edge Only - Use Code 'B'											All interior termination requires 'B' for square edge
											(BCN 16 4ABI / 31 8RBI / 31 8SBI)

See 'Model Styles' for Available Options

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.



www.bitechnologies.com www.ircct.com www.welwyn-tt.com

Packaging (Table A)

	7" Reel Diameter		13" Reel Diameter	
	Paper	Embossed	Paper	Embossed
BCN 2D	5K		20K	
BCN 4D		4K		16K
BCN 06 2	10K			
BCN 06 4	10K			
BCN 10	10K		40K	
BCN 16 4	5K		20K	
BCN 16 8	5K		20K	
BCN 21		4K		16K
BCN 31		4K		16K

Note: Tape & Reel dimensions per EIA-481.

Sulphur Resistant Arrays

- Special construction resists sulphide growth
- Withstands sulphur bearing fume environment
- Tested to ASTM-B809 ("Flowers-of-Sulphur")
- Suitable for industrial, automotive and roadside uses
- RoHS compliant matt Tin finish terminations

Performance Data

Hydrogen Sulphide exposure:

- 1000 Hours, 3-5ppm H₂S, 50°C, 92%RH
- 0.5% Max ΔR and no visual defects

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.