


Wet Tantalum Capacitors Silver Case with Glass-to-Metal Hermetic Seal, TANTALEX®



PERFORMANCE CHARACTERISTICS

Operating Temperature: -55 °C to +85 °C
(+125 °C with voltage derating)

Capacitance Range:

738D - 3.3 µF to 1200 µF; CT9 - 3.9 µF to 2200 µF

Capacitance Tolerance:

± 10 %, ± 20 %, ± 5 % (special order)

Voltage Rating: 6 V_{DC} to 125 V_{DC}

DC Leakage Current (DCL Max.): at +25 °C, +85 °C, and +125 °C: leakage current shall not exceed the values listed in the Standard Ratings tables.

Life Test: capacitors are capable of withstanding a 2000 h life test at a temperature of +85 °C or +125 °C at the applicable rated DC working voltage.

FEATURES

- Terminations: axial, standard tin / lead (SnPb), 100 % tin (RoHS-compliant) available
- High CV per unit volume
- Extremely low leakage current
- Improved reliability through the use of a glass-to-metal true hermetic anode seal is the prime feature of the 738D and CT9 TANTALEX® capacitors.
- The construction offers outstanding resistance to thermal shock
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non-RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details.

APPROVALS

CECC 30202-004 CT9 style



RoHS*
Available


**HALOGEN
FREE
GREEN**
(5-2008)
Available

ORDERING INFORMATION

CT9 738D	226	X0	100	B	2	E3
MODEL	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT +85 °C	CASE CODE	STYLE NUMBER	RoHS-COMPLIANT
	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	X0 = ± 20 % X9 = ± 10 % X5 = ± 5 % special order	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	See Ratings and Case Codes table	0 = bare case 2 = outer polyester film insulation 6 = high temperature film insulation	E3 = 100 % tin termination (RoHS-compliant design) Blank = SnPb termination (standard design)

Note

- Packaging: the use of formed plastic trays for packaging these axial lead components is standard. Tape and reel is not available due to the unit weight.

**DIMENSIONS** in inches [millimeters]

CASE CODE	D	L	D (Max.)	L (Max.)	LEAD LENGTH	MAX. WEIGHT (oz. / g)
	BARE TUBE		WITH OUTER PLASTIC-FILM INSULATION			
A	0.188 ± 0.016 [4.78 ± 0.41]	0.453 + 0.031 / - 0.016 [11.51 + 0.79 / - 0.41]	0.219 [5.56]	0.608 [15.45]	1.500 ± 0.250 [38.10 ± 6.35]	0.07 [2.0]
B	0.281 ± 0.016 [7.14 ± 0.41]	0.641 + 0.031 / - 0.016 [16.28 + 0.79 / - 0.41]	0.312 [7.92]	0.796 [20.22]	2.250 ± 0.250 [57.15 ± 6.35]	0.18 [5.1]
C	0.375 ± 0.016 [9.53 ± 0.41]	0.766 + 0.031 / - 0.016 [19.46 + 0.79 / - 0.41]	0.406 [10.31]	0.921 [23.40]	2.250 ± 0.250 [57.15 ± 6.35]	0.36 [10.2]
D	0.375 ± 0.016 [9.53 ± 0.41]	1.062 + 0.031 / - 0.023 [26.97 + 0.79 / - 0.58]	0.406 [10.31]	1.127 [30.91]	2.250 ± 0.250 [57.15 ± 6.35]	0.49 [13.9]

RATINGS AND CASE CODES 738D

μF	6.3	8	10	16	25	30	40	50	63	75	100	125
3.3												A
3.9												A
4.7											A	
5.6										A		
6.8										A		
8.2									A			
10								A				B
12							A					B
15						A						B
18					A						B	C
22					A						B	C
27				A					A	B		C
33				A						B	C	
39			A						B		C	D
47			A					B			C	D
56		A					B			C		D
68	A					B			C		D	
82					B			C			D	
100	A			A	B		C			D		
120				B		C				D		
150			B			C			D			
180			B		C			D				
220		B		C			D					
270	B			C		D						
330			C		D							
390			C		D							
470		C		D								
560	C			D								
680			D									
820		D										
1000	D											
1200	D											



RATINGS AND CASE CODES CT9									
μF	6.3	10	16	25	40	63	80	100	125
3.9									A
4.7								A	
6.8							A		A
8.2						A			
10								A	
12					A				
15									B
22				A			A	B	
27						A			B, C
33			A				B		
39					A	B		B	
47		A						C	C
56					B		C		D
68	A			A		C		C	
82							B	D	D
100			A	B	C	B	D		
120			B					D	
150		A			B	D			
180	A	B		C			C		
220					D	C	D		
270	B		C	B		D			
330					C				
390		C	B	D					
470					D				
560	C	B	D	C					
680				D					
820	B	D	C						
1000			D						
1200	D	C							
1500	C	D							
2200	D								



STANDARD RATINGS 738D

CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DF AT +20 °C (%)	MAX. IMP. AT -55 °C 100 kHz (Ω)	MAX. IMP. AT +20°C 100 kHz (Ω)	MAX. DCL (μA) AT		MAX. CAPACITANCE CHANGE (%) AT		
						+20 °C	+85 °C +125 °C	-55 °C	+85 °C	+125 °C
6.3 V _{DC} AT +85 °C; 4 V _{DC} AT +125 °C; 3 V _{DC} AT +175 °C										
68	A	738D686X06R3A2	17.1	10	1.0	1	2	-40	+10.5	+17.5
270	B	738D277X06R3B2	67.8	10	1.0	1	7	-44	+17.5	+20
560	C	738D567X06R3C2	151.9	10	1.0	2	13	-64	+17.5	+20
1000	D	738D108X06R3D2	100.5	10	1.0	3	14	-80	+25	+25
1200	D	738D128X06R3D2	120.6	10	1.0	3	14	-80	+25	+25
8 V _{DC} AT +85 °C; 5 V _{DC} AT +125 °C; 4 V _{DC} AT +175 °C										
56	A	738D566X0008A2	14.1	10	1.0	1	2	-40	+10.5	+16
220	B	738D227X0008B2	55.2	10	1.0	1	7	-44	+17.5	+20
470	C	738D477X0008C2	82.6	10	1.0	2	14	-64	+17.5	+20
820	D	738D827X0008D2	51.5	10	1.0	4	16	-80	+25	+25
10 V _{DC} AT +85 °C; 6.3 V _{DC} AT +125 °C; 5 V _{DC} AT +175 °C										
39	A	738D396X0010A2	15.1	10	1.0	1	2	-36	+12	+16
47	A	738D476X0010A2	15.1	10	1.0	1	2	-36	+14	+16
150	B	738D157X0010B2	28.2	10	1.0	1	6	-36	+14	+16
180	B	738D187X0010B2	45.2	10	1.0	1	7	-36	+14	+16
330	C	738D337X0010C2	51.9	10	1.0	2	16	-60	+17.5	+20
390	C	738D397X0010C2	73.5	10	1.0	2	16	-64	+17.5	+20
680	D	738D687X0010D2	42.7	10	1.0	4	16	-80	+25	+25
16 V _{DC} AT +85 °C; 10 V _{DC} AT +125 °C; 8 V _{DC} AT +175 °C										
27	A	738D276X0016A2	10.3	10	1.0	1	2	-28	+10.5	+16
33	A	738D336X0016A2	10.3	10	1.0	1	2	-28	+14	+16
100	A	738D107X9016A2	25.0	10	1.0	1	10	-44	+13	+16
120	B	738D127X0016B2	30.2	10	1.0	1	7	-28	+17.5	+20
220	C	738D227X0016C2	34.5	10	1.0	2	16	-50	+17.5	+18
270	C	738D277X0016C2	50.8	10	1.0	2	16	-56	+17.5	+20
470	D	738D477X0016D2	35.4	10	1.0	6	24	-80	+25	+25
560	D	738D567X0016D2	42.2	10	1.0	6	24	-80	+25	+25
25 V _{DC} AT +85 °C; 16 V _{DC} AT +125 °C; 13 V _{DC} AT +175 °C										
18	A	738D186X0025A2	6.9	10	1.0	1	2	-20	+10.5	+12
22	A	738D226X0025A2	6.9	10	1.0	1	2	-20	+10.5	+12
82	B	738D826X0025B2	20.6	10	1.0	1	10	-28	+13	+15
100	B	738D107X0025B2	25.1	10	1.0	1	10	-28	+13	+15
180	C	738D187X0025C2	42.2	10	1.0	2	18	-48	+13	+15
330	D	738D337X0025D2	27.2	10	1.0	7	28	-70	+25	+25
390	D	738D397X0025D2	31.8	10	1.0	7	28	-70	+25	+25
30 V _{DC} AT +85 °C; 19 V _{DC} AT +125 °C; 15 V _{DC} AT +175 °C										
15	A	738D156X0030A2	7.5	10	1.0	1	2	-20	+10.5	+12
68	B	738D686X0030B2	25.6	10	1.0	1	8	-24	+13	+15
120	C	738D127X0030C2	24.4	10	1.0	2	17	-44	+13	+15
150	C	738D157X0030C2	37.7	10	1.0	2	18	-48	+13	+15
270	D	738D277X0030D2	27.2	10	1.0	8	32	-60	+25	+25
40 V _{DC} AT +85 °C; 25 V _{DC} AT +125 °C; 20 V _{DC} AT +175 °C										
12	A	738D126X0040A2	6.7	10	1.0	1	2	-24	+8	+10
56	B	738D566X0040B2	21.1	10	1.0	1	9	-28	+13	+15
100	C	738D107X0040C2	15.7	10	1.0	2	17	-40	+13	+15
220	D	738D227X0040D2	25.0	10	1.0	8	32	-55	+25	+25

**STANDARD RATINGS 738D**

CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DF	MAX. IMP.	MAX. IMP.	MAX. DCL		MAX. CAPACITANCE		
			AT +20 °C	AT -55 °C	AT +20°C	(μA) AT	CHANGE (%) AT			
			(%)	100 kHz	100 kHz	+20 °C	+85 °C	-55 °C	+85 °C	+125 °C
				(Ω)	(Ω)		+125 °C			
50 V _{DC} AT +85 °C; 32 V _{DC} AT +125 °C; 25 V _{DC} AT +175 °C										
10	A	738D106X0050A2	5.7	10	1.0	1	2	-24	+8	+9
47	B	738D476X0050B2	17.7	10	1.0	1	9	-28	+12	+15
82	C	738D826X0050C2	20.6	10	1.0	2	16	-32	+12	+15
180	D	738D187X0050D2	23.7	10	1.0	8	32	-50	+25	+25
63 V _{DC} AT +85 °C; 40 V _{DC} AT +125 °C; 32 V _{DC} AT +175 °C										
8.2	A	738D825X0063A2	4.1	10	1.0	1	2	-24	+8	+9
27	A	738D276X9063A2	8.0	10	1.0	2	15	-24	+10	+12
39	B	738D396X0063B2	17.2	10	1.0	1	9	-28	+10.5	+12
68	C	738D686X0063C2	25.6	10	1.0	2	16	-32	+10.5	+12
150	D	738D157X0063D2	23.6	10	1.0	8	32	-40	+20	+20
75 V _{DC} AT +85 °C; 50 V _{DC} AT +125 °C; 38 V _{DC} AT +175 °C										
5.6	A	738D565X0075A2	3.4	10	1.0	1	2	-20	+8	+9
6.8	A	738D685X0075A2	3.4	10	1.0	1	2	-20	+8	+9
27	B	738D276X0075B2	11.8	10	1.0	1	9	-22	+11	+13
33	B	738D336X0075B2	14.5	10	1.0	1	10	-24	+15	+15
56	C	738D566X0075C2	21.8	10	1.0	2	17	-28	+15	+15
100	D	738D107X0075D2	19.5	10	1.0	9	36	-35	+20	+20
120	D	738D127X0075D2	23.3	10	1.0	9	36	-35	+20	+20
100 V _{DC} AT +85 °C; 63 V _{DC} AT +125 °C; 50 V _{DC} AT +175 °C										
4.7	A	738D475X0100A2	2.9	30	3.0	1	2	-16	+7	+8
18	B	738D186X0100B2	7.8	15	1.5	1	8	-16	+7	+8
22	B	738D226X0100B2	9.7	15	1.5	1	9	-16	+7	+8
33	C	738D336X0100C2	9.3	15	1.0	2	15	-16	+7	+8
39	C	738D396X0100C2	14.7	15	1.0	2	17	-20	+7	+8
47	C	738D476X0100C2	17.7	15	1.0	2	17	-20	+7	+8
68	D	738D686X0100D2	13.7	15	1.5	9	36	-25	+15	+15
82	D	738D826X0100D2	16.4	15	1.5	9	36	-25	+15	+15
125 V _{DC} AT +85 °C; 80 V _{DC} AT +125 °C; 63 V _{DC} AT +175 °C										
3.3	A	738D335X0125A2	3.4	30	3.0	1	2	-10	+7	+8
3.9	A	738D395X0125A2	3.4	30	3.0	1	2	-16	+7	+8
10	B	738D106X0125B2	9.4	15	1.5	1	5	-16	+7	+8
12	B	738D126X0125B2	8.3	15	1.5	1	6	-16	+7	+8
15	B	738D156X0125B2	11.2	15	1.5	1	7	-16	+7	+8
18	C	738D186X0125C2	10	15	1.0	2	9	-16	+7	+8
22	C	738D226X0125C2	12.1	15	1.0	2	11	-16	+7	+8
27	C	738D276X0125C2	16.7	15	1.0	2	13	-16	+7	+8
39	D	738D396X0125D2	7.5	15	1.5	10	40	-25	+15	+15
47	D	738D476X0125D2	9.2	15	1.5	10	40	-25	+15	+15
56	D	738D566X0125D2	14.2	15	1.5	10	40	-25	+15	+15



STANDARD RATINGS CT9

CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DF AT +20 °C (%)	MAX. IMP. AT -55 °C 100 Hz (Ω)	MAX. DCL (μA) AT		MAX. CAPACITANCE CHANGE (%) AT		
					+20 °C	+85 °C +125 °C	-55 °C	+85 °C	+125 °C
6.3 V _{DC} AT +85 °C; 4 V _{DC} AT +125 °C; 3 V _{DC} AT +175 °C									
68	A	CT9686X06R3A2	15	72	1	2	-40	+14	+16
270	B	CT9277X06R3B2	41	30	1	7	-44	+17.5	+20
560	C	CT9567X06R3C2	55	30	2	16	-64	+17.5	+20
1200	D	CT9128X06R3D2	94	24	4	16	-80	+25	+25
10 V _{DC} AT +85 °C; 6.3 V _{DC} AT +125 °C; 5 V _{DC} AT +175 °C									
47	A	CT9476X0010A2	14	120	1	2	-36	+14	+16
180	B	CT9187X0010B2	29	48	1	7	-36	+14	+16
390	C	CT9397X0010C2	44	30	2	16	-64	+17.5	+20
820	D	CT9827X0010D2	65	28	4	16	-80	+25	+25
16 V _{DC} AT +85 °C; 10 V _{DC} AT +125 °C; 8 V _{DC} AT +175 °C									
33	A	CT9336X0016A2	10	108	1	2	-28	+14	+16
120	B	CT9127X0016B2	24	60	1	7	-28	+17.5	+20
270	C	CT9277X0016C2	45	36	2	16	-56	+17.5	+20
560	D	CT9567X0016D2	44	28	6	24	-80	+25	+25
25 V _{DC} AT +85 °C; 16 V _{DC} AT +125 °C; 13 V _{DC} AT +175 °C									
22	A	CT9226X0025A2	7	168	1	2	-20	+10.5	+12
100	B	CT9107X0025B2	21	60	1	10	-28	+13	+15
180	C	CT9187X0025C2	29	39	2	18	-48	+13	+15
390	D	CT9397X0025D2	40	29	7	28	-70	+25	+25
40 V _{DC} AT +85 °C; 25 V _{DC} AT +125 °C; 20 V _{DC} AT +175 °C									
12	A	CT9126X0040A2	6	234	1	2	-24	+8	+10
56	B	CT9566X0040B2	14	78	1	9	-28	+13	+15
100	C	CT9107X0040C2	18	48	2	17	-40	+13	+15
220	D	CT9227X0040D2	27	31	8	32	-55	+25	+25
63 V _{DC} AT +85 °C; 40 V _{DC} AT +125 °C; 32 V _{DC} AT +175 °C									
8.2	A	CT9825X0063A2	4.5	330	1	2	-24	+8	+9
39	B	CT9396X0063B2	12	108	1	9	-28	+10.5	+12
68	C	CT9686X0063C2	13	60	2	16	-32	+10.5	+12
150	D	CT9157X0063D2	18	34	8	32	-40	+20	+20
80 V _{DC} AT +85 °C; 50 V _{DC} AT +125 °C; 40 V _{DC} AT +175 °C									
6.8	A	CT9685X0080A2	5	360	1	2	-20	+8	+9
33	B	CT9336X0080B2	10	108	1	10	-24	+10.5	+15
56	C	CT9566X0080C2	11	72	2	17	-28	+10.5	+15
100	D	CT9107X0080D2	12	36	9	36	-35	+20	+20
100 V _{DC} AT +85 °C; 63 V _{DC} AT +125 °C; 50 V _{DC} AT +175 °C									
4.7	A	CT9475X0100A2	3	600	1	2	-16	+7	+8
22	B	CT9226X0100B2	8	132	1	9	-16	+7	+8
47	C	CT9476X0100C2	8	84	2	17	-20	+7	+8
82	D	CT9826X0100D2	10	40	9	36	-25	+15	+15
125 V _{DC} AT +85 °C; 80 V _{DC} AT +125 °C; 63 V _{DC} AT +175 °C									
3.9	A	CT9395X0125A2	3.5	720	1	2	-16	+7	+8
15	B	CT9156X0125B2	6	200	1	7	-16	+7	+8
27	C	CT9276X0125C2	6	106	2	13	-16	+7	+8
56	D	CT9566X0125D2	7	58	10	40	-25	+15	+15



EXTENDED RATINGS CT9

CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DF AT +20 °C (%)	MAX. IMP. AT -55 °C 100 Hz (Ω)	MAX. DCL (μA) AT		MAX. CAPACITANCE CHANGE (%) AT		
					+20 °C	+85 °C +125 °C	-55 °C	+85 °C	+125 °C
6.3 V _{DC} AT +85 °C; 4 V _{DC} AT +125 °C; 3 V _{DC} AT +175 °C									
180	A	CT9187X06R3A2	30	55	1.0	10	-60	+13	+16
820	B	CT9827X06R3B2	115	22	2.0	17	-88	+16	+20
1500	C	CT9158X06R3C2	115	22	6.0	25	-90	+20	+25
2200	D	CT9228X06R3D2	125	16	6.0	25	-90	+25	+70
10 V _{DC} AT +85 °C; 6.3 V _{DC} AT +125 °C; 5 V _{DC} AT +175 °C									
150	A	CT9157X0010A2	25	65	1.0	10	-55	+13	+16
560	B	CT9567X0010B2	80	34	2.0	17	-77	+16	+20
1200	C	CT9128X0010C2	95	22	3.0	25	-88	+20	+25
1500	D	CT9158X0010D2	85	18	6.0	25	-88	+25	+30
16 V _{DC} AT +85 °C; 10 V _{DC} AT +125 °C; 8 V _{DC} AT +175 °C									
100	A	CT9107X0016A2	25	88	1.0	10	-44	+13	+16
390	B	CT9397X0016B2	55	38	2.0	17	-66	+16	+20
820	C	CT9827X0016C2	85	27	4.0	25	-77	+20	+25
1000	D	CT9108X0016D2	60	21	6.0	35	-80	+30	+30
25 V _{DC} AT +85 °C; 16 V _{DC} AT +125 °C; 13 V _{DC} AT +175 °C									
68	A	CT9686X0025A2	17	110	1.0	10	-40	+12	+15
270	B	CT9277X0025B2	38	40	2.0	17	-62	+13	+16
560	C	CT9567X0025C2	58	25	5.0	35	-72	+20	+25
680	D	CT9687X0025D2	38	24	6.0	35	-80	+25	+30
40 V _{DC} AT +85 °C; 25 V _{DC} AT +125 °C; 20 V _{DC} AT +175 °C									
39	A	CT9396X0040A2	12	140	2.0	10	-35	+10	+12
150	B	CT9157X0040B2	22	50	4.0	35	-52	+13	+16
330	C	CT9337X0040C2	22	30	6.0	40	-60	+20	+25
470	D	CT9477X0040D2	35	28	6.0	40	-70	+25	+30
63 V _{DC} AT +85 °C; 40 V _{DC} AT +125 °C; 32 V _{DC} AT +175 °C									
27	A	CT9276X0063A2	8.0	180	2.0	15	-24	+10	+12
100	B	CT9107X0063B2	15	70	4.0	25	-36	+12	+15
220	C	CT9227X0063C2	23	36	5.0	35	-40	+16	+20
270	D	CT9277X0063D2	26	35	6.0	40	-65	+25	+30
80 V _{DC} AT +85 °C; 50 V _{DC} AT +125 °C; 40 V _{DC} AT +175 °C									
22	A	CT9226X0080A2	6.0	190	2.0	15	-19	+10	+12
82	B	CT9826X0080B2	12	80	4.0	25	-30	+12	+15
180	C	CT9187X0080C2	19	36	5.0	40	-35	+16	+20
220	D	CT9227X0080D2	21	30	6.0	40	-60	+20	+25
100 V _{DC} AT +85 °C; 63 V _{DC} AT +125 °C; 50 V _{DC} AT +175 °C									
10	A	CT9106X0100A2	4.0	250	2.0	15	-17	+10	+12
39	B	CT9396X0100B2	7.0	96	4.0	30	-20	+12	+15
68	C	CT9686X0100C2	8.0	50	5.0	50	-30	+14	+16
120	D	CT9127X0100D2	15	36	6.0	50	-40	+15	+20
125 V _{DC} AT +85 °C; 80 V _{DC} AT +125 °C; 63 V _{DC} AT +175 °C									
6.8	A	CT9685X0125A2	4.0	360	2.0	15	-14	+10	+12
27	B	CT9276X0125B2	5.0	110	4.0	30	-18	+12	+15
47	C	CT9476X0125C2	6.0	65	5.0	50	-26	+16	+16
82	D	CT9826X0125D2	8.0	40	6.0	50	-30	+16	+17



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.