





** Bags are printed (hot stamp or thermal) with an ESD protective symbol and a lot code for traceability. **



Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades.

Protektive Pak bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag.
See Shielding Bag Storage at [TB-7057](#).

STATSHIELD® METAL-IN SERIES



Specifications:

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20)
ANSI/ESD S11.4

Electrical Properties

Surface Resistance:

Outer Surface
Inner Surface
Discharge Shielding
Charge Generation

Typical Values

1 x 10⁴ to < 1 x 10¹¹ ohms
1 x 10⁴ to < 1 x 10¹¹ ohms
<20 nJ
Teflon: 0.09 nC/sq. in.
Quartz: 0.01 nC/sq. in.
<30 volts

Capacitance Probe (to dissipate 1 KV)

Physical Properties

Film Thickness
Width (Inside Dimensions)
Length (Inside Dimensions)
Light Transmission
Heat Seal
Tensile Strength
Puncture Resistance
Non-corrosive
Silicone
Marking Adhesion

Nominal 0.0030" (0.0762mm) ±10%
Nominal -0" / + 0.125"
Nominal ± 0.125"
>40% (Tobias)
>10 lbs/in
4600 PSI, 32 MPa
>10 lbs
Pass
Not detected
Pass

Chemical Properties

Corrosion

No effect on aluminum, copper, silver, Sn-Pb coated foil, stainless steel, low carbon steel

Meets Requirements of:

ESD Protective Packaging
Level 3 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11
ANSI/ESD STM11.11
ANSI/ESD STM11.31, EIA 541
Modified Incline Plane
Modified Incline Plane
ANSI/EIA-541/Appendix E, 1kV Discharge

MIL-STD-3010, 1003

ASTM D-1003
375°F, 1/2 sec 60 psi
ASTM 882
MIL-STD-3010, 2065
MIL-STD-3010, M3005
ASTM E168
IPC-TM-650 2.4.1

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

1. Low charge generation
2. Dissipative or conductive materials for intimate contact
3. A structure that provides electrostatic discharge shielding."

RoHS, REACH and Conflict Minerals Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement:
[Regulatory_Statement_Statshield_Bags.pdf](#)

See Protektive Pak's Limited Warranty:
[ProtektivePak.com/Limited-Warranty](#)

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc.

See Bag Selection Chart Click [HERE](#).

Specifications and procedures subject to change without notice.



Made in the
United States of America

STATSHIELD® BAG, SHIELDING, METAL-IN, 0.0030" (0.0762mm)

PROTEKTIVE PAK

13250 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
[ProtektivePak.com](#)

DRAWING NUMBER
48700

DATE:
September
2021

PROTEKTIVE PAK