



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1848 Integrated Circuit Stepping Motor Driver

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}	40V
Output Current, I_O	1.7A
Junction Temperature, T_J	+125°C
Operating Temperature Range, T_{opr}	-20° to +80°C
Storage Temperature Range, T_{stg}	-30° to +100°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Voltage	V_{CC}		20	24	30	V
Output Current	I_O		0.2	–	1.5	A
Excitation Signal Input Current	I_{IN}		–	–	5.0	mA

Signal Input of Phase Change:

ON			OFF
Output Current (A/ Φ)	Minimum Input Voltage (Volts)	Minimum Input Current (mA)	Maximum Input Voltage (V)
0.2	2.7	1.0	0.8
0.5	3.1	1.2	
1.0	3.6	1.4	
1.5	4.5	2.0	

Output Current:

Output Current, I_O (A/ Φ)	R_X (Ω)
0.31 to 0.39	200
0.95 to 1.05	1.4k

Pin Connection Diagram (Front View)

18	V _{CC}
17	Output B $\bar{B}$
16	Output $\bar{B}$
15	Active High Input $\bar{B}$
14	Output B
13	Excitment Input B
12	GND
11	GND
10	Active High Input $\bar{A}$
9	Output $\bar{A}$
8	Excitment Input A
7	Output A
6	Output A $\bar{A}$
5	I _{CC}
4	I _{CC}
3	GND
2	I _{CC}
1	Filter

