

Industries

Solutions

Services

Software

Products

Partners

Support

About Us

-Search-

Entire Site

▼ GO

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings
- PDF-Fiber Optic ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Product On-Line Catalog > Search Results >

Your search criteria matched only one product, shown below

F98D5-5M3Y



- Pass all TIA/EIA-568-B.3 performance requirements
- FOCIS-5 compliant
- 100% factory inspected end face geometry (SC, ST, and FJ® end faces are 100% inspected in compliance with Telcordia GR-326-CORE, Issue 3)
- Insertion loss per mated pair: 0.50dB typical; 0.75dB max.
- 8-degree APC polish (55dB minimum Return Loss) on singlemode MTP* and UPC polish (55dB minimum Return Loss) on singlemode SC and ST satisfy high-speed network application requirements
- Factory terminated and 100% tested for insertion loss and return loss
- Insertion loss and return loss data recorded for every singlemode cable assembly
- Lifetime traceability of test data to a Q.C. number on each cable assembly
- *MTP is a registered trademark of US Conec Ltd.

Part Number	F98D5-5M3Y
RoHS Compliancy Status	Compliant
Note	F98D5-5M3Y replaces F98D5-5M3
Part Description	Female MTP* to female MTP* 8-fiber interconnect cable assembly (one female MTP* connector on each end on ribbon interconnect cable) = $9/125\mu m$. Outside diameter: $5mm \times 2.5mm$.
Product Type	MTP* Interconnect Cable Assemblies
Length (m)	3
Fiber Compatibility	9/125µm
Fiber Type	Singlemode
Cable Color	Yellow
Cable Type	Duplex
CE Compliant	No
Connector 1 Type	MTP* Connector
Connector 2 Type	MTP* Connector
End Configurations	MTP* to MTP*
Fiber Count	8
Fiber Count Pricing Description	8 PC 8-Fiber Singlemode MTP*-MTP* 9μm 3m
Pricing Description	PC 8-Fiber Singlemode MTP*-MTP* 9µm 3m
Pricing DescriptionMin. Order UOM	PC 8-Fiber Singlemode MTP*-MTP* 9µm 3m PC

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.