

3M™ ROUND CONDUCTOR FLAT CABLE, 3756 SERIES
.025" 30 AWG STRANDED, TPE

ORDERING INFORMATION

3756/XX XX

BLANK = STANDARD
C = CANADIAN CERTIFIED
VERSION

NUMBER OF CONDUCTORS
(SEE TABLE)

BLANK = STANDARD
SF = SPLICE FREE

NOTE:
AVAILABLE IN STANDARD 100 FT OR 300 FT ROLLS. PLEASE
SPECIFY WHEN ORDERING. CONTACT 3M FOR AVAILABILITY
OF ADDITIONAL CONDUCTOR COUNTS AND/OR CUSTOM ROLL
LENGTHS.

TABLE 1			
NUMBER OF CONDUCTORS	3M PART NUMBER	DIMENSION A	DIMENSION B
10	3756/10	0.250±.006 [6.35]	0.225±.004 [5.72]
12	3756/12	0.300±.006 [7.62]	0.275±.004 [6.99]
14	3756/14	0.350±.006 [8.89]	0.325±.004 [8.26]
16	3756/16	0.400±.006 [10.16]	0.375±.004 [9.53]
20	3756/20	0.500±.006 [12.70]	0.475±.004 [12.07]
26	3756/26	0.650±.006 [16.51]	0.625±.004 [15.88]
30	3756/30	0.750±.009 [19.05]	0.725±.006 [18.42]
34	3756/34	0.850±.009 [21.59]	0.825±.006 [20.96]
36	3756/36	0.900±.009 [22.86]	0.875±.006 [22.23]
40	3756/40	1.000±.009 [25.40]	0.975±.006 [24.77]
50	3756/50	1.250±.009 [31.75]	1.225±.006 [31.12]
60	3756/60	1.500±.012 [38.10]	1.475±.009 [37.47]
68	3756/68	1.700±.012 [43.18]	1.675±.009 [42.55]
80	3756/80	2.000±.015 [50.80]	1.975±.011 [50.17]
100	3756/100	2.500±.015 [63.50]	2.475±.012 [62.87]



3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373




AWM 20297 105C 150V HB 3M NU



AWM 1A 105C 150V FT2 EU <50V

CANADIAN OPTION

"PRINTING ILLUSTRATION"



PHYSICAL :

INSULATION
MATERIAL: THERMOPLASTIC ELASTOMER, TPE (TPO TYPE)
COLOR: GRAY
MARKING
STANDARD: NONE
CANADIAN: SEE "PRINTING ILLUSTRATION" VIEW

CONDUCTORS
MATERIAL: 30 AWG, 7 X 38AWG [7 X Ø0.102]
TINNED STRANDED COPPER

ELECTRICAL :

VOLTAGE RATING: USA 150V CANADIAN 150V EU: <50V
INSULATION RESISTANCE: >1 X 10¹⁰Ω/10ft. [3m]

CHARACTERISTIC IMPEDANCE:	UNBALANCED 82Ω	BALANCED 138Ω
CAPACITANCE:	17.3 pF/ft [56.8 pF/m]	10.0 pF/ft [32.8 pF/m]
INDUCTANCE:	0.12μH/ft [0.38μH/m]	0.19μH/ft [0.62μH/m]
PROPAGATION DELAY:	1.42 ns/ft [4.66 ns/m]	1.38 ns/ft [4.53 ns/m]
VELOCITY OF PROPAGATION:	72%	74%

NOTE: UNBALANCED IS MEASURED BETWEEN GROUND-SIGNAL-GROUND CONDUCTORS.
BALANCED IS MEASURED BETWEEN SIGNAL CONDUCTORS WITHIN A PAIR.

ENVIRONMENTAL :

TEMPERATURE RATING: -40°C TO +105°C
FLAMMABILITY RATING: USA: UL HORIZONTAL CANADA: FT2

- NOTES
- REGULATORY INFORMATION:
FOR REGULATORY INFORMATION
ABOUT THIS PRODUCT, VISIT
3m.com/regs OR CONTACT YOUR
3M REPRESENTATIVE.

UL FILE NO: E42769.
STYLE NO: 20297
 - .025 INCH WIRE SPACING
INCREASES SIGNAL DENSITY
 - TPE INSULATION PROVIDES
EXCELLENT TRANSMISSION
PROPERTIES.
 - 30 AWG STRANDED CONDUCTORS ON
.025 INCH WIRE SPACING IS
DESIGNED FOR MASS TERMINATION
AND FLEXIBILITY.
 - MEETS THE SCSI-3 CHARACTERISTIC
IMPEDANCE REQUIREMENTS.
 - BLUE MARKING ON ONE EDGE OF
CABLE DESIGNATES WIRE #1.

DIMENSIONS: INCH [MM]

INCH [MM]			
TOLERANCE - UNLESS NOTED			
	.X	.XX	.XXX
INCH	±.1	±.05	±.010
[] = DIM. FOR REFERENCE ONLY			

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
CODES		L	SCHMIDT	DEC 14, 2021	MFG	DATE
		CHKD	T PLEPYS	JAN 04, 2022	APPRVL	DATE
DIVISION	DIVISION CODE	© 3M COPYRIGHT 2022				
DO NOT SCALE DRAWING	SCALE 4/1	TOLERANCES EXCEPT AS NOTED				
THIRD ANGLE PROJECTION	INTERPRET PER ASME Y14.5 - 2018	INCHES .0 ±.1 .00 ±.02 .000 ±.005 .0000 ±.0002				
MAX SURFACE ROUGHNESS 125 ✓	ALL SURFACES ✓ MARKED ONLY	MILLIMETERS 0 ± .0 ±.00 ±.000 ±.000				
		CAGE NUMBER		DRAWING NO.		
		D		78-5100-0508-1		
		MODEL		REV. H		

1/20/2022 -- UTC Off-set (hrs) 6

3M™ ROUND CONDUCTOR FLAT CABLE, 3756 SERIES
 .025" 30 AWG STRANDED, TPE

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.


Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Business Center
Electronics Materials Solutions Division
13011 McCallen Pass, BLDG C
Austin, TX 78753-5380
1-800-225-5373
www.3M.com/interconnect

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3M.com/interconnect>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
ADDS CODES		 ADDS CODES 		DRFT	L SCHMIDT	DATE DEC 14, 2021		MFG	DATE
 ADDS CODES 		 ADDS CODES 		CHD	T PLEPYS	DATE JAN 04, 2022		APPL	DATE
DIVISION		DIVISION CODE		3M 3M Center St. Paul, MN 55144		© 3M COPYRIGHT 2022 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or copied other than for 3M authorized purposes.			
DO NOT SCALE DRAWING		SCALE 4 1							
		INCHES .0 .00 ±.1 .00 ±.02 .000 ±.005 .0000 ±.0002		TITLE ROUND CONDUCTOR FLAT CABLE SERIES 3756 .025" 30AWG STRANDED					
THIRD ANGLE PROJECTION		MILLIMETERS 0 .0 .00 ±.1 .00 ±.02 .000 ±.005							
INTERPRET PER ASME Y14.5 - 2018		 MILLIMETERS 0 .0 .00 ±.1 .00 ±.02 .000 ±.005 		CASE NUMBER D 78-5100-0508-1		DRAWING NO. H		REV. 1	
MAX SURFACE ROUGHNESS 125		☐ ALL SURFACES ☒ MARKED ONLY		MODEL		DET: ☐ YES ☒ NO SHT 2 OF 4			
		ANGLES ± 1°							