

NOTES:

1. MATERIALS AND FINISHES:

HD-BNC STR PLUG - BRASS, NICKEL PLATED
BNC STR PLUG - BRASS, NICKEL PLATED
CABLE - BELDEN 1694A

2. ELECTRICAL:

A. IMPEDANCE: 75 OHM
B. FREQUENCY RANGE: DC - 3.0 GHz

3. MECHANICAL:

A. TEMPERATURE RANGE : 0°C TO +50°C

4. PACKAGING:

A. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-850-131-XXX AND DATE CODE"

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	1/30/13	49339	KR

SCALE 0.500

LENGTH "L" SEE TABLE

3.00 ± 0.197
[76.20 ± 5.00 MM]

LABEL WITH:
"AMPHENOLRF
95-850-131-XXX WWWW"

1.52 ± 0.05
[38.61 ± 1.27 MM]

BELDEN 1694A CABLE

BNC PLUG

HD-BNC PLUG

S.NO	AMPHENOL RF PART NUMBER	LENGTH "L"
1	95-850-131-006	6.00 ^{+0.30} ₋₀ [152.40 ^{+7.62} ₋₀ MM]
2	95-850-131-012	12.00 ^{+0.60} ₋₀ [304.80 ^{+15.24} ₋₀ MM]
3	95-850-131-018	18.00 ^{+0.90} ₋₀ [457.20 ^{+22.86} ₋₀ MM]
4	95-850-131-036	36.00 ^{+1.80} ₋₀ [914.40 ^{+45.72} ₋₀ MM]

95-850-131-XXX, WHERE XXX REPRESENTS THE LENGTH OF THE CABLE ASSEMBLY.
CUSTOM LENGTHS ARE AVAILABLE ON REQUEST.

DESIGN REQUIREMENTS:

☒ FREQUENCY : DC TO 3 GHz

☐ VSWR : 1 MAX

☐ INS. LOSS : dB MAX

☒ CONTINUITY

☒ HI-POT: 750 VRMS

☐ OTHER

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL
SEE NOTES

REFERENCE
EAR #

CONFIGURATION LEVEL: In Work

FINISH

DRAWN
ABHAYA KISHORE

ENGINEER
ABHAYA KISHORE

APPROVED
K. CAPOZZI

CAD FILE

DATE
19-Jan-12

DATE
19-Jan-12

DATE
1/30/13

TITLE
HD-BNC STR PLUG TO
BNC STR CRIMP PLUG
USING BELDEN 1694A
CABLE, VARIOUS LENGTH

SCALE: 2.0:1.0

SHEET 2 OF 2

DWG SIZE
B

REV
A

Amphenol RF
www.amphenolrf.com

DRAWING NO.95-850-131-XXX

ITEM NO.95-850-131-XXX

PART NO.95-850-131-XXX