

2A, 40V - 200V Surface Mount Schottky Barrier Rectifiers

FEATURES

- Low power loss, high efficiency
- Ideal for automated placement
- Guard ring for over-voltage protection
- High surge current capability
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21


**HALOGEN
FREE**

MECHANICAL DATA

SOD-123W

Case: SOD-123W

Molding compound: UL flammability classification rating 94V-0

Moisture sensitivity level: level 1, per J-STD-020

Part no. with suffix "H" means AEC-Q101 qualified

Packing code with suffix "G" means green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 2 whisker test

Polarity: Indicated by cathode band

Weight: 16 mg (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)									
PARAMETER	SYMBOL	SS24 LW	SS26 LW	SS210 LW	SS215 LW	SS220 LW	UNIT		
Marking Code		24LW	26LW	20LW	2ALW	2BLW			
Maximum repetitive peak reverse voltage	V _{RRM}	40	60	100	150	200	V		
Maximum RMS voltage	V _{RMS}	28	42	70	105	140	V		
Maximum DC blocking voltage	V _{DC}	40	60	100	150	200	V		
Maximum average forward rectified current	I _{F(AV)}	2					A		
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	50					A		
Maximum instantaneous forward voltage (Note 1) @ 2 A	V _F	0.55	0.70	0.85	0.95		V		
Maximum reverse current @ rated V _R T _J =25°C	I _R	200		20	10		µA		
Typical thermal resistance	R _{θJL} R _{θJA}	25 80					°C/W		
Operating junction temperature range	T _J	- 55 to +125		- 55 to +150			°C		
Storage temperature range	T _{STG}	- 55 to +125		- 55 to +150			°C		

Note 1: Pulse test with PW=300µs, 1% duty cycle

ORDERING INFORMATION

PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
SS2xLW (Note 1, 2)	H	RV	G	SOD-123W	3,000 / 7" Plastic reel
		RQ			10,000 / 13" Paper reel

Note 1: "x" defines voltage from 40V (SS24LW) to 200V (SS220LW)

Note 2: Whole series with green compound (halogen-free)

EXAMPLE

EXAMPLE P/N	PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
SS24LWHRVG	SS24LW	H	RV	G	AEC-Q101 qualified Green compound







RATINGS AND CHARACTERISTICS CURVES ($T_A=25^\circ\text{C}$ unless otherwise noted)
FIG.1 FORWARD CURRENT DERATING CURVE

FIG. 2 TYPICAL FORWARD CHARACTERISTICS

FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

FIG. 4 TYPICAL REVERSE CHARACTERISTICS


FIG. 5 TYPICAL JUNCTION CAPACITANCE




PACKAGE OUTLINE DIMENSIONS

SOD-123W


DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
B	1.70	1.90	0.067	0.075
C	2.60	2.90	0.102	0.114
D	0.10	0.22	0.004	0.009
E	0.90	1.02	0.035	0.040
F	0.90	1.05	0.035	0.041
G	3.60	3.80	0.142	0.150
H	0.50	0.85	0.020	0.033
I	0.00	0.10	0.000	0.004

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.4	0.055
B	1.2	0.047
C	3.1	0.122
D	1.9	0.075
E	4.3	0.169

MARKING DIAGRAM



P/N = Marking Code
G = Green compound Code
YW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.