

# NCS2552

## 750 MHz Voltage Feedback Op Amp with Fast Enable Feature


NCS2552 is a 750 MHz voltage feedback monolithic operational amplifier featuring high slew rate and low differential gain and phase error. The voltage feedback architecture allows for a superior bandwidth and low power consumption. This device features an enable pin.

### Features

- -3.0 dB Small Signal BW ( $A_V = +2.0$ ,  $V_O = 0.5 V_{p-p}$ ) 750 MHz Typ
- Slew Rate 1700 V/ $\mu$ s
- Fast Enable Time 5.0 ns
- Supply Current 13 mA
- Input Referred Voltage Noise 5.0 nV/ $\sqrt{\text{Hz}}$
- THD -64 dBc ( $f = 5.0 \text{ MHz}$ ,  $V_O = 2.0 V_{p-p}$ )
- Output Current 100 mA
- Pin Compatible with EL5157, AD8057
- This is a Pb-Free Device

### Applications

- Line Drivers
- Radar/Communication Receivers



**Figure 1. Frequency Response:**  
Gain (dB) vs. Frequency  $A_V = +2.0$




**ON Semiconductor®**

<http://onsemi.com>

### MARKING DIAGRAM




**SOT23-6**  
(TSOP-6)  
SN SUFFIX  
CASE 318G



YF2, N2552 = NCS2552  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

### SOT23-6 PINOUT



### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 12 of this data sheet.

PIN FUNCTION DESCRIPTION

| Pin<br>(SOT23/SC70) | Symbol | Function              | Equivalent Circuit |
|---------------------|--------|-----------------------|--------------------|
| 1                   | OUT    | Output                |                    |
| 2                   | VEE    | Negative Power Supply |                    |
| 3                   | +IN    | Non-inverted Input    |                    |
| 4                   | -IN    | Inverted Input        | See Above          |
| 6                   | VCC    | Positive Power Supply |                    |
| 5                   | EN     | Enable                |                    |

ENABLE PIN TRUTH TABLE

|        | High     | Low*    |
|--------|----------|---------|
| Enable | Disabled | Enabled |

\*Default open state




Figure 2. Simplified Device Schematic

## ATTRIBUTES

| Characteristics                                 | Value                |
|-------------------------------------------------|----------------------|
| ESD                                             |                      |
| Human Body Model                                | 2.0 kV               |
| Machine Model                                   | 200 V                |
| Charged Device Model                            | 1.0 kV               |
| Moisture Sensitivity (Note 1)                   | Level 1              |
| Flammability Rating      Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in |

1. For additional information, see Application Note AND8003/D.

## MAXIMUM RATINGS

| Parameter                             | Symbol          | Rating      | Unit |
|---------------------------------------|-----------------|-------------|------|
| Power Supply Voltage                  | $V_S$           | 11          | Vdc  |
| Input Voltage Range                   | $V_I$           | $\leq V_S$  | Vdc  |
| Input Differential Voltage Range      | $V_{ID}$        | $\leq V_S$  | Vdc  |
| Output Current                        | $I_O$           | 100         | mA   |
| Maximum Junction Temperature (Note 2) | $T_J$           | 150         | °C   |
| Operating Ambient Temperature         | $T_A$           | -40 to +85  | °C   |
| Storage Temperature Range             | $T_{stg}$       | -60 to +150 | °C   |
| Power Dissipation                     | $P_D$           | (See Graph) | mW   |
| Thermal Resistance, Junction-to-Air   | $R_{\theta JA}$ | 158         | °C/W |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

2. Power dissipation must be considered to ensure maximum junction temperature ( $T_J$ ) is not exceeded.

## MAXIMUM POWER DISSIPATION

The maximum power that can be safely dissipated is limited by the associated rise in junction temperature. For the plastic packages, the maximum safe junction temperature is 150°C. If the maximum is exceeded momentarily, proper circuit operation will be restored as soon as the die temperature is reduced. Leaving the device in the “overheated” condition for an extended period can result in device damage.




Figure 3. Power Dissipation vs. Temperature

# NCS2552

**AC ELECTRICAL CHARACTERISTICS** ( $V_{CC} = +5.0\text{ V}$ ,  $V_{EE} = -5.0\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $R_L = 150\ \Omega$  to GND,  $R_F = 150\ \Omega$ ,  $A_V = +2.0$ , Enable is left open, unless otherwise specified).

| Symbol | Characteristic | Conditions | Min | Typ | Max | Unit |
|--------|----------------|------------|-----|-----|-----|------|
|--------|----------------|------------|-----|-----|-----|------|

## FREQUENCY DOMAIN PERFORMANCE

|                     |                                                         |                                                                                        |  |            |  |     |
|---------------------|---------------------------------------------------------|----------------------------------------------------------------------------------------|--|------------|--|-----|
| BW                  | Bandwidth<br>3.0 dB Small Signal<br>3.0 dB Large Signal | $A_V = +2.0$ , $V_O = 0.5\text{ V}_{p-p}$<br>$A_V = +2.0$ , $V_O = 2.0\text{ V}_{p-p}$ |  | 750<br>350 |  | MHz |
| GF <sub>0.1dB</sub> | 0.1 dB Gain Flatness<br>Bandwidth                       | $A_V = +2.0$                                                                           |  | 40         |  | MHz |
| dG                  | Differential Gain                                       | $A_V = +2.0$ , $R_L = 150\ \Omega$ , $f = 3.58\text{ MHz}$                             |  | 0.07       |  | %   |
| dP                  | Differential Phase                                      | $A_V = +2.0$ , $R_L = 150\ \Omega$ , $f = 3.58\text{ MHz}$                             |  | 0.01       |  | °   |

## TIME DOMAIN RESPONSE

|             |                       |                                                    |  |      |  |                  |
|-------------|-----------------------|----------------------------------------------------|--|------|--|------------------|
| SR          | Slew Rate             | $A_V = +2.0$ , $V_{step} = 2.0\text{ V}$           |  | 1700 |  | V/ $\mu\text{s}$ |
| $t_s$       | Settling Time<br>0.1% | $A_V = +2.0$ , $V_{step} = 2.0\text{ V}$           |  | 10   |  | ns               |
| $t_r$ $t_f$ | Rise and Fall Time    | (10%–90%) $A_V = +2.0$ , $V_{step} = 2.0\text{ V}$ |  | 2.0  |  | ns               |
| $t_{ON}$    | Turn-on Time          |                                                    |  | 5.0  |  | ns               |
| $t_{OFF}$   | Turn-off Time         |                                                    |  | 15   |  | ns               |

## HARMONIC/NOISE PERFORMANCE

|       |                                |                                                   |  |     |  |                        |
|-------|--------------------------------|---------------------------------------------------|--|-----|--|------------------------|
| THD   | Total Harmonic Distortion      | $f = 5.0\text{ MHz}$ , $V_O = 2.0\text{ V}_{p-p}$ |  | –64 |  | dB                     |
| HD2   | 2nd Harmonic Distortion        | $f = 5.0\text{ MHz}$ , $V_O = 2.0\text{ V}_{p-p}$ |  | –65 |  | dBc                    |
| HD3   | 3rd Harmonic Distortion        | $f = 5.0\text{ MHz}$ , $V_O = 2.0\text{ V}_{p-p}$ |  | –75 |  | dBc                    |
| IP3   | Third-Order Intercept          | $f = 10\text{ MHz}$ , $V_O = 1.0\text{ V}_{p-p}$  |  | 40  |  | dBm                    |
| SFDR  | Spurious-Free Dynamic<br>Range | $f = 5.0\text{ MHz}$ , $V_O = 2.0\text{ V}_{p-p}$ |  | 55  |  | dBc                    |
| $e_N$ | Input Referred Voltage Noise   | $f = 1.0\text{ MHz}$                              |  | 5.0 |  | nV/ $\sqrt{\text{Hz}}$ |
| $i_N$ | Input Referred Current Noise   | $f = 1.0\text{ MHz}$                              |  | 4.0 |  | pA/ $\sqrt{\text{Hz}}$ |

# NCS2552

**DC ELECTRICAL CHARACTERISTICS** ( $V_{CC} = +5.0\text{ V}$ ,  $V_{EE} = -5.0\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $R_L = 150\ \Omega$  to GND,  $R_F = 150\ \Omega$ ,  $A_V = +2.0$ , Enable is left open, unless otherwise specified). Closed Loop  
Open Loop

| Symbol | Characteristic | Conditions | Min | Typ | Max | Unit |
|--------|----------------|------------|-----|-----|-----|------|
|--------|----------------|------------|-----|-----|-----|------|

## DC PERFORMANCE

|                          |                                              |                    |     |           |          |                              |
|--------------------------|----------------------------------------------|--------------------|-----|-----------|----------|------------------------------|
| $V_{IO}$                 | Input Offset Voltage                         |                    | -10 | 0         | +10      | mV                           |
| $\Delta V_{IO}/\Delta T$ | Input Offset Voltage Temperature Coefficient |                    |     | 6.0       |          | $\mu\text{V}/^\circ\text{C}$ |
| $I_{IB}$                 | Input Bias Current                           | $V_O = 0\text{ V}$ |     | $\pm 3.2$ | $\pm 20$ | $\mu\text{A}$                |
| $\Delta I_{IB}/\Delta T$ | Input Bias Current Temperature Coefficient   | $V_O = 0\text{ V}$ |     | $\pm 40$  |          | $\text{nA}/^\circ\text{C}$   |
| $V_{IH}$                 | Input High Voltage (Enable)<br>(Note 3)      |                    | 3.0 |           |          | V                            |
| $V_{IL}$                 | Input Low Voltage (Enable)<br>(Note 3)       |                    |     |           | 1.0      | V                            |

## INPUT CHARACTERISTICS

|          |                                          |             |           |           |  |            |
|----------|------------------------------------------|-------------|-----------|-----------|--|------------|
| $V_{CM}$ | Input Common Mode Voltage Range (Note 3) |             | $\pm 3.0$ | $\pm 3.2$ |  | V          |
| CMRR     | Common Mode Rejection Ratio              | (See Graph) | 40        | 50        |  | dB         |
| $R_{IN}$ | Input Resistance                         |             |           | 4.5       |  | M $\Omega$ |
| $C_{IN}$ | Differential Input Capacitance           |             |           | 1.0       |  | pF         |

## OUTPUT CHARACTERISTICS

|           |                      |                          |           |           |  |          |
|-----------|----------------------|--------------------------|-----------|-----------|--|----------|
| $R_{OUT}$ | Output Resistance    | Closed Loop<br>Open Loop |           | 0.1<br>13 |  | $\Omega$ |
| $V_O$     | Output Voltage Range |                          | $\pm 3.0$ | $\pm 4.0$ |  | V        |
| $I_O$     | Output Current       |                          | $\pm 50$  | $\pm 100$ |  | mA       |

## POWER SUPPLY

|             |                                 |             |     |     |     |    |
|-------------|---------------------------------|-------------|-----|-----|-----|----|
| $V_S$       | Operating Voltage Supply        |             |     | 10  |     | V  |
| $I_{S,ON}$  | Power Supply Current – Enabled  |             | 5.0 | 13  | 17  | mA |
| $I_{S,OFF}$ | Power Supply Current – Disabled |             |     | 0.5 | 0.8 | mA |
| PSRR        | Power Supply Rejection Ratio    | (See Graph) | 40  | 56  |     | dB |

3. Guaranteed by design and/or characterization.

# NCS2552

**AC ELECTRICAL CHARACTERISTICS** ( $V_{CC} = +2.5\text{ V}$ ,  $V_{EE} = -2.5\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $R_L = 150\ \Omega$  to GND,  $R_F = 150\ \Omega$ ,  $A_V = +2.0$ , Enable is left open, unless otherwise specified).

| Symbol | Characteristic | Conditions | Min | Typ | Max | Unit |
|--------|----------------|------------|-----|-----|-----|------|
|--------|----------------|------------|-----|-----|-----|------|

## FREQUENCY DOMAIN PERFORMANCE

|                     |                                                         |                                                                                        |  |            |  |     |
|---------------------|---------------------------------------------------------|----------------------------------------------------------------------------------------|--|------------|--|-----|
| BW                  | Bandwidth<br>3.0 dB Small Signal<br>3.0 dB Large Signal | $A_V = +2.0$ , $V_O = 0.5\text{ V}_{p-p}$<br>$A_V = +2.0$ , $V_O = 1.0\text{ V}_{p-p}$ |  | 550<br>200 |  | MHz |
| GF <sub>0.1dB</sub> | 0.1 dB Gain Flatness<br>Bandwidth                       | $A_V = +2.0$                                                                           |  | 35         |  | MHz |
| dG                  | Differential Gain                                       | $A_V = +2.0$ , $R_L = 150\ \Omega$ , $f = 3.58\text{ MHz}$                             |  | 0.07       |  | %   |
| dP                  | Differential Phase                                      | $A_V = +2.0$ , $R_L = 150\ \Omega$ , $f = 3.58\text{ MHz}$                             |  | 0.02       |  | °   |

## TIME DOMAIN RESPONSE

|             |                       |                                                    |  |     |  |                  |
|-------------|-----------------------|----------------------------------------------------|--|-----|--|------------------|
| SR          | Slew Rate             | $A_V = +2.0$ , $V_{step} = 1.0\text{ V}$           |  | 900 |  | V/ $\mu\text{s}$ |
| $t_s$       | Settling Time<br>0.1% | $A_V = +2.0$ , $V_{step} = 1.0\text{ V}$           |  | 10  |  | ns               |
| $t_r$ $t_f$ | Rise and Fall Time    | (10%–90%) $A_V = +2.0$ , $V_{step} = 1.0\text{ V}$ |  | 1.7 |  | ns               |
| $t_{ON}$    | Turn-on Time          |                                                    |  | 5.0 |  | ns               |
| $t_{OFF}$   | Turn-off Time         |                                                    |  | 15  |  | ns               |

## HARMONIC/NOISE PERFORMANCE

|       |                                |                                                   |  |     |  |                        |
|-------|--------------------------------|---------------------------------------------------|--|-----|--|------------------------|
| THD   | Total Harmonic Distortion      | $f = 5.0\text{ MHz}$ , $V_O = 1.0\text{ V}_{p-p}$ |  | –60 |  | dB                     |
| HD2   | 2nd Harmonic Distortion        | $f = 5.0\text{ MHz}$ , $V_O = 1.0\text{ V}_{p-p}$ |  | –65 |  | dBc                    |
| HD3   | 3rd Harmonic Distortion        | $f = 5.0\text{ MHz}$ , $V_O = 1.0\text{ V}_{p-p}$ |  | –63 |  | dBc                    |
| IP3   | Third-Order Intercept          | $f = 10\text{ MHz}$ , $V_O = 0.5\text{ V}_{p-p}$  |  | 35  |  | dBm                    |
| SFDR  | Spurious-Free Dynamic<br>Range | $f = 5.0\text{ MHz}$ , $V_O = 1.0\text{ V}_{p-p}$ |  | 63  |  | dBc                    |
| $e_N$ | Input Referred Voltage Noise   | $f = 1.0\text{ MHz}$                              |  | 5.0 |  | nV/ $\sqrt{\text{Hz}}$ |
| $i_N$ | Input Referred Current Noise   | $f = 1.0\text{ MHz}$                              |  | 4.0 |  | pA/ $\sqrt{\text{Hz}}$ |

**DC ELECTRICAL CHARACTERISTICS** ( $V_{CC} = +2.5\text{ V}$ ,  $V_{EE} = -2.5\text{ V}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $R_L = 150\ \Omega$  to GND,  $R_F = 150\ \Omega$ ,  $A_V = +2.0$ , Enable is left open, unless otherwise specified).

| Symbol | Characteristic | Conditions | Min | Typ | Max | Unit |
|--------|----------------|------------|-----|-----|-----|------|
|--------|----------------|------------|-----|-----|-----|------|

**DC PERFORMANCE**

|                          |                                              |                    |     |           |          |                              |
|--------------------------|----------------------------------------------|--------------------|-----|-----------|----------|------------------------------|
| $V_{IO}$                 | Input Offset Voltage                         |                    | -10 | 0         | +10      | mV                           |
| $\Delta V_{IO}/\Delta T$ | Input Offset Voltage Temperature Coefficient |                    |     | 6.0       |          | $\mu\text{V}/^\circ\text{C}$ |
| $I_{IB}$                 | Input Bias Current                           | $V_O = 0\text{ V}$ |     | $\pm 3.2$ | $\pm 20$ | $\mu\text{A}$                |
| $\Delta I_{IB}/\Delta T$ | Input Bias Current Temperature Coefficient   | $V_O = 0\text{ V}$ |     | $\pm 40$  |          | $\text{nA}/^\circ\text{C}$   |
| $V_{IH}$                 | Input High Voltage (Enable)<br>(Note 3)      |                    | 1.5 |           |          | V                            |
| $V_{IL}$                 | Input Low Voltage (Enable)<br>(Note 3)       |                    |     |           | 0.5      | V                            |

**INPUT CHARACTERISTICS**

|          |                                          |             |           |           |  |                  |
|----------|------------------------------------------|-------------|-----------|-----------|--|------------------|
| $V_{CM}$ | Input Common Mode Voltage Range (Note 3) |             | $\pm 1.1$ | $\pm 1.6$ |  | V                |
| CMRR     | Common Mode Rejection Ratio              | (See Graph) | 40        | 50        |  | dB               |
| $R_{IN}$ | Input Resistance                         |             |           | 4.5       |  | $\text{M}\Omega$ |
| $C_{IN}$ | Differential Input Capacitance           |             |           | 1.0       |  | pF               |


**OUTPUT CHARACTERISTICS**

|           |                      |                          |           |           |  |          |
|-----------|----------------------|--------------------------|-----------|-----------|--|----------|
| $R_{OUT}$ | Output Resistance    | Closed Loop<br>Open Loop |           | 0.1<br>13 |  | $\Omega$ |
| $V_O$     | Output Voltage Range |                          | $\pm 1.1$ | $\pm 1.6$ |  | V        |
| $I_O$     | Output Current       |                          | $\pm 50$  | $\pm 100$ |  | mA       |


**POWER SUPPLY**

|             |                                 |             |     |      |     |    |
|-------------|---------------------------------|-------------|-----|------|-----|----|
| $V_S$       | Operating Voltage Supply        |             |     | 5.0  |     | V  |
| $I_{S,ON}$  | Power Supply Current – Enabled  |             | 5.0 | 11.5 | 17  | mA |
| $I_{S,OFF}$ | Power Supply Current – Disabled |             |     | 0.5  | 0.8 | mA |
| PSRR        | Power Supply Rejection Ratio    | (See Graph) | 40  | 56   |     | dB |


4. Guaranteed by design and/or characterization.




**Figure 4. Typical Test Setup**  
( $A_V = +2.0$ ,  $R_F = 1.0\text{ k}\Omega$ ,  $R_L = 100\ \Omega$ )




**Figure 5. Frequency Response:**  
Gain (dB) vs. Frequency  
 $A_v = +2.0$




**Figure 6. Frequency Response:**  
Gain (dB) vs. Frequency  
 $A_v = +1.0$




**Figure 7. Large Signal Frequency Response**  
Gain (dB) vs. Frequency



**Figure 8. Small Signal Frequency Response**  
Gain (dB) vs. Frequency



**Figure 9. Small Signal Step Response**  
Vertical: 20 mV/div  
Horizontal: 3 ns/div



**Figure 10. Large Signal Step Response**  
Vertical: 1 V/div  
Horizontal: 3 ns/div




Figure 11. THD, HD2, HD3 vs. Frequency




Figure 12. THD, HD2, HD3 vs. Output Voltage




Figure 13. Input Referred Voltage Noise vs. Frequency




Figure 14. CMRR vs. Frequency




Figure 15. PSRR vs. Frequency




Figure 16. Differential Gain




Figure 17. Differential Phase




Figure 18. Supply Current vs. Power Supply (Enabled)




Figure 19. Supply Current (Disabled)




Figure 20. Output Voltage Swing vs. Supply Voltage




Figure 21. Closed Loop Output Resistance vs. Frequency






Figure 22. Frequency Response vs. Capacitive Load



**Figure 23. Turn ON Time Delay**  
 Vertical: 500 mV/div (Enable), 200 mV/div (Output)  
 Horizontal: 5 ns/div



**Figure 24. Turn OFF Time Delay**  
 Vertical: 500 mV/div (Enable), 200 mV/div (Output)  
 Horizontal: 5 ns/div

### Printed Circuit Board Layout Techniques

Proper high speed PCB design rules should be used for all wideband amplifiers as the PCB parasitics can affect the overall performance. Most important are stray capacitances at the output and inverting input nodes as it can effect peaking and bandwidth. A space (3/16" is plenty) should be left around the signal lines to minimize coupling. Also, signal lines connecting the feedback and gain resistors should be short enough so that their associated inductance does not cause high frequency gain errors. Line lengths less than 1/4" are recommended.

### Video Performance

This device designed to provide good performance with NTSC, PAL, and HDTV video signals. Best performance is obtained with back terminated loads as performance is degraded as the load is increased. The back termination reduces reflections from the transmission line and effectively masks transmission line and other parasitic capacitances from the amplifier output stage.

### ESD Protection

All device pins have limited ESD protection using internal diodes to power supplies as specified in the attributes table (see Figure 25). These diodes provide moderate protection

to input overdrive voltages above the supplies. The ESD diodes can support high input currents with current limiting series resistors. Keep these resistor values as low as possible since high values degrade both noise performance and frequency response. Under closed-loop operation, the ESD diodes have no effect on circuit performance. However, under certain conditions the ESD diodes will be evident. If the device is driven into a slewing condition, the ESD diodes will clamp large differential voltages until the feedback loop restores closed-loop operation. Also, if the device is powered down and a large input signal is applied, the ESD diodes will conduct.

NOTE: Human Body Model for +IN and -IN pins are rated at 0.8kV while all other pins are rated at 2.0kV.





Figure 25. Internal ESD Protection

### ORDERING INFORMATION

| Device       | Package                       | Shipping†        |
|--------------|-------------------------------|------------------|
| NCS2552SNT1G | SOT23-6 (TSOP-6)<br>(Pb-Free) | 3000 Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## PACKAGE DIMENSIONS


TSOP-6  
CASE 318G-02  
ISSUE S

## NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.90        | 1.00 | 1.10 | 0.035  | 0.039 | 0.043 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.25        | 0.38 | 0.50 | 0.010  | 0.014 | 0.020 |
| c   | 0.10        | 0.18 | 0.26 | 0.004  | 0.007 | 0.010 |
| D   | 2.90        | 3.00 | 3.10 | 0.114  | 0.118 | 0.122 |
| E   | 1.30        | 1.50 | 1.70 | 0.051  | 0.059 | 0.067 |
| e   | 0.85        | 0.95 | 1.05 | 0.034  | 0.037 | 0.041 |
| L   | 0.20        | 0.40 | 0.60 | 0.008  | 0.016 | 0.024 |
| HE  | 2.50        | 2.75 | 3.00 | 0.099  | 0.108 | 0.118 |
| θ   | 0°          | —    | 10°  | 0°     | —     | 10°   |

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

## LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative